CREATIVE September 2005 www.woodworksandcrafts.com OUTIVE September 2005 www.woodworksandcrafts.com OUTIVE September 2005 www.woodworksandcrafts.com CRAFTS & CRAFTS

Great Projects!

\$6.49 U.S.A \$8.49 Canada

High Quality Full Size Patterns





Projects in Full Size Pattern Section No. 1 shown on this page.

CONTENIS



Watchful Eyes





Reverent Denomination


Pug Puppies








Three Wildcat Portraits



Scrolling Projects:

Watchful Eyes	6
Screaming Eagle	
Ready for Flight	
Whiskers	
Three Wildcat Portraits	
Engine 86	
Reverent Denomination	
Curly Sue	
The Tree Swing	
Pen and Pencil Boxes Using Through	
Dovetails and Box Joints	32
Fretwork Box	
Mare and Colt: Variations on a Pattern	
Pug Puppies	
Chirping Chickadees Wall Pocket	



Engine 86







Helm's Wheel Intarsia



Curly Sue

CREATIVE WOODWORKS & CRAFTS® September 2005, No.110 Alt American Crafts, Inc. 2005 ALL RICITIS RESERVED ON ENTURE CONTRINES.

Creative Weedworks & Origine (185N-1988-6729) is published sight times a year by All American Creati, Inc. Waterlow Road, Statutings N.J. (1878-4, L.S.A. All rights reserved on entire contents of magazine. We need to so of usooficined material. We reserve the right to edit and publish correspondence unless specific communitary motion nome and address are requested to be withheld. Representation of editoration and evidence of the Euclidean States of University problished. The instructions in this magazine are problemed in good faith and have been the decided by account syllnowing, no somewhat, either expressed or implied, is made nor an accordant by a state of the support of Confess Weekers and address changes to Creative Weekerski & Craftive Research and the confession of the Euclidean Craftive Research and the Confession of Euclidean Craftive Research and the Euclidean Craftive Research and the Confession of Craftive Weekerski & Craftive Research and Craftive Research Researc

Intarsia Project:

Helm's Wheel Intarsia	51
Turkey Beard Holder Intarsia	56

Woodburning Project:

Red-Tail Hawk and the	
Secrets of Feathering	64

Turning Project:

Mini-Lathe	Sarias.	Pockat	Matches		71
MILLEGIES.	20103.	LOCKEL	4 4 CH CH CO	*************	-

Features:

Editorial	9
Wes' Workshop: Copyrights	
and Releases	20
Intarsia Talk	
Reader's Gallery	



Screaming Eagle



The Tree Swing



ON THE COVER: This issue's cover features Rob Letvinchuck's Helm's Wheel Intarsia. Rob has become a regular contributor to Creative Woodworks & Crafts* and we are grateful to have him with us.

Whiskers

Chirping Chickadees Wall Pocket

Projects in Full Size Pattern Section No. 2 shown on this page.



Fretwork Box



Pocket Watches (no pattern for this project)



Turkey Beard Holder Intersia




Mare and Colt





pattern by Jacob Fowler, cut and finished by Wayne Fowler



SUPPLIES

Wood; hardwood in mid- to light-brown color (such as butternut, cherry, or oak)—one rectangular tree slice 1/2"- to 3/4"-thick x 15" x 8" (or 15" x 8" rectangle with straight sides)

Tools: scroll saw with No. 2R and/or No. 5R blades; fixed disc or belt sander with fine or extra fine (120/220) disc or belt: access to photocopier

Temporary-bond spray adhesive (such as 3M 777 adhesive)

Clear packing tape 1/4 sheet of 220-grit sandpaper

Finish oil of choice

Introduction

Most of the designs we do are single animal pieces, so, for a change Jacob decided last year to try a forest scene with a mother doe and her two fawns. It was a bit large, and my arms were a bit short(!), so I put the design aside for a few months while I did my Christmas craft shows. Over the Christmas break, after I had managed to lose a little weight and made the pattern a little smaller, I was able to cut a trial piece. Jacob then modified the design to make it a bit shorter. The resulting design, nicknamed "Watchful Eyes" because of the mother deer's alert stance, cuts well and looks great.

butternut with the bark still on. It has a great knot just beside the mother, which gives it some good lines and some very white sapwood. The piece was cut on an Excalibur FX30 saw. Send questions concerning this project to: Weyne Fowler, 33 using mainly No. 5R blades for the mother and frame and No. 2R blades for the two fawns, given their fine details.

INSTRUCTIONS

Photocopy the pattern and use spray adhesive to attach it to the wood. I recommend using clear packing tape on top of the pattern to reduce the burn from the tight turns you will have to make while cutting the pattern. If the slippery packing tape makes handling the piece difficult, try putting the packing tape on the wood first, then glue the pattern to the tape. For cutting, I recommend using a combination of No. 2 and No. 5 reverse tooth blades to reduce chipping on the bottom of the piece.

After you have drilled the guide holes and cut out the fret pieces, either peel the pattern off or use a solvent such as paint thinner to remove the paper pattern, and let the piece dry. Sand the front and back of the piece, and straighten the outside lines of the rectangle using a disc or belt sander. [When I am in a hurry, I just peel off the packing tape and sand off the pattern.) Using a piece of 220-grit sandpaper is a good way to remove any remaining burns and to lightly round the edges to give the piece a more finished look. Clean the piece using your favorite tool of choice, such as a clean paintbrush. Finish with a thin oil to seal the inner edges. I use mainly walnut oil, but I also like tung oil.

The finished cutting could be displayed on a wali, but I The finished family was cut from a tree slice of 3/4"-thick recommend backing it with a thin piece of plywood cut to the shape of the piece.

> Longmeadow Cres., Markham, Ontario, Canado L3R 3J6, or emait hirr: at: fantasiesisaw@rogers.com





Pattern Located In Full Size Pattern Section No. 2!

by Roy King, Scott Kochendorfer, and Bob Valle of While Tail Designs, Ltd.

SUPPLIES

Wood: maple or other light colored wood of choice—one piece 1/4" x 6-1/2" x 7-1/2" (for eagle); oak, walnut, or wood of choice—one piece 1/2" to 3/4" x 12-1/2" x 9" (for frame); Ballic birch—one piece 1/8" x 12-1/2" x 9" (for back board) Tools: scroll saw with No. 2R blades; drill with 1/16" bit; router with decorative router bit and roundover bit (optional) Temporary-bond spray adhesive Clear packing tape Sandpaper, medium and fine grits

of finish Spray paint in flat black or choice of color Hanger

Polyurethane spray in sotin or choice

NSTRUCTIONS

Photocopy your patterns, saving the originals for later use, and cut them out. Using the spray adhesive, apply a thin coat to the back of the patterns and let them tack up until they feel sticky, like masking tape. Apply the eagle pattern to the light colored wood. Place the piece of wood for the frame on the piece of Baltic birch for the back board, attach the two pieces using clear packing tape, and apply the pattern to the top. (The frame and back board will be cut at the same time to ensure that both pieces are the same size.) Place alear packing tape over all patterns, which makes cutting easier and lubricates the blade, keeping it


Drill all entry holes on the eagle piece, then cut out all holes and along all internal veining lines as you come to them, Finish by cutting along the outside pattern lines.

Cutting through both thicknesses, cut along the outer line of the frame pattern. Separate the two pieces of wood and set the back board aside. Drill an entry hole within the frame opening area and cut out along the inner line. If desired, use a router with a decorative bit to cut along the outside of the frame and use a roundover bit along the inner edge of the frame. Remove the patterns and sand all pieces.

For a protective finish, we suggest using a spray polyurethane for both the eagle and the frame. Spray in short bursts, making sure to keep the can moving to avoid unsightly runs in your work. When dry, sand lightly, then apply another coat and let dry.

Using spray paint in the color of your choice, paint both sides and the edges of the back board and let dry. Glue a 1/4"-thick spacer to the back of the eagle, staying clear of any cut out creas. This will lift the project off the back board, creating a pleasing look. Glue the back board to the back of the frame. Center the eagle on the back board and glue in place. Let dry. Lay the assembled project on a flat surface and place weight on the assembly to prevent any pieces from shifting. When completely dry, attach a hanger to the back. Be sure to always work in a well-ventilated area and follow all safety instructions!

For questions concerning this project, contact: White Tail Designs, Ltd., 17713 S. 66th Ct., Tinley Park, IL 60477; email: scrolled1@comcast.net 😜





along internal

veining lines.



from the editor's desk

Welcome to the 110th edition of Creative Woodworks & Crafts*! I believe this to be one of our best issues to date, with a truly wide selection of projects for you to choose from. We have two new contributors in this issue, Sue Mey and Scott Roberts. Sue hails from South Africa and brings a lot of talent and passion to her work. There's something hauntingly real about her Three Wildcat Portraits; it seems she's captured the essence of these magnificent creatures within those flat pieces of wood, bringing them to life and making the imagination soar. Scott Roberts does a fine job with his Reverent Denomination, showing us how the power of creativity can transform the humble Lincoln Penny into an eye-catching project. Scott is also a good woodurner, and has contributed significantly to our sister publication, Woodturning DesignTM.

On the other side of the coin (pardon the pun), I want to acknowledge two other design teams who have been so consistently good they usually wind up with two projects per issue-Wayne and Jacob Fowler, and Shelli and Kerry Robinson. Wes and Alice Demarest and I met Wayne Fowler at


a scroll saw show in Pennsylvania a couple of years ago and we were blown away by his wonderful use of select pieces of various hardwoods. His son, Jacob, does the designing, and Wayne does the cutting. But Wayne is not "just" a cutter, he's an artist with wood as his medium. Take a close look at Ready For Flight on page 11 of this issue. Even if dragons are not your thing, you've got to appreciate Wayne's wood selection, and how the eastern cottonwood he selected for the pattern piece elevates the entire project to a high artistic level.

Similarly, the Fowlers' Watchful Hyes project is distinguished not only by a line pattern, but also by how the 3/4"-thick butternut slab, with bark attached, causes the project to come to life and hold your attention.

Shelli Robinson began designing for us with our June '04 issue and has been a regular ever since. Without doubt, Shelli has a special talent for creating scroll saw patterns with lots of heart. Through Shelli's art we know her to be a great lover of horses, puppies, children, bunnies, carousel horses, and all those sweet subjects that warm the soul and touch us directly in that place that loves the purity and inno-

A Few Highlights From Our Next Issue (the 2005 Holiday Edition)

Kerry and Shelli Robinson cence of life. Her loyal busband Kerry does a fine job of cutting (and often framing) Shelli's projects, and for this we are also very grateful.



Enjoy this issue and until the next one, health and happiness to everyone.



Wayne and Jacob Fowler



Sincerely,

Robert A. Becken Robert A. Becker



Christmas Angel by Wayne and Jacob Fowler

Christmas **Ornaments** by Party Beach





Snowman Bank by Diana Thompson



Lion and Lamb Intarsia by Rob Letvinchuck




Sue Mey

Snowflake Tambour Clock by Dan and Ray Wilckens

Don't miss these upcoming issues of Creative Woodworks & Crafts®!

Issue No. 111 (Holiday 2005) - on sale September 1st, 2005 Issue No. 112 - on sale October 4th, 2005 Issue No. 113 - on sale November 8th, 2005

Check us out online at www.woodworksandcrafts.com



"The ease of blade changing and tensioning, and smoothness put this machine in a class of its own."

Alain T. New Hyde Park, NY



"The difference between HEGNER and other scroll saws is like night and day."

Elizabeth H. Brookhaven, PA



"I am amazed at the quietness, lack of vibration and ease of cutting intricate detailed patterns with my HEGNER."

Lester E. Austin, TX



The above is unsolicited feedback from three of thousands of satisfied HEGNER owners the world over. The benefits that impressed them can make you a better and more satisfied scroller and create the **Ultimate Scroll Saw Experience**.

Clean, efficient, effective design, solid all-cast construction, quality materials and innovative design solutions all contribute to the unique benefits HEGNER provides. To find out more, visit us online, write, or call toll-free

1-800-SCROLLER (727-6553).



HEGNER Precision Scroll Saws

Are You Ready for the Ultimute Scroll Saw Experience?

Visit www.advmachinery.com/facts today!

ADVANCED MACHINERY - P.O. Box BIZ - Dept. 6861 - New Castle, DE 19720

A CRAFTS CRAFTS

Creative Woodworks & Crafts^o is a registered trademark of All American Crafts, Inc.

Publisher

CEO arren S. Cohen

<u>Vice President of Circulation & Marketing</u> Ideale-Claire Macdonald

> Editor Robert Becker

Associate Editor
Debbie McGowan

Special Projects Editor
Wes Demorest

Scrolling Editors

Sheila Bergner Dirk Boelmon Marilyn Carmin Jacob Fowler Weyne Fowler Roy King Scott Kochendorfer Rick Hutcheson John A. Nelson John Pollvenns Dan Wilckens Raymond Wilckens

> Intarsia <u>Editor</u> Robert J. Hlavacek, Sv.

> > Art Director
> > Kelly Albertson

Assistant Art Director
Beyorky Horz

Digital Imaging Technicians
Kathleen Nosti • Jennifer Waldron

thleen Nosti • Jennijer Waldr Gruphic Designers

Kelly Beach * Julie Calandriello Marion Michaels * Lorie Rhoden

Technical Illustrator
George Ahlers

Photographer
Wes Demarest

Webmaster Jean Perkee

Procfreader
Jennifer Novesch

Public Relations
Madeline S. Cohen

Reader Service (973) 347-6900 ext.101

Advertising Sales

Rrett Cohen (973) 347-6900 ext, 115 Russell Cohen • Lee Jawenski • Tamara Hanes

Newsstand Consultant
Dick Glossrava

RETAILERS

To carry Creative Woodworks & Crafts® in your store, please write; All American Crafts, Inc. 7 Waterloe Read, Stanbope, NI 07874 (973) 347-6900

For subscription information, write to: Creative Woodworks & Crafts® P.O. Box 518, Mt. Morris, IL 61054-1-840-940-6592 Subscription rate: \$29.97/8 issues

If you would like to contact us, you can c mail us at: editors@eraxhwarksandcrafts.com or visit our website at; www.woodworksandcrafts.com

Published by All American Crafts, Inc.

PRESIDENT
Jerry Cohen
SECRETARY
Irving Spielberg



FORFIL

aftern by Jacob Fowler, cut and finished by Wayne Fowler



Introduction

One of the reasons for the name of our craft business, "Fantasies I Saw." is that we make and sell lots of fantasy designs. We have found that dragons, whether big or small, sell consistently, regardless of whether we are at a science fiction and fantasy show or just a local craft sale. Jacob has made a number of simple dragons over the years, but never a big, complex one. Last month he finished a great dragon perched on a rock, looking for excitement or her next meail. We will show that one at our upcoming Christmas craft shows for all those dragon callectors out there.

This dragon was out from one of my last pieces of an eastern cottonwood stump found by Edgar Werner, in the town dump in Durham, Ontario. The great lines in the

SUPPLIES

Wood: hardwood in mid-brown or red color with strong lines or grain (such as brown cak, willow, butternut, or cherry)---one piace 3/4" x 12" x 8 3/4" (for cragon); complementary or same type of hardwood—one piece 3/4"-1" thick x 2" x 9" (for optiona: base)
Tools: scroll saw with No. 2R and/or No. 5R biades; fixed

disc or bolt sander with fine or extra fine (120/220) disc or belt; access to photocopier

Temporary-band spray adhesive (such as 3M 777

Clear packing tapo 1/4 sheet of 220-grit sandpaper

Finish oil of choice (e.g., tung, walnut, Danish, etc.)

wood are caused by the crotch at the top of the log. The base is a piece of brown oak with a lot of character. It is finished in several coats of walnut oil. I also cut a larger, sister version mounted on a piece of grey elm burl that has attracted a lot of attention in my office at work

INSTRUCTIONS

Photocopy the pattern and use spray achesive to attach it to the wood. I recommend using clear packing tape on top of the pattern to reduce the burn from the tight turns you will have to make while cutting the pattern. For culting, Frecommend using a No. 5 or a No. 2 roverse tooth blade to reduce chipping on the bottom of the piece.

After you have drilled the guide holes and cut out the fret pieces, either peel the pattern off or use a solvent, such as paint thinner, to remove the paper pattern, and let the piece dry. Sand the front and back of the piece on a disc or belt sander. This is your chance to ensure that the bottom surface is straight and flat by sanding out any bumps. I find that using a 1/4-sheet of 220 grit sandpaper is a good way to remove any remaining burrs and to

lightly round the edges to give it a more finished look. Clean the dragon using your favorite tool of choice, such as a clean paintbrush. Finish with a thin oil to seal the inner edges. Hike to use either walnut or tung cit.

If you plan to display the finished piece on a shelf, you may choose to mount it on a rectangular base measuring about 9" x 2". Use two dowels or screws through the right end and center of the bottom of the dragon. I use a roundover router bit to give bases a more finished look. You could also round the ends of the base before routing for another option.

Send questions concerning this project to: Wayne Fowler, 33 Longmeadow Cres., Markham, Ontario, Canada L3R 3J6, or email him at: fantasiesisaw@rogers.com

Pattern Located in Full Size Pattern Section No. 2!





SUPPLIES

Wood: Baltic birch plywood—one piece 1/8" x

12-11/16" x 9-7/8" Tools; scroll saw with No. 2/0 spiral blades; drill with assorted bits; square

Temporary-bond spray adhesive or Removable Adhesive Paper

Clear packaging tape Wood glue Sandpaper, assorted grits Black spray paint Ready-made frame. 10" x 13" or 11" x 14"

Introduction

We all have our childhood heroes, and mine were, and still are, the authors and illustrators of classic horse stories, such as Walter Farley, Marguerite Henry, Anna Sewell, and Sam Savitt. I have accumulated a rather large library of their works and books as I anxicusly await the day when I can read these cherished stories to my own daughter. I remember checking out the Black Stallion so many times from our library that the borrower card for the book was almost completely filled with my name!

Mr. Savitt's works inspired my realistic approach to drawing horses, and therein everything else I draw. His artistry flored my imagination to run with the characters in the books he illustrated. I will never outgrow my childhood dreams of being Alec, riding like the wind on the back of the mighty Black Stallion, with no saddle or bridle.

With this pattern, I wanted to capture the gentle and curious look of a gorgeous stallion as he gracefully arches his neck over the paddock fence. I named him "Whiskers," suggesting that the most insignificant part of this magnificent animal is his most endearing feature! His ears are pricked forward at attention, as if to say, "Do you have something for me?" Whether I'm bringing him a corrot, an apple, or simply a loving pat and kiss for his satin muzzle, he is happy to see me. Of all the positions I have seen horses assume such as rearing, bucking, running, or prancing, this is by far my favorite. There is nothing as heartworming as my horse warmly nickering to me as I approach.

Whiskers is just one of my many designs that feature harses, and my unending admiration for these noble creatures is matched by my admiration for the storytellers and illustrators of my youth who were able to bring their tales of horses to life for me.

INSTRUCTIONS

Using your method of choice, apply your pattern to the clean surface of your wood. We use Removable Adhesive Paper for ALL of our scrolling projects. Although we have listed only one piece of 1/8"-thick wood in the supplies list. we usually stack cut about six boards of 1/8"-thick Baltic birch plywood for stability and enhanced productivity. We apply double-sided tape to the four corners of the wood.

staying clear of the pattern. These particular boards were cut to fit the inside of ready-mode frames.

No matter which pattern application method you use, it is a good idea to apply 2"- or 3"-wide clear packaging tape over the entire top of your pattern. This simple and inexpensive step will lengthen the life of your blades because it helps to keep them cooler by lubricating them while you cut. Do not wrap tape around to the bottom of your wood as this could make your board(s) uneven or take your blade out of square. Make sure your blade is square, and check this frequently while scrolling.

Pre-drill all your holes and make starter holes at the end of all the single lines, such as the lines within the fence. Cut out the smaller areas first. Kerry out this pattern following the usual "center-working-out" method. I recommend cutting out the biggest areas last. Of course, let your own experience guide your hands and direct your blades, and have some fun with this pattern!

When you are finished, gently pry the boards apart. For those of you who have discovered the ease of working with Removable Adhesive Paper, just peel off the pattern! Otherwise, remove your pottern using your preferred method and clean the wood surface. Sand the back of the board.

For a backer, you can use the cardboard that comes with the frame spray painted black (as shown in this example), a piece of birch board spray painted black, or choose your own color combination of materials and frames. Glue your finished piece to the backer and frame as desired.

We are SKWoodWorks, which stands for "Shelli Kerry Woodworks." Visit our website at www.skwoodworks.com. Check us out every now and again for updates from us from around the barn. I draw in standard 8 1/2" x 11" lettersize patterns for easy copying, cutting, mounting and framing. We sell the adhesive paper, finished pieces, and patterns off of our website. For more information, visit us on the web, or send a SASE to: SKWoodWorks, P.O. Box 583, Pleasant View, TN 37146. Pattern requests and suggestions are always welcome!

SCROLLER Presents...IMPRESSIVE INTARSIA



5-Small Quilt Squares...#W-WQ5 \$8.95 (10"x10" ea.) For Fastest Service, call us toll-free at Enclose check or money order (USD\$) for merchandise, SCROLLER, LTD. - Dept. SCWW905 - P.O. Box 827

(15"x19")

AND AWE - INSPIRING SCROLL SAW ART PROJECTS



Undaunted...#JZ325 (8"x10")



Mt. Rushmore #SCP101 (11"x17")



JFK...#SCP102 (8½"x10½")



Pope of the




Ferocious Beauty...#JZ330 (11"x14")



Tender Moments...#JZ323 (8"x10")





Power of Prayer.. #SCP103 (10"x14")



All I Need...#JZ327 (11"x14")

1-800-486-6053 to place credit card order or, along with \$4.95 shipping & handling and mail to: Fenton, MI 48430 - www.scrolleronline.com



by Sue Mey







SUPPLIES

Wood: Baltic birch plywood or wood of choice—one piece 1/4" x 8" x 10" (for each cat); MDF (medium density fiberboard)—one piece 3/4" x 8" x 10" (for each cat). Tools: scroll saw with No. 2 or No. 3 reverse tooth blade; drill press with 1/8"- and 1/16"-Dia, bits; disc sander; palm sander; sanding block; clamps. Temporary-bond spray adhesive.

Wood glue
Packaging tape
Thin double sided tape

Carton paper
Sandpaper, assorted grits
Clear spray varnish
Deep penetrating furniture wax liquid or Danish oil

Artist's brush Matte black spray paint Saw tooth hanger

instructions on page 18



continued from page 17

Introduction

I live in beautiful South Africa where the climate is warm, the landscope is varied and verdant in summer, and there is an abundance of wildlife. Nature inspires me and, being a devoted cat lover, I would like to share with you three of

the many wildcats I have captured on wood.

Cheelahs are often thought of as African and pumas are thought of as American, yet the two cats have a lot in common. Because the cheetah hunted in the open planes and the puma hunted in stealth in thick forest and tall grass, the two cats were not in competition and were able to live together in the New World. Both make trilling sounds, chirps like birdcails and whistling noises. They also have pupils that stay round and do not form slits like the pupils of wild cats or house cats. They rely on their long-distance vision, using high places as lockouts, for their information. Both types of cats have extremely long, heavy talls to give them balance and both are extremely fast. The cheetah is, of course, the fastest land animal and can reach speeds in excess of 60 mph.

The leopard, which is classified as one of South Africa's "Big Five," is most easily recognized by its rosette-patterned coat and extremely long, dark tail. It has powerful limb and neck muscles, enabling it to carry a fully-grown male antelope or even young giraffe, weighing up to three times its own body weight, high into treetops. This is to keep its trophy away from scavenging packs of hyenos and opportunistic lions. The leapard is a versatile hunter

and is generally nocturnal in its pursuit of prey.

Patterns for all three of these big cats are provided with this project.

INSTRUCTIONS

Using the palm sander, sand the wood. This not only reduces the amount of hard sanding to be done later but also the risk of breaking off fragile pieces when sanding after cutting. Photocopy the pattern at 100% and attach to the wood, using temporary-bond spray adhesive or method of choice. (Note: To prevent tear-out underneath when cutting a portrait, attach some carton paper, such as an empty breakfast cereal box, to the bottom of the wood with thin double-sided tape. Cover the carton with packaging tape.)

Drill the blade entry holes using the 1/8"-Dia, bit. Carofully drill the holes in the small areas using the 1/16"-Dia, bit, Use sandpaper or a scraper blade held at a slight angle to remove any burs created by drilling the holes. Be

sure to follow the grain of the wood.

Thread either the No. 2 or No. 3 blade through the blade entry holes and cut all the black areas on the pattern. Slow down the speed of your saw when cutting fragile parts like the eyes and whiskers, and use a zero clearance insert to reduce the risk of breaking these parts. (Note: You can use a piece of your cercal box carton to make a zero clearance insert. Simply drill a small blade entry hole in it and tape it to your saw table with masking tape.)

Remove the pattern and, using 150-grit sandpaper, sand the back of the piece by hand or use a sanding block to remove all burs. Sand the front of the piece starting with 320-grit sandpaper and working up to 500-grit sandpaper until you have a smooth finish. Be careful not to catch and break any fragile pieces. I prefer to use a three-finger-sized piece of sandpaper without a sanding block because it

gives me a bottor sonse of the amount of pressure required.

Square the four edges of both the portrait and the backing piece using the disc sander. The two pieces can be done separately and dry-fitted to ensure that the two work pieces line up nicely. Alternatively, attach the partrait to the backing with thin double-sided tape or hot glue on the four corners before straight sandling the edges. Detach the two pieces immediately afterwards, as the tape becomes stickier and more difficult to remove if you leave it or for a day or two. Remove all sanding dust. (I block-mount my portraits on pointed MDF backings, if you prefer, back the piece with black matting board and mount in an 8" x 10" ready-made frame.)

Use a medium-size artist's brush to apply deep penetrating furniture wax liquid to the portrait front and edges. The brush makes it easy to reach all the nocks and crannies of the pierce cuts. (Note: In cold conditions, I pour some wax liquid into an old ceramic mug and heat it in the microwave oven for 15 seconds to allow the wax to liquiefy. This way, the wax penetrates the wood without leaving a waxy layer.) Let the portrait dry for a day or two. To speed the process, place the portrait in the sun to dry, or use warm heat from a hairdryer. As an alternative to the furniture wax liquid, you can apply Danish oil, following the manufacturer's directions. Carefully wipe surfaces with a dry lint-free cloth.

Spray the front, back, and edges of the MDF backing with three thin doats of spray paint, allowing it to dry completely between coats. (Note: The edges absorb the paint, resulting in a "rough" appearance. To ensure a smooth-edged finish, spray as above and when dry, sand the edges of the MDF backing with 150-grit sandpaper. Remove sanding dust with a clean paintbrush, and then spray on another two to three coats of paint, allowing it to

dry between coats.)

Working quickly, apply wood glue to the back of the portrait. Use only small beads of glue near the edges and on the fragile pieces. If you apply too much glue, it will seep out once clamped. Place the portrait on top of the MDF backing, "square up" the two pieces on a flat surface, and apply clamps. If glue seepage occurs, wait until the glue starts to thicken before using a toothpick to remove excess glue from a small area at a time. Once the glue has dried, remove the clamps.

Apply several thin coats of clear spray vamish, allowing the project to dry thoroughly between coats. Attach the saw tooth hanger, and you're ready to present the partrait to your favorite wildcat enthusiast. Or, add the partrait to the collection on your wall. If you have run out of wall space like I have, try the following display option. Make a pelmet for a window in your house or workshop by attaching a selection of partraits to the curtain rail; secure the partraits with bendable wire attached to the saw tooth hangers.

I live in Pretoria, South Africa and have been scrolling for about 10 years. My hobbies include photography, assorted crafts, and watercolor painling. As a molorcycle enthusiasi, I enjoy touring with my BMW and acting as a marshal at the annual motorcycle economy run. I scroll logos, trophies, and desk stands for corporate companies, and I combine scrolling with painting and decoupage, using the techniques to create colorful clocks and children's bedroom accessories. I can be confacted at 27 12 460 1013 (telephone), or E-mail: suem@storage.co.za. To see more of my work, visit www.geocities.com/meydenhart

US Funds Only, MAIL-IN ORDERS AND WEBSITE ORDERS WITHIN THE U.S. GET FREE SHIPPING! PHONE ORDERS SUBJECT TO A SHIPPING CHARGE. FOR MORE INFORMATION CALL (972) 722-9722. EACH ISSUE \$6.00 · ANY 5 ISSUES \$28.00 · ANY 10 ISSUES \$50.00 · ANY 15 ISSUES \$70.00

sevco com



JUNE 1997 Figer and Eagle Mini Clocks, Raccoon Intarsia, Evetwork Eagle, Carving a Frame, Christopher Mantel Clock, and more!



OCTOBER 1999 Wolf Intarsia, Eagle Dreamcotcher, Cougar, Whitetail Buck, "Bless Our Home? Silho, and morel



NOVEMBER 1999 Two Lighthouse Mini Clocks, Dragon, Butterfly Band Saw Box, Mini Grandmother Clock, and more!



OCTOBER 2000 Deer Intarsia, Fretwork Basket, Fretwork Music Box, Oak Leaf Clock, "American Pride Eagle" and more!



JANUARY 2001 Bull Rider Lightbox, Fish Clock, Musician's Shelf, "Sailing The Globe" Silhouette, Spider Clock, Two Wildkens Mini Clocks, and more!




MARCH 2001 Wild Turkeys, Fretwork Music Box, Nascar Plaque, 3 Dragons Mohtlight, Fretwork Cross Candicholder, Grizzly Bear, Hawk, Shamening Carving Tools, and much more!



JANUARY 2002 Eagle Intersia, Fretwork Frame, U.S. Navy Plaque, Basketball Clock, Cougar Plaque, Sexolling Antler, Three 3-D Ornaments, and



MARCH 2002 Baseball Desk Set, Horse Liberty Bell Intarsia, Eagle Intarsia Clock, Lighthouse Music Box, Two Train Frame, Lake Trout Plaque, & more!



JUNE 2002 Music Box, Two Train Intarsia, Guardian Angel Projects, Candy Machine, Birdhouse, & more!



SEPTEMBER 2002 Bi-Plane, Baseball Clock, Fretwork Dragon, Woodburned Horse, Striped Bass Intarsia, and more!



JANUARY 2003 Squirrel Plaque, Segmented Hawk, Bear Intarsia, Band Saw Box, Rocking Reindeer, Ring Box, and morel



AUGUS1 2003 Wolf & Eagle Mirror, Howling Wolves, Family Photo Frame, Name Key Tags, Train Shelf, Tubletop Clock, Intarsia



NOVEMBER 2003 Turkey Leaf, Turned Pens, Pen Box, Eagle With Cheese, Lion, Carved Trout, Angelic Clocks, and more!



MARCH 2004 Caribon Weather Station. Smallmouth Bass Plaque, Feather, Quarter Pounder Basketweave Jewelry Pax, Two Native American Silhos, Intarsia Mammoth and much more!



APRIL 2004 Kitten Plaque, Keepsake Box, Malanute, Heart Clocks, Snowy Owl, and more!



JUNE 2004 Jaguar, Eagle Scout Plaque, Toothpick Hokler, Kitten, Musical Cutting Board and more!



AUGUST 2004 Black Bear, Church Clock, Mailbox Stamp Dispenser, Golden Lab Pups, and morel



BEST OF CREATIVE WOODWORKS & **CRAFTS Featuring 23 of** our best projects!



WOOD ORNAMENTS WINTER '99-'00 Featuring 151
Full Size Patterns!




WOOD ORNAMENTS WINTER '00-'01 Featuring 233 **Full Size Patterns!**



WOOD ORNAMENTS WINTER '01-'02 Featuring 300 Great Full Size Patterns!

Majod warks	724 100	Moodwark	题。
Orne	DOD Iment	Orn	ame
7. 14			
10 EST			W 4
, ØÇ		32	
		0 0	

WINTER '02-'03 Featuring 315 Full Size Patterns!



WOOD ORNAMENTS WOOD ORNAMENTS WINTER '03-'04
Featuring 305 Full
Size Patterns!
THE LAST **ORNAMENT ISSUE!**



2004 HOLIDAY ISSUE 12 great seasonal projects plus 100 ornament patterns.

Name	Enclosed is my payment of:
Address	SS
	for
City/Sate/Zip	back issues.
Write the issues (months/years) that	you want:

PISA DISCOVER accepted

ORDERING GUIDELINES: PLEASE ADDRESS ALL BACK ISSUE ORDERS (AND MAKE CHECK OR MONEY ORDER PAYABLE) TO: SEYCO, THE SCROLL SAW SPECIALISTS, INC., P.O. BOX 1900, ROCKWALL, TX 75087, (DEPT. B-10), • MANY OTHER ISSUES AVAILABLE - SEE OUR WEBSITE AT SEYCO.COM FOR MORE INFO. CALL (972) 722-9722 • PLEASE USE THE PRICES SHOWN IN THIS AD; DO NOT ORDER FROM PAST BACK ISSUE ADS.



Wes' Workshop

COPYRIGHTS AND RELEASES

Lately I have received several questions regarding copyrights. As I'm not a laywer, I can't give legal advice. In fact, copyrights, trade dress, trademarks, patents, and releases are such complex areas of the law, all pertaining to intellectual property rights, that major corporations retain specialists to handle such matters. Although I'm not a legal professional, I'll share with you what I know.

I'm sure many of you are familiar with the latest legal battles over downloading music from the Internet and not paying for it,

and that is only one small facet of this gem. Just as musicians write original music, pattern designers create patterns from their original ideas. That pattern, song, lyric, photograph, writing, or other creative endeavor becomes that person's original intellectual property and is, from that moment on, protected from being used by ANYONE clsc without their express permission. The word "express" is a specific legal word that really puts an obligation on both parties. The rights to these properties are controlled by their creators in all aspects of any use, which includes the numbers and

types of use, how long the rights last, and the cost of acquiring the rights from the creator. So where does that leave a budding artist?

Watch out for your influences and inspirations!

We have heard some folks say, "All I have to do is make eight changes and it is my original." Not so! Whether you add or remove eight or 800 holes, it is NOT yours.

Public Domain

Many things cannot be copyrighted and are in what is called the "public domain." Numbers, letters of the alphabet, wildlife species, and words found in the dictionary are just a few. But when you put together any combination of them, that combination is now your copyright, unless someone else beat you to it or it is derived from another similar pattern. Confused yet? Wait, it gets worse.

Assume that you would like to turn someone's carving pattern into a scroll saw pattern. The creator of the original pattern probably never considered that type of use, and being the creative type that you are, you work on it and end up with a beautiful design. You begin selling the objects you cut from that pattern, and they sell like hotcakes in the arctic. Then, one day, you receive a regis tered letter from a law firm, and it is a cease and desist order, AND the originator of the design is seeking compensation for the violation of his copyright. Well, after your mouth goes dry, your stomach will start flopping around, and your knees will get weak. My advice is that you better seek legal counsel who specializes in the intellectual property rights field (not your family attorney).

Yes, dear reader, pattern modification is also covered. "Trade dress," mentioned earlier, is another less known trap into which you can easily fall. An example would be if someone makes a bunch of different items and paints them all in a very similar and distinctive manner. That person becomes known for his product line because, although the patterns may be of anything, the finishing technique is so recognizable. (One trade dress case in the courts involved a Holstein cow pattern, and the person copying it LOST!) Again, many of these issues require legal advice for the

designer.

Let's look at another type of infringement. You see a photograph of an eagle in a magazine, newspaper, etc., and make a scroll saw pattern from it. Well, you are heading down a stony path. You make items from that pattern and use them as gifts, and it is only a

little rocky. Then they become so popular that you sell a few of them to some local folks, and the path now has bigger rocks. You step up to selling at a wider range of craft shows, and the rocks continue to get bigger. As your success grows, so does your distribution. One day, the original photographer sees your project, perhaps on someone's wall, in a store, or at a craft show, he recognizes it as one of his photographs and can prove it. Well, now you could get hit with a boulder.

We have heard some folks say, "All I have to do is make eight

changes and it is my original." Not so! Whether you add or remove eight or 800 holes, it is NOT yours. You have to make changes sufficient enough that the original pattern is, at best, not even recognizable. Anything less and you are on thin ice. For example, say you see an original pattern of a cardinal bird that sells well. You want the pattern to be your own, so you make it a bluebird. Well, it had better not be a cardinal with his crest removed and colored differently because that may not work.

While you may think the consequences for simply selling a knock-off that you made

seem excessive, just consider how anery (and rightly so) the originator of the pattern would be if you sold the pattern without his permission and under your name. Remember that the artists rely on their designs to distinguish themselves from the competition. They are juried into exclusive galleries, shows, and museums because of their uniqueness. If someone comes along and cuts into their market by selling knock-offs of their designs, it effectively reduces their income through loss of sales, reduction of prices, and/or loss of exclusivity.

Releases

Did you know that if you use a recognizable feature of private property in a design you need a release from the property owner? And that applies to some public properties as well, such as famous architectural structures like cathedrals, castles, and the like. At the very least, you may need a permit to make images of anything within the boundaries of a federal, state, county, or municipal property or park to be legal. Those permits can get rather expensive, but fortunately, most are in the public domain. If you use a person as a model for your pattern, or a likeness of a person, including celebrities (living or dead), you also need a release to keep yourself out of trouble.

Have you ever visited a museum, art gallery, or even certain tourist spots, and noticed signs warning that photography or other recording methods are forbidden? Well, it may not be an issue of Homeland Security. It may mean that the rights to the feature and its contents are already owned or controlled by someone else. And guess what? Most of them have set fees for your intended use and

possibly royalties as well.

So, are you new designers out there looking over your shoulder and worrying about what is in the mail? If so, don't. The first step to avoiding these pitfalls is knowing they exist, and now you do. A chat with the appropriate lawyer will further clarify these matters and put your mind at case. By the way, did I mention coloring books, and cartoon characters, and...?!

For questions concerning this article, send a SASE to: Wes Demarest, 66 Snover Rd., Sussex, NJ 07461: email: wes@woodworksandcrafts.com (54)

Wood so good you won't want to cut it!


This "Baltic Birch" plywood is the ultimate plywood for scrollwork or fretwork. All the plies are birch, with no inner voids so the edges finish beautifully. Our Scroll-PLY is always clear and perfect on one face, though the back may have an occasional plug. Just call for special sizes!

1/8" Scroll-Ply	1-20 pieces of same size	20+ pieces of same size
12" x 12"	1.20	.95
12" x 24"	2.40	1.90
24" x 24"	5.00	4.50
1/4" Scroll-Ply		
12" x 12"	1.50	1.25
12" x 24"	3.00	2.50
24" x 24"	6.25	5.50
1/2" Scroll-Ply		
12" x 12"	2.40	1.95
12" x 24"	4.80	3.90
24" x 24"	10.00	9.00

Scrollsaw Blank Solid Hardwood!! These are the solid hardwood blanks that have

the scroll world talking! Each blank is a clear color matched panel, sanded to thickness. Spend your time scrolling instead of trying to glue and plane wide panels yourself!! Just apply your pattern and start scrolling.

-					.5.			-
			1/4"	1/2"	3/4"		4	>
	ASPEN	12"x12"	3.20	4.30	5.10			Si.
		12"x16"	4.30	5.70	6.70		-	÷
	POPLAR	12"x20"	5.40	7,20	8.50			-
	ASH						O	0
	ASH	12"x12"	4.20	5.60	6.60		Ŀ	\leq
		12"x16"	5.60	7.50	8.80			
	BASSWOOD	12"x20"	7.00	9,30	10,90			
	BIRCH							
		12"x12"	5.20	6.90	8.10		<	
	OAK	12"x16"	6.90	9.20	10.80			
	BUTTERNUT	12"x20"	8.60	11.50	13.50		5	
	MAPLE							3
	10/10/10/10/10/10	12"x12"	6.50	8.70	10.20		2	
	WALNUT	12"x16"	8.70	11.60	13.70			
	PURPLEHEART	12"x20"	10.90	14.50	17.10			5
	CHERRY					Ш	W.I IC	6
	SATINWOOD	12"x12"	7.90	10.50	12.40			
	MAHOGANY	12"x16"		14.00	16.50			
	MATIOGANT	12"x20"			20.60		-5	4
		Note: Sin					4	
1		tom made					C	2
_		is shipped					Œ	•
1		1					-	
ŀ	(中国)) in	sured F	reight (Charge	s	<	
1			Continent					5
7					D, add \$5.		7	
1				\$20.01-\$	50.00, add	1	4	2
	DAWGUST SAN	\$7.9		een na di	100.00, ac			2_
	ERITAGE	\$9.9		фэл:пл-ф.	100.00, ax	(U)		
	muliding Speciatries		er Value (ver \$100	.00, add		•	
	got wood?	\$10.	95					
	gor wood:		ika, Hawa				18	\$
t	age Building Speck		ada, and					3
255	O S-book	DIES	inations v	VIII IFFICUL S	MEMODIAN		Consultant or other Designation of the last of the las	and the



Canada, and other International destinations will Incur additional freight charges. Call for quote.



"Cut with the hardest sawblade in the industry" You will see that the blades slice through work fast, cut straight and have good life. Once you experience the great performance, you will be equally impressed with our prices.

For a complete catalog describing the saw blade line, services, packaging, discounts, and becoming a dealer contact us at:

Phone: 800-998-4467 • Fax: 800-758-4467 email: industrial@grobrtusa.com



Wood Works With Rit!

Revealing Rit...The Secret Ingredient!

Professional and hobby woodworkers, basket and toy makers of all kinds have known for years that the easiest way to evenly and deeply color raw wood has been to use Rit powder or liquid dye. Wood fibers open up and welcome the dye color!

It is for easier to batchdye small items than to paint them. The color penetrates more deeply, and the rich, vibrant colors enhance natural wood grains.

The five scroll saw projects shown above were designed by John Nolson exclusively for Creative Woodworks & Crafts. All five were made with Rit Dyes and were featured in Creative Woodworks & Crafts.

Over 35 Colors Can Be Found At Area Retailers!



For more information, about where to find Rit retail products, contact: Rit Consumer Services, P.O. Box 21070, Indianapolis, IN 46221. Phone: 866-794-0800.

www.ritdve.com




Heritage Building Specialties 205 N. Cascade Fergus Falls, MN 56537-2208



ENGINE 86 E

by Jeff Zaffino



Introduction

Across the street from my house is a railroad track that is used by the Tennessee Valley Railroad Museum. They run an antique steam engine up and down the tracks a couple of times per month as a special tour of our scenic neck of the woods. I have always been fascinated with the people and machinery of days gone by, and the things they accomplished with such limited technology and resources have always amazed me. I could sit and watch that old train pass by for hours on end, but I must say my favorite thing about "Old Smokey," my nickname for the train, is the way my son Gianni's eyes light up when he hears the whistle in the distance. The way he runs to the window dropping whatever he is doing to watch the train, the wonder in his eyes, and the smile on his face, make my heart smile the way only a father's can. So I decided to design and cut a piece especially for him. Engine 86 is the result.

Soon after I started designing this pattern, something in

me made me bend the rules a bit. You see, when you design patterns for other people to cut, there are certain "rules" that you have to follow. For example, all of your connections have to maintain a certain thickness, all of your cutouts must be at least a certain width, etc. I have a penchant for pushing those rules right up to the very edge. I love a challenge, and the thought of cutting samething that could explode into "designer firewood" with ony stroke of the saw blade fills me with excitement, so with this pattern I thought I would push just a bit further than I usually do. The result is a piece that captures an incredible amount of detail and can be quite tricky to cut. My son's face upon seeing the finished piece was reward enough for me and made all the extra effort well worth it. My sense of satisfaction with this piece is way up there with some of the most difficult ones I ever cut.

Don't let this pattern intimidate you. Granted, it is highly detailed and there are a few places where the scrolling will make you hold your breath, but with some basic

SUPPLIES

Wood: Balfic birch plywood—one piece 1/8" to 1/4" x 14" x 11"

Tools; scroll saw with Flying Dutchman 2/0 spiral blades; drill press with No. 68 bit; palm sander or sanding block; spring clamps; air compressor; bernzomatic plumber's torch (optional)

Temporary-bond spray adhesive
Blue or purple painter's tape
220-grit sandpaper
Clear coat finish
Mineral spirits
Spray bottle
Black felt or backer of choice

planning and advice, you can cut this. That being said, however, don't think this piece is going to cut out like a simple puzzle. It will take an investment of both time and patience, and it will force you to use your best scrolling techniques. The completed cutting will be a piece that will make any scroller proud! The pattern itself has a little more than 700 cuts and took approximately 15 hours for me to complete. Confidence is the most important thing a scroller needs in order to attempt a detailed pattern such as this. Believe you can do it and you can.

I make my living with my saw, selling framed wall art, so a lot of the things I do are designed to achieve acceptable quality at maximum speed. If you have a tried and true method that works for you, by all means stick with it. The tips I share in this article are ones that work for me.

I prefer using spiral blades on patterns that are this detailed, but straight blades can be used too. I prefer Baltic birch for my cuttings, but any good quality ply will work well for this pattern. Use at least two pieces of 1/4"-thick ply, but if you are going to use 1/8"-thick Baltic birch for this cutting, stack a minimum of three pieces, because many of the areas of this pattern can use that extra support. The extra thickness will also help take some of the aggressiveness out of the spiral blades, making them easier to control.

Now that we have all that out of the way, let's begin our trip... ALL ABOARD!

INSTRUCTIONS

After ripping the wood down to size, I prefer to sand it before cutting. Once cut, a piece like this is VERY fragile, and you will not be able to sand it aggressively. As previously mentioned, using a stack of a few sheets will dramat ically improve your odds of making it all the way to completion of this project. Stacking the wood tightly will also dramatically reduce the fuzzies that a spiral will inevitably leave behind. After stacking your wood with the ends flush and all the front sides facing up, temporarily secure one side with a few large spring clamps. I like to use three clamps for a cutting of this size, with one on each corner and one in the middle. Place the clamps far enough into the wood so you can run tape along the edges without having to remove the clamps. Blue painter's tape is easy to see on the wood and releases fairly easily. However, if

you pre-finish your wood, you will have an incredibly difficult time removing this kind of tape; try using purple painter's tape instead. After you run the tape along the edge, pull it snugly around to the top of the wood and, while keeping pressure on it, fold it over to the back. Once you have secured the first side, remove the clamps and continue around the wood. If you want to check the stack to be sure it is tight, finish all four sides and squeeze the stack right on the edge between your fingers. If wrinkles appear in the tape, then the stack is still loose. I know it sounds like a lot of extra work, but I assure you the time you save in removing those fuzzies will make it well worth the effort. Unfortunately, there is no technique I know of that will minimize them on the back of the bottom sheet.

Let's adhere the pattern and get down to the nitty gritty of cutting this piece. Apply a HEAVY coat of spray adhesive. (We will deal with removal later.) This cutting has lots of very thin areas and long floating pieces. If you don't use enough glue, they will lift, and you will be left trying to guess where to end your cut.

Take a good look at the pattern before heading to the drill press, taking note of the long cuts in the bottom as well as the way cutting the roof of the shed will effect the overall strength of the wood. Try to plan your cutting in advance. I suggest starting with the smokestack on the front of the train and cutting all of the train first, then moving to the tracks at the bottom, finishing with the shed. This piece will lose A LOT of strength as you cut, so keep that in mind and drill accordingly. Another consideration before you drill is that several of the connections in this piece are VERY thin and the cuts are very close together. You have to be sure your drill bit is perpendicular to the wood, and be extremely precise when you drill. I cut this with a 2/0 Flying Dutchman spiral and used a No. 68 bit to drill my holes. Bits that small, while wonderful for this kind of detail, will often cause the wood to "splinter" on the bottom, making blade changes all but impossible. To eliminate this problem, run the bit down in each hole a second time to cut the back clean.

Remember that this pattern, like any other, is simply a guide, not a rule book. Feel free to make any changes you want. You may decide to thicken some of the connections or to even totally ignore some of the cuts. Do whatever you feel is possible with your talent and experience. The condition and quality of your saw could also effect the cutting; a saw with a lot of "wobble" in the blade may cause you some difficulties.

Blade tension preferences are probably as varied as approaches to cutting a pattern. I personally like a setting of about 4-1/2 on my DeWalt. A setting that high will cause the blade to react with a very slight amount of movement of the wood. There are a few areas of the train, most notably the wheels, where you might want to think about trying a different cutting technique, such as changing direction. To do this, start cuts at the place where you decided to drill. Cut until you reach a point that will weaken the long piece that hangs back into the waste area. Once there, stop cutting around the outside and cut around the hanger, ensuring it doesn't break off. Sometimes that means cutting all the way across the waste area to reach a hanger, and then going back and resuming the outside of the cut. This technique has helped me to save many cuttings from the firewood pile, and I hope it will help you as well.

ENGINE 86 MILL

continued from page 23

If you are new to spirals, try not to turn the wood around the blade. Because spirals don't have an area you can push against to pivot your wood, they will cut in whatever direction you push. Instead, use the blade like a pencil to trace the line, using the entire cutting surface a spiral offers. I make as many cuts pulling the wood towards me as I do pushing it into the blade. Some people say that spirals are impossible to control and you shouldn't use them; however, there are a bunch of scrollers out there who use them, including me. I will let my work speak for itself as to whether or not a spiral can be controlled. Like anything else, they take getting used to, but now that I have tried them. I won't ever go back!

Take your time and let the blade do the cutting. As with any other scrolling project, start somewhere in the center and work out into solid wood. If you start to get a bit nervous about the way the wood "bends" (and it will) toward the end of cutting, try running some clear tape from the top of the piece to the bottom in a few areas, crossing over the area where you have already cut the strength out of the wood. This will allow you to see the pattern,

while adding some stability.

After completing the cutting, I recommend using an air compressor to blow the dust out before you take the stack apart. This helps prevent any of those long pieces from breaking off. When you are ready, take a deep breath and unpack the stack by peeling the tape from the back of the stack back up to the pattern side. After carefully separating the pieces, blow the dust out again, only this time from both the front and back. CAUTION: Do not blow this piece without placing something solid behind it for support. Also, be sure to turn your pressure down to about 40 PSI.

There are still a few stops left on our journey through this cutting, but we are getting closer to the end of the line!

You now have a couple of completed cuttings that would be absolutely wonderful if not for those darn fuzzies! Here is the easiest and fastest way I have found for getting rid of them. Select a piece of scrap wood that you don't mind getting damaged. Make sure it is big enough to cover the entire cutting. I use a 1 x 12 scrap piece of yellow pine, but whatever you have that is big enough should be just fine. Stand the scrap piece up on your bench (I use my drill index behind it to keep it from falling over), and then place the cutting with the back facing you against the scrap wood. Here's the part that might shock you a bit. Grab a propane torch! I use a Bernzomatic plumber's torch, but you could also use a pen torch. Turn the flame way down and QUICKLY wave it back and forth across the back of the cutting.

There are a few safety concerns we'll address here before going into too much detail. First and foremost, be careful. A propane torch burns much hotter than a standard lighter flame and will start a fire in a hurry. If you have used any solvents on your wood at all up to this point, don't try this method. The solvents are all extremely flammable and could result in disaster. As far as technique goes, be sure the scrap wood extends beyond the edges of the piece in all directions. If the flame goes through the cutout areas and hits the scrap wood, it will have a much less damaging effect on the front of the piece than if it just went through the cuts with nothing to stop it on the other side, and it will go a long way towards eliminating scorch

marks on the front. Also, keep the torch moving quickly. Make several passes but don't hold the torch in one place or you will burn through, especially on the thin areas which burn very fast. When you think you have most of the fuzzies charred, lay the piece flat and gently rub the back with a piece of 220-grit sandpaper to remove the ones that may remain. Carefully blow the dust and charred fuzzies off again using the air compressor. Examine the piece closely, and if you can still see fuzzies, repeat the process. Should you find some minor charring on the front, fold a piece of 220-grit sandpaper in half and run it in the cut on the front side of the piece. It will quickly remove all but the worst scorches. This process will not work if you intend for both sides of your cutting to be seen, but because we are adding a backer, it will do nicely for us here.

Are you ready to unveil your masterpiece and remove the pattern? To do so, use a spray bottle filled with mineral spirits and mist the paper thoroughly. Let it soak in for about five minutes, and then you should be able to peel the paper off in one piece. Remove the tape from the edges, and mist the entire piece one more time. This time rub gently with the balls of your fingers to remove any stubborn glue or paper that might remain. I know you are thinking that mineral spirits will discolor your wood, but that's not true. Let it dry thoroughly (overnight is best) before applying your finish, and, after they are finished, you won't be able to tell the difference between the piece you used the mineral spirits on and the one you didn't. For a final finish, spray the piece front and back with two coats of lacquer.


I usually use felt for my backer because I like the texture of it, but use whatever you like. It was suggested to me that I might want to try mat board from the frame shop as it is easier to clean dust off of, so that is what I did with this piece. The jury is still out on that decision for me. I am not yet sure whether I like it as much as the felt or not. I have found that the color black works best, but use whatever backer you feel completes your cutting best. Normally, I use Aleene's tacky glue to mount my backer board. In this case, however, I chose to use spray mount adhesive to help hold all the little pieces in. Use whatever product you like the best.

I personally frame all of my pieces in professionally made frames; it's easier to do than you think. If you can find a reasonable frame wholesaler in your area, I would recommend giving it a try. It really adds that special finishing touch to something you have invested so much of yourself in. The cutting deserves it, and so do you!

I hope you enjoy the challenge this pattern presents and that you will share your cutting of it with us. Remember to enjoy the experience. Good luck and happy scrolling!

Jeff has been scrolling for about two years and designing for a little over a year. He is an accomplished artist with scroll saw works hanging in four different galleries nationwide. Jeff says that he owes a great deal to Tom Mullane for his guidance and teachings. To see more of Jeff's work, visit his website, www.advancedscrollsawpatterns.com. For questions or comments, email him at: jeff@advancedscrollsawpatterns.com, or send a SASE to: 247 Lyle Road, Rossville, GA 30741.

REVERENT DENOMINATION



SUPPLIES

Wood: oak—one piece 3/4" x 7" x 7" (for outer rim), one piece 1/4" x 3-1/4" x 4-3/4" (for Lincoln's profile); oak or oak plywood—one piece 1/4" x 7" x 7" (for background); plywood—one piece 3/8" x 7" x 7" (for backer)
Tools: scroll saw with No. 5 blades: woodburner; clamp

Temporary-bond spray adhesive

Sandpaper, assorted grits

Wand also

Wood glue

CA glue

Thick rubber band

Double-sided tape

Golden oak stain

Spray polyurethane finish

Hanger of choice

Introduction

Why not display the venerable old penny as another symbol of our country's continued healing after 9/11? The Lincoln Cent gets passed between Americans like a welcome handshake every day. And who better to represent our freedom than Abraham Lincoln? Constructed of mighty red oak, this wall plaque will be a meaningful addition to any home.

continued on page 26


Creative Woodworks & Crafts September 2005 • 25

INSTRUCTIONS





Stack the 3/4"-thick oak, the 3/8" backing plywood, and the 1/4"-thick background oak or oak ply. Temporarily secure the pieces together using double-sided tape.





Draw a 6"-Dia, circle in the center of the wood (a coffee can is a handy tracing guide), and cut along the traced line.



Sand the outer edges of the wood stack. Draw a circle 1/4" inside the edge of the circle just cut.



Change to a fresh, sharp blade to cut along the inner traced line. Enter with the grain for this cut. Go slowly to avoid blade flexion, and back up now and then to allow for dust removal and blade reorientation. Try to avoid burning, because it is somewhat difficult to sand the inside of the rim. Once finished, handle the outer rim very carefully so it doesn't snap in half.



Carefully separate all of the pieces and remove the tape. Only the 3/4"-thick oak outer rim, the 1/4"-thick oak inner disc, and the 3/8"-thick plywood inner disc will be used for the project. The remaining pieces can be set aside. Palm sand all surfaces in the direction of the grain.

Assemble the rim around the plywood base with the bottom edges flush. Wood glue the base to the rim, and glue the opening in the rim closed. Place a thick rubber band around the rim and clamp in place. Let dry overnight.



Using temporary-bond spray adhesive, attach the pattern of Lincoln to the 3-1/4" x 4-1/4" piece of oak and the lettering patterns to the 1/4"-thick oak disc. Cut along the outline of Lincoln's profile, and woodburn along all other lines. Lightly sand with a fine-grit sandpaper.

Apply oak stain to all pieces and let dry. Using CA glue, glue the background piece into the rim base, then glue the Lincoln profile into position. Spray with a polyurethane finish, attach a hanger, and display!

For questions concerning this project, send a SASE to: Scott Roberts, 136 Waverly Court, Dawsonville, GA 30934, or email: spinwood @ aol.com



CURLY SUE

CURLY

designed by Shelli Robinson and cut by Kerry Robinson of SKWoodWorks



Introduction

Here is little Curly Sue, an adorable American Cocker Spaniel, as she waits for her beloved "Jim-Dear" and "Darling" (of Lady and the Tramp fame) to arrive home and shower her with gentle pats and heartfelt endearments. Cockers are such devoted little dogs. They are wonderful indoor companions and fit perfectly on your lap. Spoiling them comes easy as they stretch out in their own beds or curl comfortably atop your comforter. In either case, Cockers crawl irretrievably into your heart and warm you from the inside like a perfectly brewed cup of coffee. As Curly Sue patiently waits with her velvety muzzle across her ruffled paws, just the hint of her salontrimmed nails are visible to the left of her puffed cheek and under the mass of a wavy, curly ear!

These dogs are also famous for their eyelashes, which are present (and precious) on both male and female dogs. Cocker pups are some of the all-time cutest animals I have ever seen (and this is coming from a bona fide

Golden Retriever and horse fanatic)! We had a fawncolored, curly-haired "Goldie" Cocker Spaniel in our extended family when I was growing up, and she was as much fun to visit as our relatives!

"Accentuate the positive" was what we were thinking as we looked for the appropriate piece of wood from which to cut the pattern, and we soon found this curly maple board at our local woodshop. To give this piece a "mat" or framed area, I squared the corners around the dog, which also helped with the framing process. However, you can easily round off the 90° angles to create an oval shape that may fit into a narrower plank, possibly with a live edge. Kerry used a piece of Honduran mahogany for the frame to beautifully emphasize the red-gold in the maple and bring out the colors in the dog. He measured and built the frame according to the final dimensions of his curly board. Depending upon your preferred thickness and availability of wood, your frame will vary.

CURLY SUE

SUPPLIES

Wood: curly maple or wood of choice—one piece 3/4" x 10" x 13"; Baltic birch or other plyboardone piece 1/8" x 10" x 13"

Tools: scroll saw with No. 2/0 spiral blades: drill with assorted bits; square

Temporary-bond spray adhesive or Removable

Adhesive Paper

Sandpaper

Black spray paint

Clear shellac spray

Wire nails, 1/2

Wood for frame (optional)

INSTRUCTIONS

Using your method of choice, apply your pattern to the clean surface of your wood. We use Removable Adhesive Paper for ALL of our scrolling projects. Because of the thickness of the wood used for this design, it was cut individually, rather than stack cut. Make sure your blade is square and check your square while scrolling. Pre-drill all your holes, and make starter holes at the end of all the single lines, such as the lines on the muzzle. Cut out the smaller areas first. Kerry cut this pattern following the usual "center-working-out" method. Of course, let your own experience guide your hands and direct your blades.

When you are finished, remove the pattern. For those of

you who have discovered the ease of working with Removable Adhesive Paper, just peel off the pattern! Otherwise, remove your pattern using your preferred method and clean the wood surface. Sand the back of the board.

Cut the 1/8"-thick plyboard to match the size of the finished piece. Spray paint the plyboard black, or use your color of choice, and let dry.

To finish, Kerry inserted the scrolled maple piece into the frame. He then placed the plyboard on the back and tapped it into the maple using 1/2" wire nails. (Make sure the nails don't go all the way through your piece.) Then he applied several coats of clear shellac spray. There aren't any very delicate or fragile "Don't-louch-'em!" pieces on this project, so a glass overlay is not really necessary. The clear shellac coat provides a smooth enough finish that you can simply dust it off as needed.

We are SKWoodWorks, which stands for "Shelli Kerry Woodworks," For more information, or for questions concerning this project (including questions for Kerry about framing this piece), visit our website, www.skwoodworks.com, or send a SASE to: SKWoodWorks, P.O. Box 583, Pleasant View, TN 37146. Lusually draw in standard 8-1/2" x 11" letter-size patterns for easy cutting, mounting or framing. We sell the adhesive paper, finished pieces and patterns off of our website. Pattern requests and suggestions are always welcome! 😭

VILDWOOD DESIGNS

Supplying the hobby industry since 1985 www.wildwooddesigns.com • 1-800-470-9090

Our Inserts Are a Great Buy At Any Quantity. . Mention code 0509CWA



White Arabic



White Roman



Ivory Arabic



Ivory Roman



Gold Arabic



Gold Roman



CALL FOR OUR FREE CATALOG



Economy 17/16" Mini Quartz Inserts Stock

Quantity Pricing # 1+ 5+ 10+ 25+ 50+ 100+ 26412 \$3.85 \$3.65 \$3.35 \$2.95 \$2.75 \$2.65 2" Economy Mini Quartz Inserts

26423 \$5.25 \$4.95 \$4.65 \$4.45 \$4.15 \$3.95 23/4" Inserts - Available in White Arabic & White Roman Only

26401 \$4.45 \$4.25 \$3.95 \$3.70 \$3.35 \$2.95

11/4" Gold Valentine Inserts				
1+	10+	50+	1004	
\$1.95	\$1.65	\$1.45	\$1.25	
\$5.15	\$4.45	\$3.95	\$3.35	
	1+ \$1.95	1+ 10+ \$1.95 \$1.65		

New Larger Size Heart Inserts 11/8" outer rim diam, flts 13/6" hole Metal Case w glass lens. 3 year warranty.

27097 White Arabic \$6.95 \$5.95 \$4.45 \$4.25 27098 Photo Frame \$2,35 \$2.05 \$1.80 \$1.65



Photo Insert



FREE BATTERIES INCLUDED except photo frame



White Arabic



White Roman

Gold Arabic



Pink Arabic



Ivory Arabic



Ivory Roman





The Tree Swing

by John Polhemus (aka "The Little Engineer")



SUPPLIES

Wood: mahogany (or wood of choice)—one piece 1/4" x 5" x 5" (for tree swing design), one piece 1/4" x 2" x 7" (for base)

Tools: scroll saw and No. 3 blades; drill press with No. 60 and 1/16" drill bits; awl or nail

Temporary-bond spray adhesive

Cyanoacrylate (CA) glue

Sandpaper, assorted grits

Introduction

I grew up in a rural area where large families were the norm. Being one of nine children, of which I was number three, had its benefits. One was that there was always someone to play with, whether they liked it or not. Despite the broken bones and teeth, cuts, and contusions, we had a lot of fun. I can't remember ever being bored as a kid.

We had the perfect climbing tree in the woods behind our house. Our parents called it the "Monkey Tree." We thought it was just a funny name they gave it because we where always playing in it. Really, it was because they knew they'd find their little monkeys there when it was time to call them in to be fed and locked up for the night.

This pattern isn't representative of my siblings and me because the children in this scene are normal! It's a friendly setting with a nice, safe swing. Anybody caught under our tree would have been ducking falling objects, like the time one of the swing ropes broke just as my sister got the swing going full tilt. (I still say it was just a coincidence that one of my brothers was up in the tree with a hatchet at the time.) Looking back on our childhood, I don't know what amazes me more: that my siblings and I survived it or that our parents did!

INSTRUCTIONS




Recommended interior areas to be cut first.

Apply the tree swing pattern to the wood. Cut the outside of the pattern, Drill 1/16" blade access holes, and cut the interior holes, the veining cuts of the tree, and the smaller areas around the children. Some areas are too small for a 1/16" drill bit, so use a No. 60 in those spots. Save the larger areas, such as between the frame and the swing rope, to cut last.



Cutting beveled edge of base.

Apply the base pattern to the wood you've chosen. Tilt your saw table 20°, and cut the base so the edge bevels outward from the top to the bottom.



Make holes at "X" marks on base.

There are two "X" marks inside the dashed outline on the base pattern. They indicate where to place the tree swing on the base. Use an awl, nail, or small drill bit to make holes at the "X" marks on the base. The holes, which will remain after the base has been finish sanded, will be used to align the tree swing to the base.



Aligning and gluing the tree swing to the base.

Finish sand the tree swing and base. Apply CA glue to the bottom of the tree swing and align it on the base by covering the holes. Apply the finish of your choice.

For questions concerning this project, send a SASE to: John Polhemus, 3000 Charleton Ct., Waldorf, MD 20602; email: fretsawyer @verizon.net



PEN AND PENCIL BOXES USING



SUPPLIES

Wood: wood of choice—one piece 1/4" x 3-1/2" x 15" long (for sides and bottom of box with dovetail joints), or one piece 1/4" x 3-1/4" x 15" (for sides and bottom of box with box joints); scrap wood—four pieces 1/2" to 3/4" x 2" x 3-1/2" (for clamping box sides)

Tools: scroll saw with No. 5 reverse tooth scroll saw blades; straight edge and utility

knife; belt sander; two pairs of pliers; two clamps, screw type or quick grip Wood glue Glue stick or spray glue

Clear packaging tape Sandpaper, assorted grits Sharp pencil

Clear finish of choice

Introduction

Dovetails and box joints have been around for hundreds of years. Through the years, they have been cut by hand, band saw, scroll saw, table saw, and router table. This article shows how to use your scroll saw to make a box with dovetail or box joint corners that would be handy for holding pens and pencils and other objects that clutter your desk.

Any 1/4"-thick wood can be used. All the waste from cutting the joints will fit in one hand. Using combinations of contrasting woods for the box sides will draw attention to your wood joinery. Red oak, poplar, and aspen are often readily available at your local home improvement store. Other good choices include ash, cherry, mahogany, and maple; many more wood choices are available through the advertisers in this magazine.

HROUGH DOVETAILS AND BOX JOINTS

INSTRUCTIONS




it would be a good idea to practice cutting and gluing the joint you want to make using scrap wood or less expensive woods. You will need two pieces, each measuring 1/4" x 1-1/2" x 3-1/2", to practice the dovetail joint, or two pieces, each measuring 1/4" x 1-1/2" x 3-1/4", to practice the box joint. By practicing on scrap wood you will better understand the difference of cutting to the line versus on the line, as mentioned in the instructions, so the joints will fit properly. You will also get the feel for how much glue to use, including how to apply it and clean up glue squeeze-out before you start using your "good" wood.

before you start using your "good" wood.

Cut four 2-3/4"-long pieces from the wood you have chosen for either joint type. These will be the sides of your box. (The remaining piece will be used to make the bottom of the box.) Apply clear packing tape to one side of each of the four pieces.

There are four "Pins and Tails" sets of joint patterns in the pattern section. Two are dovetail joint patterns and two are box joint patterns. Choose the pattern for the joint type you want to cut and make four copies of it. Use a straight edge and sharp utility knife to cut each of the patterns exactly on the dashed lines.


Use a glue stick or spray glue to apply a "Pins" pattern to each long end of two of the pieces of wood for the sides. Apply a "Tails" pattern to each long end of the other two pieces of wood for the sides. The end of the patterns with the dots must be flush with the edge of the wood and centered to the width of the wood.



Stand one of the pieces on end on a flat surface, so the edge with the dots is down. Place another piece flat on the surface and against the piece standing upright. Use a sharp pencil to trace the edge of the piece laying flat onto the pattern on the piece standing upright. This depth line is traced, instead of being printed with the pattern, so it will match the exact thickness of the wood you are using. Repeat this process on both ends of all four pieces of wood.

Note: Where it says "split depth lines" on the patterns, it means you should cut right on the lines you just traced. Where it says "leave lines," it means you should cut just to the line so you can still see the line, but not the white paper between the line and the cut.

Making the sides with dovetail joints




Start with the two side pieces that have the patterns labeled "Tails" on them. The spaces with a dot in them will be cut away. Cut down to the depth line you traced, leaving the line with the space that does not have a dot in it.



Back out of the cut, and cut from the edge of the wood, through the dot to the traced depth line, then to a corner. Turn the wood around and finish cutting the traced line to the other corner.


The two side pieces with the patterns labeled "Pins" on them are cut next. Tilt the right side of your scroll saw table down 14°. Using a No. 5 blade, cut right on the pattern lines marked "R" down to the depth line you traced. Tilt the left side of your scroll saw table down 14°. Using a No. 5 blade, cut right on the pattern lines marked "L" down to the depth line you traced.



The spaces with the dot will be cut away in these two pieces also. Because the left and right sides were cut at 14°, a special technique is used to cut away the waste wood. The ends of a blade will be twisted so the teeth face to the right, and the right side of the saw table will be tilted down. Then, instead of standing in front of the saw and cutting, you'll stand at the right side of the saw and cut away the waste wood.

Twisting the blade ends

Install a blade in your saw. With the blade in the full up stroke, use a felt-tipped marker or pencil to mark the blade where it comes through the table. When you twist the blade, you don't want the twist to come up through the table and ruin your cut. Note: If the mark ends up being on the teeth, drop the mark down to the point where there are no teeth. You will be twisting the blade at this mark, and it will make the blade too weak if you twist it



Grasp the blade with a second pair of pliers just below the first pair of pliers, leaving about 1/4" between them to allow the blade to twist. Twist the blade so the teeth face to the right.

With the blade still upright as it would be in the saw, grasp the top of the blade with a pair of pliers just above where the teeth end. Grasp the blade with a second pair of pliers just above the first pair of pliers, leaving about 1/4" between them to allow the blade to twist. Twist the blade so the teeth face to the right.

Tilt the right side of your scroll saw lable down 14° and install the twisted blade in your saw. The teeth should be facing to your right when you are in front of the saw. Move to the side of the saw and make some straight line test cuts on a piece of scrap wood to get a feel for the blade's tracking direction. When you are comfortable cutting with it, cut the waste material from the spaces with a dot in them.

(The assembly for both boxes is the same and follows the instructions for cutting the box type joint.)


Making the sides with box joints

Start with the two pieces with the patterns labeled "Tails" on them. Cut the spaces with the dot in them down to the depth line you traced. Cut so you just leave the line on the space that does not have a dot in it (as shown for cutting the dovetail joint tail pieces). Back out of the cut and cut from the edge of the wood, through the dot to the traced depth line, then to a corner. Turn the wood around and finish cutting the traced line to the other corner.

On the two pieces with the "Pins" patterns on them, cut on the line, instead of leaving the line, and finish them the same way as the tails pieces.

Gluing up the box sides

Remove the patterns and tape from the box sides and sand off any wood fuzzies on the joints. Dry test fit the joints and make any needed adjustments to the tails side of the joint. If a joint is snug or fits halfway, it may only need to be tapped in place with a hammer and block of scrap wood. Just be sure it's not so tight it would split the wood.



Put a small puddle of wood glue on a piece of old newspaper. Use a toothpick or old scroll saw blade to apply glue to the pins and tails and put the joints together. Use four clamping blocks and two clamps to clamp the box sides together. Remove any glue squeeze-out from inside the joints of the glued up sides. A flat blade screwdriver works well for this. **Note:** Dovetail joints seem to clamp up OK, but box joints can slip out of position. Check the box with a square before the glue sets and adjust as needed.

Making and attaching the box

Use a belt sander to flatten both ends of the glued up box sides. Set the box on the wood for the bottom and trace around the outside edges of the box. Cut the bottom just outside the pencil lines so it will be slightly larger than the actual base of the box. Glue and clamp the box bottom onto the box sides. Clean up any glue squeeze-out on the inside of the box. After the glue dries, use the belt sander to sand the sides and box bottom smooth. Apply the finish of your choice.





Half dovetail and box joint keys

You can also make interesting joints that look like half dovetail and box joint keys. If making the dovetail joints, reduce the width measurements of two box sides by 1/2", so they measure 1/4" x 2-1/4" x 3-1/2". (The other two sides will remain at 1/4" x 2-3/4" x 3-1/2".) Glue a 1/4"-thick x 1/4"-wide x 3-1/2"-long strip of contrasting color wood to the two long edges of the smaller box side pieces. All four sides will now be 2-3/4"-wide. Let the glue dry completely, then cutout the dovetail joints as in the previous directions. For the box joints, follow the same process, using 3-1/4"-long box sides.

For questions concerning this project, send a SASE to: Gary MacKay, 2779 Canvasback Trail, Myrtle Beach, SC 29588; email: gmackay@sccoast.net



retwork

by Dan and Ray Wilckens





SUPPLIES

Wood: wood of choice*—two pieces 1/4" x 6-1/2" x 9-1/2" (for box base and lid), fwo pieces 1/4" x 3-1/2" x 7" (for box front and back), two pieces 1/4" x 3-1/2" x 3-1/2" x 3-1/2" (for box sides), one piece 1/4" x 3-1/2" x 6-1/2" (for box support), one piece 1/8" x 3-1/8" x 6-5/8" (for front overlay), two pieces 1/8" x 3-1/8" x 3-5/8" (for side overlays), and one piece 1/8" x 4-3/8" x 7-3/8" (for top overlay) top overlay)

Tools: scroll saw; drill press with very small drill bit (for starter holes); table saw or similar saw; planer (for proper wood thickness); belt and/or handheld sander: X-acto knife or needle pick; assorted clamps

Temporary-bond spray adhesive Wood glue

Sandpaper, assorted grits

Masking tape

Double-face tape

Spray lacquer finish

Brass butt hinges, No. 39147 (two)**
Suede-Tex flocking***
*Darker wood was used for the 1/4"-thick box pieces, and lighter wood for the 1/8"-thick overlay pieces. **Available from Klockit, 800-556-2548,

***Available from DonJer Products Corp... Info@donjer.com, 800-336-6537

Instructions

Preparing the wood

Copy the patterns, saving the originals for future use. Plane selected wood to proper thickness. Cut wood to size of patterns. All straight-edge pieces should be cut to size on a table saw or equivalent for accurate dimensions and straight edges. Cut scroll saw edges oversize.

Attach the patterns to the wood using a temporarybond spray adhesive. (It takes practice to know the right amount to apply. Apply too much, and the pattern is hard to remove; not enough, and the pattern may come loose during sawing.) When attaching the patterns, align the straight edges of the patterns with the straight edges of the wood you have cut.

Using a small drill bit, drill a hole in the waste area of each cutout. Feed the scroll saw blade through the small holes and cut along the lines. Feed the blade through the next hole and so on, doing all the interior cuts first. For exterior cuts, you can cut in from the edge or drill a small hole just outside the exterior line.

Remove the patterns from the wood by peeling them off. You may try using a hair dryer to remove some pieces if they are attached too firmly. Be careful because some cuts are very fragile. Sand pieces using a belt sander or handheld sander. Remove any burrs and clean up any cuts using an X-acto knife or needle pick.


Assembling the box

Throughout assembly, fill any seams with a bead of glue, and sand while the glue is still wet. This should fill the seams to match the parent wood.




Glue the box sides (B) to the box support (D). Make sure these are flush on the ends and the bottom. Sand as needed.

Glue the box front and back (C) to the box assembly. These need to be flush on the ends and the bottom. Sand as needed.





Center and glue the box bottom (A) to the box assembly.





Center the lid overlay (E) on the lid and glue in place.






Center the front overlay (F) on the front of the box and glue in place.

continued on page 38

Creative Woodworks & Crafts September 2005 • 37





Center the side overlays (G) on the sides of the box and glue them in place. Allow all glue to dry for one hour.

Attach the small hinges to the top back of the box assembly. (Note: To assist in positioning the hinges, apply a small piece of double-face tape to the backs of the hinges.) Carefully drill pilot holes, which are smaller than your hinge screws, in the center of the holes in the hinges. Be careful not to drill through the wood. Start the small screws, but do not completely install them. Remove the screws and sand them shorter, so they will not go through the project.

Remove the tape from the hinges and, after placing a small amount of furniture wax on the screws, attach the hinges. Clamp the lid and the box assembly together, making sure that they are lined up, and mark the location of the holes in the hinges on the lid. Unclamp the lid and the box and drill the pilot holes in the centers of the marked holes. Attach the hinges to the lid using the same process.



Remove the lid from the box. Apply spray lacquer to the box and the lid following the manufacturer's instructions, and allow it to dry completely.



Use masking tape to mask off the top edge surfaces of the box. Flock the entire interior of the box, following the manufacturer's instructions to apply the initial coat of flocking adhesive and then the flocking itself. When all the surfaces are completely covered, allow the box to sit undisturbed for 10-12 hours. After complete curing, turn the box over and pour out the excess flocking to be saved and used for a future project. Reattach the lid, and enjoy your new box!

For questions concerning this project, send a SASE to: Wilckens Woodworking, P.O. Box 52096, Independence, MO 64052. Email: wilkswood @ col.com

38 • Creative Woodworks & Crafts September 2005



Line boxes in seconds with

"Suede-Tex" Spray-on Suede

No Messy Cutting & Pastina just FLOCK IT!

- Available in over 30 colors
- Simple & Economical
- · No skill required

Call for information & color chart 800-336-6537

DonJer Products Corporation 13142 Murphy Rd., Winnebago, IL 61088

> Outside USA 815-247-8775 FAX 815-247-8644

> > www.donjer.com

MEMPHIS HARDWOOD LUMBER, INC.

6535 CHURCH ST. MEMPHIS, NY 13112. 1-(800) 286-3949 (315) 689-3949 www.memphishardwoodlumber.com

WHY CHOOSE MEMPHIS HARDWOOD LUMBER? HERE'S WHY:

- * FAST COURTEOUS SERVICE!
- 27 YEARS IN BUSINESS!!
- WE MAINTAIN AN INVENTORY OF 60 SPECIES, BOTH DOMESTIC AND IMPORTED HARDWOODS!
- HIGH-QUALITY, MILLED ACCURATELY AND CONSISTENTLY!
- COMPETITIVE PRICING!

BALTIC BIRCH PLYWOOD

1/8" thick - 12" x 30" - \$1.79 (that's 69¢ per square fr.t)

1/4" thick - 12" x 30" - 52.48 (that's 99¢ per square ft.!)

TOP-OUALITY HARDWOODS

we sell top-quality hardwoods 1/8", 1/4", 3/8" and 1/2" thick at GREAT PRICES!

CUSTOMIZED GLUED-UP HARDWOOD PANELS

Available in any dimensions in thicknesses of 1/4", 3/8", 1/2", and 3/4". Call for pricing.

1-800-286-3949 🎑









You Name It, Our Fonts Print It!

Scroll Saw Software Patterns

Space Letters to be.

Print your pattern, Apply to a board and Cut! Yo more tracing from templates - Yo more copy magninest

WoodTrax 4.0! Unlimited Name Patterns.
Patterns of 50 states & USA



- · Board Foot Calculator · Use our Fonts in Other Applications
- Double-Sided Pattern

 Multiple Patterns
 Use Other Fonts in WoodTrax

 - Scroll It English · Scroll It Script · Vertical Lettering in Original Lines Font



WoodTrax Professional!

- Everything Wood Trax 4.0 PLUS
- Adding, Scanning & Cropping Images
- Add Text with Different Colors
- Draw Circles, Squares, Lines and More
- Zoom Several Ways
- · Thirty-Five New Patterns







Additional Fonts Available

Scroll It Extra Bold

Scroll It Bold

WOODTRAX

1-800-939-4414 www.pswood.com



Shepard (#191) Beginner 12" x 8" 40 pcs.

\$7.95



Dragon #2 (#195) Beginner 19" x 17" 29 pcs..\$7.95



Draft Horse (#193)

Advanced 17" x 17" 134 pcs....\$7.95

Woodworkers Clock #2 (#194) Intermediate

20" x 11" 61 pcs. \$7.95



Pumpkin (#186) Intermediate 58 pcs...57.95

Candle & Snowman (#185)

Candle: 10" x 8": 18 p

Snowman: 16" x 9": 32 pcs




Experience the optimum in scroll sawing pleasure NEW EXCALIBUR EX-21 TILT

The unique "Rack & Pinion" gear operated head tilts to your desired angle from a full 45 degrees left to 45 degrees right! Excalibur's "Tilt Head" design takes the work out of angle cutting while adding precision.



#EX-21 Features:

- 21" Throat Depth 2" Thickness Capacity
- EXCALIBUR'S Proven Link Drive Design
- Tilting Head Glides Smoothly On A Rack & Pinion
- Finger Operated Blade Clamps
- Extra Large Table (13 1/2" X 23 1/2")
- Easy Access Speed and Tension Controls
- Built-In Blade Tube Storage On Both Sides Of Base
- Excalibur's Unique Top Arm Lift Capability
- * 5 Year Warranty Includes Motor & Control
- Seyco's Satisfaction Guarantee
- Options Available Stand; Footswitch; Magnifier Worklamp & Dust Collection/Vacuum System.



Top Arm lifts for easy "top down" blade insertion for inside cuts and can also lock in the up position if desired.

#EX-21 \$849.00 Introductory Special \$799 Plus Shipping



TO ORDER:

CALL SEYCO at 800-462-3353 or

visit our secure website at


http://www.seyco.com/sawspcl.html

And click the Add To Cart Button or

Mail to Seyco, P.O. Box 1900, Rockwall TX 75087

ING HEAD SCROLL SAW

Scroll saw artist Wayne Fowler was among the first to have put this new machine to the test, and here's what he says about the EX-21:



Before I tell you about the new Excalibur EX-21 scroll saw, my code of ethics requires me to tell you about two conflicts of interest I have. First, I have been cutting on Excalibur saws for about sixteen years. Secondly, I am a proud Canadian, and the Excalibur is made at a plant about 20 minutes from where I live here in Canada! While those two factors may tend to bias me favorably toward the new saw, I will try my best to give an unbiased review of my experiences with it.

I had the opportunity to use the new saw at the Toronto Workshop Show this past March. I was able to cut on it, between conversations, for three days during the show. The first noticeable difference between the EX-21 and just about any other saw is the fact that the saw table is fixed, and it is the saw itself that tilts in either direction for angle cuts. The second major difference for current Excalibur owners is that the cutting plate is much larger than on the EX-30 or EX-19 saw. Although I have never found the size of the plate on the older saws to be an issue, the bigger plate does provide some level of comfort. As with the older saws, this plate has a low friction powder coat to minimize drag on the wood as you cut.

The tilting mechanism

The EX-21 saw is mounted on a central "axle," with a crank on the front for tilting it in either direction. There is a dial for selecting the angle of tilt and a plunge mechanism to ensure that the saw has been returned to 90°. Both are very useful features. The method of placing the saw at 90° using the spring plunger and hole behind the dial is very precise, and I certainly need that precision for some of our finer designs. I used the saw to cut a tiger head drawn by my son Jacob on 1/2"-thick mulberry, and I was quite pleased with the outcome. The design has a lot of fine line detail, particularly its whiskers, and the many close cuts were all handled well by the saw.

Blade changes

Whenever anyone asks me what scroll saw to buy, I always suggest that they have the salesperson show them how to change the blades, then imagine doing that 20,000 times! I was pleased that the EX-21 has a blade holding system similar to the EX-30 that I cut on, although I found the EX-21 mount a little easier to use. The clamp mechanism is the same, but there is a wider, longer slot for the blade to go into so it is easier to find when you are not looking. That may sound odd but, as with other Excalibur saws, when you are doing fretwork you enter from the top of the piece and attach the blade on the bottom. I have done this probably 50,000 to 100,000 times with all the fretwork that I do, so it is extremely important to me that the reattachment process is fast and easy.

Because I like to insert the blade into the hole from above when doing fret cutting, and since that is the best way to insert the blades on the Excalibur, I find it is a very handy saw for fretwork. One big improvement with the new saw is that the arm can remain elevated by itself. Due to this feature, I could use both hands to position the wood and thread the blade into the hole without using my wrist to keep the arm raised. The only downside that I found about this was that the arm sometimes

had a tendency to lower quickly, resulting in some bent blades. Once I got used to the differences, however, I achieved a modest increase in the speed at which I normally fret cut on my

Angle cutting

The angle mechanism for tilting the saw is very precise, so if you need to be 2° right or left of true, it is very easy to set the saw for that angle. I cut two very small burl castles at the show and was able to make accurate adjustments, down to fractions of a degree, as I cut the smaller and smaller layers of the castles. I was also able to cut very thin walls, mainly because the cutting surface and the plate remain parallel to the ground as the saw tilts. Another benefit to the plate remaining in the same position was that I didn't have to change my cutting posture for angle cutting. With my current saw, I sometimes have trouble seeing what I am cutting when the plate is tilted, and I need to lean over and angle my head. I also had better light for cutting since the light was above me and not to the side.

A few other observations

I am a left-handed person in a right-handed world, so I had a few issues with the EX-21 configuration which is, as with most saws, better designed for right-handed sawyers. After talking this over with the saw designer, we decided that the saw could be made more "left-hander friendly" by simply detaching and reattaching the blower and hold-down clamp on the right side of the saw. This still left me with the problem of the arrangement of the tensioning arm and speed control dial on the upper arm, however. I kept accidentally hitting the speed control dial with my left arm as I was fret cutting because I worked the tensioning lever with my left hand. I would then have to stop to readjust the speed. This was an inconvenience, but not a big problem, as I am sure that I would get used to the control arrangement given more time to practice.

I was pleased that over the three days of cutting I didn't break any blades, although I did dull out a few, and I changed blade sizes a number of times. Because I wanted to see what would happen if I did break a blade, I removed the blade and started the saw at full speed. The saw ran quietly with very little bounce, so I assume that damage would be minimal during a

The motor on the EX-21 is a variable speed direct drive and seemed to be quite powerful. However, I didn't cut extra-thick hardwood, so I can't comment on how strong the EX-21 is in comparison to other saws that I have cut on. Finally, the dust blower on the EX-21 is quite a bit better than the one on the EX-30 and is much easier to position over the work piece.

General impressions

I really enjoyed my stint with the EX-21, (even though it is purple and not basic black), and I am certain I could find room in my workshop for the new saw. However, I am also still very much enthralled with my EX-30, so I am currently trying to work out an excuse to purchase the EX-21 for my wife! So far, my main justification is the EX-21's superior angle cutting. I guess I'll need to generate a little revenue, so I'm off to the next Star Trek convention, where my burl castles have been selling well!

ARE AND COLT: by Marilyn Carmin Finish of choice 42 • Creative Woodworks & Crafts September 2005.

SUPPLIES

Wood: wood of choice—one piece, approximately 5" x 14" Tools: scroll saw with No. 5 (12.5 TPI) blade; drill with No. 58 drill bit Temporary-bond spray adhesive Sandpaper, assorted grits Leather, or other backer material of choice




Introduction

After originally cutting this design from wood, I decided to experiment with several different applications of the same pattern. The supply list is for the main wood-cut piece, and directions are provided for the three variations.

INSTRUCTIONS

Using spray adhesive, attach the pattern to your piece of wood. Drill for all inside cuts and cut out. Sand as needed; then apply your finish of choice. Cut a piece of leather or other backer material of your choice, and attach to the back of the wood.

TATIONS ON A PATTERN



For Corian horses:

Use a No. 5 wood blade to cut the design from a piece of Corian countertop material. The color of the Corian can make a difference as to how it cuts, so you may need to experiment with some different pieces. An application of beeswax on the blade can aid in the cutting. When finished, apply green felt or other material of choice for a backer, and glue a length of rope around the outside of the Corian to frame it.

For metal horses:

Sandwich a piece of sheet brass, available at most craft stores, between two pieces of thin plywood. Attach the pattern to the wood, then cut through all layers using a No. 5 wood blade, which works well when cutting metal. To color the metal, apply a brush-on or spray liquid patina, which causes a chemical reaction with the brass. Glue the cut metal piece to a wood backer board, and finish by outlining the piece with tapestry tacks.

For birch horses:


Cut the pattern from 1/4"-thick Baltic birch and insert in a frame.

Push yourself a little with your patterns. Step out of the box, color outside the lines, and watch yourself grow as an artist!

For questions concerning this project, send a SASE to: Marilyn Carmin, 4569 NE 78th Place, Portland, OR 97218.



JG PUPPLES



SUPPLIES

Wood: basswood or wood of choice—one piece 3/4" x 12" x 14"; Baltic birch plywood—one piece 1/8" x 9" x

Tools: scroll saw with No. 5 and No. 2 skip-tooth blades; drill with assorted small bits; router and 1/4" roundover

Temporary-bond spray adhesive Sandpaper, assorted grits Tack cloth

Tacky glue Golden oak stain Acrylic paints in aqua, black, dark beige, leaf green, pumpkin orange, white, and yellow

Paintbrushes |

Clear finish Sawtooth picture hanger

Introduction

The sweetness and curiosity of pupples always make me smile. I painted the pupples in this project so they would appear more lifelike. A little stain and thinned paint can make all the difference.

INSTRUCTIONS

Copy the pattern, and save the original for later use. Sand the wood smooth and wipe clean with a tack cloth. Spray the back of the pattern with a medium-light coat of the spray adhesive, wait a few minutes until the glue feels tacky, then adhere the pattern to the center of the wood.



Draw a 2"-wide oval around the entire perimeter of the pattern, and cut along the traced line.



Drill the pilot holes for the design. Do NOT drill the circles on the butterfly wings. They will be painted later. Make all the inside cuts using the No. 2 blade.



Tilt the table 4° degrees to the left. Using a No. 5 blade and cutting to the right, cut out the outer frame.



Push the center section back into place to check the fit.

Adjust if necessary.

continued on page 46



Remove the center section from the frame. Sand the frame, slightly rounding the inner edge. Using a 1/4" roundover router bit, roundover the outside edge and sand it smooth. Tack to remove the dust. Stain the frame, wipe it dry, and set it oside to cure.



Trace the perimeter of the center section onto the plywood. Cut along the traced line to make the backer.



Paint the backer using white and aqua paint, creating the effect of a streaked sky. Set it aside to dry.



Paint the top and inner edge of the center section to match the backer.



Thin the dark beige paint with water. Apply a very light coat of paint to the puppies' heads and bodies, letting the wood show through.



Using thinned black paint, lightly paint the ears and eyes. Add more of the thinned black paint to deepen the color where needed. Paint the eyeballs dark black and dot them with white paint.



Paint the center of the butterfly wings first with thinned yellow paint, then with some thinned orange paint. Using black paint, paint the wing edges, the vein lines, and the body. Use white paint for the dots. Paint the flower petals using thinned white paint. Paint the flower centers, including the holes in the flower centers, using yellow paint. Using thinned green paint, paint the grass, adding more of the thinned green paint where needed to deepen the color. Let dry.



Apply a coat of clear finish to the backer, the center section, and the frame. Let dry. Insert the center section into the frame. Use tacky glue to glue the backer to the center section, and place a weight on it until the glue dries. Center and attach a sawtooth picture hanger to the top back of the center section, then push the center section toward the back of the frame until it locks into place.

For questions concerning this project, contact BJ at BJHolm51@yahoo.com or visit her live chat at www.wooders.com



END of SUMMER SALE!!!!

Sale Prices Effective August 1, 2005 through September 31, 2005



#2100 Deluxe Electric Version Electro-File™Tool Kit Reg \$89.95 SALE PRICE \$79.95 File, Rasp, Sand and Saw with this versatile tool kit

Electro-File™ Accessories

#111 Sanding Paddle Reg \$6.00 SALE PRICE \$2.95 #121 14-TPI Saw Blade Reg \$6.35 SALE PRICE \$2.95 #123 32-TPI Saw Blade Reg \$6.35 SALE PRICE \$2.95 #130 Wire Brush Asst. Pack Reg \$6.95 SALE PRICE \$1.95

#125 10 Pc. Diamond File Set with Case 1/8" Dia. Reg \$24.95 SALE PRICE \$14.95



#5000 Wonder-Cut™ Saw with 3 blades Reg \$19.95 SALE PRICE \$14.95
Cut any contour thru wood, ferrous and non ferrous materials
#5001Wonder-Cut™ 4 Pack Replacement Blades Reg \$6.95 SALE PRICE \$2.95

All items in stock for immediate shipment. In contiguous U.S.A. add \$8.50 for S & H. Wi residents add 5.6% sales tax.

CALL TOLL FREE TO ORDER 1-877-872-0924

You must use code 7438 when ordering for Special Prices
Precision Hobby Tools, Inc. • P.O. Box 195 • Hubertus, WI 53033
We Believe That Quality Is In The Details









Chirping Chickadees Wall Pocket

designed by John Nelson, sawn and developed by John Polhemus



SUPPLIES

Wood: mahogany—one piece 1/4" x 11-1/2" x 18" (for chickadees and pocket parts), and one piece 1/4" x 11-1/2" x 12" (for backer)

Tools: scroll saw and blades; drill press with assorted drill bits; small square; circle template or washer; awl or small brad nail Temporary-bond spray adhesive Cyanoacrylate (CA) glue Sandpaper, assorted grits Black Aqua Oil* or stain of choice


Mounting screws, appropriate for wall mounting (two) *Available from Cash Coatings, (608) 222-2445

Introduction

This wall pocket designed by John Nelson could be a handy place to stash your watch, wallet, and keys at the end of the day. It's an excellent companion piece for his Doves Among the Leaves Hat Rack featured in the March, 2005 issue of Creative Woodworks & Crafts[®].

I chose to use mahagany for this project and apply black aqua oil to the surface of the backer, but you may choose a different type of wood for the backer, without applying any stain, for a different effect.

INSTRUCTIONS



Patterns applied for cutting.

Apply the patterns for the chickadees and pocket parts to the larger piece of mahogany so the grain of all the pieces runs from side to side. Whether to cut the exterior of the parts first or drill and make the interior cuts first is up to you. Separate the pieces for the sides, front, and bottom of the pocket by cutting along the dashed lines on the pattern. (DO NOT cut on the dashed-lined rectangles on the chickadees piece. Those lines are used for placement only.) Sand the back of the cut chickadees piece.



Circles on chickadees pattern for mounting hole covers.

There are two circles in one of the waste areas of the chickadees pattern. These will be covers for the mounting holes after the finished wall pocket is mounted to the wall. They will be bevel cut like the backer board, so set the piece with the two circles aside until the backer board is cut.




Drawing the pattern line for the backer board.

Finish sand the face of the backer board, then wipe on black aqua oil with a clean rag. When it is dry, center the chickadees piece on the backer board and glue in place. Make a pattern for the backer board by tracing around the chickadees piece using a circle template or a washer.



Cutting the backer board.

Tilt your saw table 20° and cut the backer board along the traced line, so the edge tapers outward from top to bottom. Because the cut edges of the backer board are not treated with black aqua oil, they will match the chickadees and pocket parts, while contrasting with the surface of the backer board.



Cutting the mounting hole covers.

With the saw table still angled, cut the circles for the mounting hole covers, again tapering the edge outword from top to bottom.

continued on page 50


Creative Woodworks & Crafts September 2005 • 49



Countersink holes for mounting screws.

Where indicated on the chickadees pattern, drill countersunk mounting holes for the heads of the mounting screws,

There are dashedline rectangles on the chickadees pattern that indicate pocket placement. Use an awl, brad nail, or small drill bit to make a hole just inside the upper and lower inside corners of the rectangles. These holes will remain after the pattern is removed and the wood is fin-



Make alignment holes.

ish sanded and will be used to align the sides of the pocket with the chickadees piece.

Remove the patterns from all the pieces and finish sand them. When assembling the pocket, the face piece will not be glued to the side pieces. Rather, the tabs on each end of the front piece fit through the slots in the side pieces to hold it in place. Test fit those pieces before the pocket is assembled. If the tabs are too lhick to fit the slots, sand the face of the pocket until they fit freely. Don't enlarge the slots in the side pieces to make the tabs fit because it will weaken the side pieces!



Align and glue on the left side pocket piece.

Apply CA glue to the back edge of the left side pocket piece. Position it on the chickadees piece so the upper and lower inside corners just cover the alignment holes. Use a square and hold the side piece in place while the glue sets.



Pocket parts held in place while marking position of bottom piece.

Insert the left tab of the front piece (remember, no glue!) of the pocket through the slot in the left side piece just glued on. Test fit the remaining pocket pieces, without gluing them in place. Position the right side piece by inserting the tab into the slot and covering the alignment holes. Put the bottom pocket piece in place, and check it with a square. Use a pencil to lightly mark the underside of the bottom piece where it cames in contact with the glued-on left side and chickadees piece. Set the front and right side pieces aside.



Gluing on the bottom piece of the pocket.

Apply CA glue to the left and back edges of the bottom piece; align them to the pencil marks and hold in place until the glue sets.

Apply CA glue to the right edge of the bottom piece and the back edge of the right-side piece where it attaches to the chickadees piece. Insert the right tab of the front piece through the slot in the right-side piece while aligning the side piece, the same way as the left side was done. Hold in place until the glue sets.

Apply the finish of your choice to the wall pocket and the mounting hole covers. Once they're dry and the wall pocket is mounted on the wall, the hole covers can be attached. Two very small dots of CA glue will do the job. The covers can be pried off with a sharp knife if needed in the future. Although double-sided tape, rubber cement, or spray glue can also be used to attach the hole covers, their bonds may weaken over time, causing the covers to fall off.

For questions concerning this project, send a SASE to: John Polhemus, 3000 Charleton Ct., Waldorf, MD 20602; email: fretsawyer@verizon.net



HELM'S WHEEL INTARSIA

by Robert T. Letvinchuck of Against The Grain Woodart™



Introduction

With a rope ladder overlay and button inlays, this piece is sure to sharpen your intarsia skills. Let's set sail on a journey that will guide you through the detailed process of creating this beautiful addition to your nautical collection. If you happen to fall overboard, send out an S.O.S. call to rob@againstthegrainwoodart.com, and I'll be happy to get you back on board!

INSTRUCTIONS

Note: For transferring patterns to wood throughout the project, use the following trace-and-transfer method. Place tracing paper over the pattern and trace your starting piece. Place the tracing paper onto chosen stock, noting grain direction. Slide transfer paper under the tracing paper, and transfer the pattern piece to the stock. Cut out the pattern piece. Trace next piece, using the edge of the previously cut piece as a template.

Continued on page 52




SUPPLIES

Wood: cherry (or medium-colored wood)—one piece 1-1/8" x 8" x 22" (for wheel); teak (or medium-dark wood)—one piece 1-1/8" x 6-1/2" x 7" (for handles), one piece 1/2" x 3" x 9" (for ship body and masts), one piece 1/4" x 4" x 8" (for wheel overlay and rope ladder); aspen (or other light wood)—one piece 1/2" x 4" x 8" (for sails and portholes), one piece 1/4" x 1" x 5-1/2" (for rope ladder overlay); black wainut (or other dark wood)—one piece 1/4" x 2" x 2" (for rings on rope ladder overlay); blue pine (or other medium-light wood)—one piece 3/4" x 4" x 11" (for water); oak (or other medium-colored wood)—one piece 1/4" x 2" x 11" (for plugs and rope ladder overlay); pine (or other medium-light, fight-grained wood)—one piece 1/2" x 1" x 3" (for rope ladder on ship); Santos mahagany (or other medium-dark wood)—one piece 1/2" x 2" x 3" (for flags)

Tools: scroll saw with assorted blades; drill with 3/8" bit; 3/8" plug cutter; router with 1/4" and 1/2" roundover bits; spindle or drum-mounted sander; ctamps

Dits; spindle or drum-moi Tracing paper Transfer paper Wax paper Sandpaper, assorted grits Wood glue Tape Finish of choice Hanger of choice



Start with the handles. Trace, transfer, and cut one handle. Use the handle as a template to trace the other five handles. Keep the inside ends square (you will round them out after frame is complete).




Use a spindle or drill-mounted drum sander to square up the edges, making sure they are at 90°.



Place the handles on the pattern and number them. Start with the top right and go clockwise.



Starting with the top right, cut, square up, and number the thicker wheel sections between the handles.



Use a router with a 1/2" roundover bil to round the outside edge of each wheel section.





Re-assemble the wheel. Trace the roundover from the wheel frame onto the handles. This line shows where to stop sanding to match the roundover of the wheel.




With the same 1/2" roundover router bit, roundover the handles up to your traced line, then finish sand by hand to match the contour of the wheel.

Finish sand all pieces cut so far. Lay down wax paper over the pattern so you will be able to see the pattern through the wax paper. Edge give the wheel back together by applying a small bead of give to the lower edges of the pieces and pressing together, making sure everything is lined up. (Too much give will cause squeeze-out that could ruin the finished piece.) Allow the give to dry thoroughly.



Cut and number the overlay sections for the wheel, making sure to mark the buttonholes. Bore the holes using a 3/8" drill bit, being sure to place a scrap piece of wood underneath to prevent breakout.



Cut 18 plugs using a 3/8" plug cutter (found at most local hardware stores). On the wax paper, glue the plugs into the holes and let dry.

Assemble the overlays on wax paper by edge gluing. Let dry.



Sand the inside of the wheel and the inner and outer edges of the wheel overlay to create even-flowing circles.

Using the router with the 1/4" roundover bit, roundover the inner edge of the wheel. Rout the edges of the overlay also using a 1/4" roundover bit. Finish sand the wheel and the wheel overlay, removing all glue residue.





Apply a small bead of glue to the bottom side of the wheel overlay and center it onto the wheel. It is a good idea to let the glue set for a short time before clamping so the overlay doesn't move around while clamping. Lay scrap pieces of wood on the overlay, and clamp the overlay to the wheel.

Continued on page 54



Cut the rope ladder overlay next. The dotted lines on the pattern represent the pieces underneath the overlay. You should ignore them at this point. Make sure to cut all edges that touch the inside of the wheel about 1/4" longer than the pattern. (The excess will be cut later.) Finish sand the entire rope ladder overlay and edge glue it on wax paper. Set aside and let dry.






Ignoring the rope ladder overlay and using the dotted lines now, cut the water and ship body, making sure you add the extra 1/4" on all pieces that touch the inside of the wheel, as when making the rope ladder overlay. Cut the ship body as one piece, first marking the portholes and board seams. Bore the portholes and cut the plugs as you did for the buttonholes on the wheel overlay, then cut the board seams and insert the portholes. To give the water depth, use a penal to mark the two pieces on the left and right sides of the ship. Sand the two pieces down just past the mark



Tape the water and ship together and position them on the pattern. Place the wheel onto the assembled pieces and place a shim at the opposite end of the wheel. Trace the cut line anto the water pieces.



Cut the pieces you just marked and fit them into the wheel, making any needed adjustments at this point.



Move the water and ship section off the pattern. Position the rope ladder overlay in place. Mark the cut line in the same manner as you did for the water.

Cut and fit the rope ladder overlay, and then set it off to the side. Contour and sand the water and ship. Place wax paper onto pattern and edge glue the water and ship to the wheel. Let dry.





Cut and fit all the masts, sails, and flags. I preferred to start from the right and work my way to the left, sanding and gluing as I went. Because this piece is intricate, you may need to make minor adjustments as you go.



Edge glue the rope ladder overlay to the water and to the wheel, using a shim to keep it level. Allow to dry.

When the project is completely dry, turn the wheel over. Rub glue into all seams and let dry. Sand the back smooth. Turn the piece over and finish sand the front by hand. Apply two coats of finish to the back, and let dry. Apply three coats of finish to the front with a light sanding between coats. Let dry. Attach a hanger, and enjoy your work of art. Happy cutting!

For questions concerning this project, or to receive a free catalog of more patterns by Robert T. Letvinchuck, write to: Against The Grain WoodArt, 382 E. 1st St., Fond du Lac, WI; or, visit us on line at: www.againstthegrainwoodart.com



CHECK OUT

CREATIVE WOODWORKS & CRAFTS NEW FORUM ONLINE TALK LIVE WITH MANY GREAT DESIGNERS FROM THE MAGAZINE!

WOODWORKSANDCRAFTS.COM TODAY!

Scroll Saw Patterns By Jett Zattino Take your scrolling to the next level with our extremely detailed patterns



Pattern Located in Full Size Pattern Section No. 2!

Turkey Beard Holder Intarsia



Around two years ago, a good friend of mine, Danny Griggs, invited me to go turkey hunting. I'd never been turkey hunting before and figured, "Why not?" Well, I didn't get a turkey, but I did find out lots of interesting things. While white-tail buck hunters are after the "Big Rack," turkey hunters are after the "beard." The beard is located on the upper chest area of the male, and the longer the beard, the better the trophy.

After hunting, Danny showed me all of his turkey beards, which were hanging here and there on noils. That was when I came up with the idea of creating a turkey beard holder. (By the way, the turkey beards in the photo are Danny's, not mine!)

SUPPLIES

Wood; oak—one piece 3/4" x 22" x 4" (for base), one piece 1/2" x 2" x 2" (for beak); walnut—one piece 3/4" x 18" x 10" (for tail feathers and body), one piece 1/2" x 5" x 5" (for ruffled neck area); mahogany—one piece 3/4" x 10" x 4" (for tips of feathers); yellow heart—one piece 3/4" x 3" x 5" (for inlay of footprints in base); purple heart—one piece 1/2" x 2" x 2" (for area around the eye); cedar—one piece 1/2" x 4" x 9" (for head and throat areas); plywood—one piece

1/4" x 22" x 15" (for backer board)
Tools: scroll saw with No. 3 Flying Dutchman blades; drill
with 3/4" forstner bit; palm sander with assorted grits;
oscillating spindle sander with assorted grits; mop
wheel

Tracing paper
Carbon paper
Sharp pencil
Ink pen
Wood glue
Super glue
USED shotgun shells
8mm orange glass eye*
Clear finish of choice
Hanger

*Available from Wildlife Intarsia Design (708) 788-6455, www.wildlifeintarsiadesign.com

INSTRUCTIONS

Trace the patterns onto tracing paper. This will allow you to choose your grain direction.




With the carbon paper, trace the face onto the wood and cut it out. The darker area around the eyes is purple heart.



Cut and fit the top of the head, the beak, and the bill, making sure there is a good 90° fit.



Cut out the throat area and fit into place.







Start rounding the neck pieces. The "ruffled" look on the neck is achieved by sanding the sides and top of each piece, while leaving the bottom with a straight edge.



Dip the center of the throat section inward, to show more detail. Drill an 8mm hole in the head area to accommodate the eye. After all rounding and sanding to the head, throat, and neck section is done, glue the pieces together, clamp, and set aside.



With the grain running the length of the pattern, trace the tail feathers onto the walnut. Align the bottom of the feathers to the straight edge of the board, so there will be a good, straight fit with the oak board.



When cutting out the tail feathers, start by cutting out the rounded body area first, then cut out the individual feathers. continued on page 58



Tip each of the feathers with mahogany, I found it was easiest to glue each tip into place as I cut it. First, make sure there is a good fit. Then, attach the mahogany tip using wood glue, and add a small drop of super glue to serve as a "clamp" until the wood glue has dried.



Cut the USED shotgun shells at 1-1/2" from the brass end. Lightly sand the cut end to fit the hole. Insert the shells into the holes, using a small amount of glue to secure. Glue the combination head, throat, and neck piece into place. Let dry.



Start rounding the feathers using the oscillating spindle sander.



Place the entire piece on 1/4"-thick plywood and trace the outer edge. Cut along the traced line at a 45° angle, and glue the plywood into place.



Trace and cut out the oak for the base. Cut out the footprints and fit with yellow heart. For the shell holes, use a 3/4" forstner bit to drill 1/2" deep into the oak base where indicated on the pattern. Sand the oak base and lightly round the edges. Glue the tail feathers and body to the oak base.



Apply a clear coat of your finish of choice. Glue the glass eye into place. Let dry, then apply a hanger to the back. Hang and enjoy your turkey beard holder (and good luck filling it up!).

For questions concerning this project, send a SASE to: Darin Liles, 252 Sam St., Shirley, AR 72153; website: www.darinswoodworks.com



Intarsia Talk Shop-Made Intarsia Accessories

By Robert J. Hlavacek, Sr., of Wildlife Intarsia Designs

Introduction

A helpful addition to your arsenal of intarsia tools is a light source that will shed some light under your project. As you cut and fit the pieces, there will be sections along the joints that will bind, causing gaps between the pieces. Working on an illuminated surface helps you quickly spot these troublesome areas. The lighted surface can be made either as a light table workstation or as a light box, and directions are provided for constructing both.



In both cases, the illumination is supplied by a General Electric Brite StikTM (available at ACE Hardware stores). The Brite Stik is a pre-wired fluorescent light fixture complete with a line switch installed, so you won't need any knowledge of electrical wiring. Just slide it under the light table or box, plug it in, and turn it on.

Any problem edges on your intarsia project that do come to light can be eliminated by sanding the edges using the auxiliary drill press table, and I have provided guidelines for making one of your own. Sanding always creates dust. Three methods of dust control I use are presented at the end of this article. Although not 100% efficient, they do help quite a bit.

Light table workstation



If you need more storage space in your shop, you may want to build a light table workstation. This version has a few changes from the one that appeared in the August, 1997 issue of Creative Woodworks & Crafts*.

Light Table Workstation Plan



I made this light table to fit on the top of a mechanic's metal tool cabinet. The five drawers provide ample storage for C-clamps, sanding sleeves, sandpaper, and anything else you want to keep handy while creating your intarsia masterpiece. The cabinet is equipped with casters, so it can easily be moved if necessary.



The top of my cabinet measures 26" x 18" and has a 3/4"-high edge on three sides and part of the front. Four 6"-long pieces of 2 x 4 are used to elevate the work surface. Place one block in each corner of the cabinet top and attach the plywood top to them using 1-1/2" No. 8 flathead screws, counter sunk flush or slightly below the surface. As you can see, the top of the tool cabinet should be painted white, or have a sheet of white paper

continued on page 60

continued from page 59

on it, to better reflect the light. When completed, the light table sits on the tool cabinet. It is not fastened to it.


As shown in the illustration, the dimensions of the work surface measure 34" x 24", and I made it out of a piece of 3/4"-thick birch plywood. Round the corners, because they hurt if you bump into them! A jigsaw was used to cut two light windows, each measuring 10-1/2" x 16". A 1"-wide strip divides the windows; this is to better support the 1/8"- to 1/4"-thick acrylic sheet so it doesn't sag.



To provide additional support, a 1"-wide x 3/4"-thick strip of plywood was screwed and glued beneath the center divider. Note: Whether constructing the light table or light box, it is important to make sure the top is flat. If the acrylic surface sags or bows upward, it will be difficult, if not impossible, to achieve tight joints in your projects. Covering the entire top with acrylic provides a smooth surface on which to work.

If the acrylic sheet is larger than the work surface, it can be cut with a jigsaw and fine blade after it has been screwed to the plywood top. Because I couldn't find white acrylic large enough to cover the work surface, I purchased a clear piece from the hardware store. A sheet of white paper was placed beneath the acrylic to diffuse the light. The acrylic was then screwed in place with 3/4" No. 6 flathead screws which had been counter sunk, leaving the screw heads flush with, or slightly below, the surface. Note: Handle the acrylic sheet carefully because the edges may be very sharp (as the new bandage on my finger will attest to). Sand the edges smooth, either by hand or with a finish sander.

I've found this light table to be an adequate size for the projects I've made. However, you may want to adjust the size to better suit your needs.



Light box

If you don't need the additional storage space provided by the light table workstation, a simple light box will work just fine. For minimal cutting, the light box in the plan shown was made using two 6'-long pine 1 x 4s (actual wood size is 3/4" x 3-1/2"). The bottom was constructed from 3/4"-thick plywood.


Cut the material to size and bore or cut vent holes as shown in the plan. Assemble the frame with carpenter's glue and 1-1/2" No. 8 flathead wood screws. Attach the box frame to the plywood bottom. Add the four top supports which will prevent

the acrylic from sagging in the center.

Paint the inside of the box white to reflect the light. When dry, place the 1/8"- to 1/4"-thick x 27" x 18" acrylic sheet on top, and lay a straightedge across the top to make sure it is flat. A little sanding or shimming may be necessary to achieve this. If you are using clear acrylic, place a sheet of white paper beneath it to diffuse the light. Bore and countersink holes about every six inches for 3/4" No. 6 flathead screws and attach the acrylic. Be sure the screw heads are flush with, or slightly below, the surface. Sand the edges and corners of the acrylic sheet, as they may be quite sharp.

Slide the Brite Stik in the opening cut in the end of the box,

and shed some light under your next intarsia project.



For edge sanding intarsia project parts, I use the drill press 95% of the time. I find I can change drum sizes much faster than with the oscillating spindle sander. A good size for an auxiliary table is 20° x 16°. Fastening the auxiliary table to your drill press will vary with the design of your machine; therefore, dimensions for drilling mounting holes are not indicated on the illustration.

Begin by selecting a 3/4"-thick piece of flat, smooth plywood, like birch, measuring 20" x 16". Position it on the work surface of the drill press table. Hold it in place and trace the outline of all cutout areas of the drill press table to the bottom of the plywood. This will provide the proper location of the mounting holes and the hole to accept the sanding drums.

In the middle of the outermost corners of the drill press table cutouts, bore a 1/16" hole through the plywood. Flip the plywood over. Using a forstner or brad point bit, bore a hole in each corner, just deep enough to recess the bolt heads either flush or slightly below the surface of the auxiliary tabletop. The 1/16" holes are the location points. In the center of each recess, bore a 1/4"-Dia. hole through the plywood and 3/4" x 3" x 12" elevation blocks for mounting to the drill press table.

Using four 1/4" x 3" carriage bolts with nuts and washers, fasten the plywood to the drill press table, after first placing a

piece of 3/4" scrap wood in the center to prevent tear-out for when you use a hole saw to make the cutout for the sanding drum. I used an adjustable hole saw to cut the hole in the auxiliary table, making it about 1/4" larger than the largest sanding drum I planned on employing. Because I use a 2"-Dia. drum, the hole was cut 2-1/4" in diameter. (You may also cut the hole with your scroll saw if you don't have a hole saw.)

Remove the auxiliary table from the drill press, discard the scrap piece, and round the corners with a jigsaw. Sand the top and edges smooth and apply two coats of varnish to the sides

and edges.



Reassemble the auxiliary table on the drill press and tighten the bolts. Insert a large sanding drum in the chuck and use a 90° angle or square to make sure the drum is perpendicular to the table. If the angle is incorrect, loosen the bolts and place shims under the bolts until the drum and table are perpendicular. This is very important to achieve accurate edge sanding.

Using your auxiliary drill press table



When using a sanding drum of a smaller diameter than the hole in the auxiliary table, either swing the drill press head or the table in order to position the sanding drum close to the edge of the tabletop. This will prevent smaller pieces from tipping into the hole.

Any time you use your drill press for sanding, the selection of the proper grit sleeve is a must. Applying more pressure against the sanding drum will not do the same job as a coarser grit sleeve. Excessive pressure only ruins your sanding drums, burns the edge, and puts unnecessary strain on your machine.



Sawdust-packed sleeves should be cleaned to extend the life of your sanding sleeves.



A crepe rubber cleaning stick is a very useful tool, and I highly recommend having one in your tool supply. Just lightly press the cleaning stick against the spinning drum, and a sawdust-packed sleeve will be as good as new in only a few seconds.

Basic dust collection and safety

Now that you've found you really enjoy making intarsia projects, you've also discovered that the sanding required to fit and

contour the pieces of your project will create sawdust . . . lots of it. Inhaling sawdust is not a good way to keep your shop clean! How do we keep it under control? Here are a few tips.

This set-up is the one I used for several years. It did a pretty good job of drawing away and capturing dust, and it wasn't very expensive. It consisted of an old 24" x 24" household fan, to which I attached three 20" x 25" fiberglass furnace filters. Because the fan was wider than the filters, I



continued on page 62 Creative Woodworks & Crafts September 2005 • 61

continued from page 61

attached corrugated cardboard to the sides with duct tape. A plywood shelf was screwed to the bottom of the fan, then the

lilters were held in place with a bungee cord.


Use the workshop vacuum to remove the accumulation of dust that builds up on the filters. When doing a lot of sanding, the filters should be vacuumed every hour or so. If a lot of sawdust is allowed to accumulate on the filters, it will restrict airflow, which defeats the purpose of the fan drawing the dust away from you and may result in the fan motor overheating. The filters should be replaced regularly depending upon use.



A dust collection system with a 4" intake hose, positioned as close as practical to the sanding drum, is also an efficient arrangement for edge sanding and contouring.




I used a piece of wire to hold the intake hose to the drill press column near the sanding drum. If you decide to use a system like this, I highly recommend taking the time to make a guard for the end of the intake hose. Here's why. When the dust collector was delivered, I was anxious to try it out. The hose was connected to the drill press as described above, and the machine was turned on. I grabbed a piece of the project I was contouring and started sanding it . . . for about 30 seconds. I lost my grip on the piece, and it shot down the intake hose like a bullet hitting a bull's-eye, dead center, making the kind of noise you don't like to hear coming out of a new tool. Figuring the impeller was wrecked, I shut it off, unplugged it, and took it apart. Well, the impeller was fine, but my perfectly fitting intarsia part was mutilated, having several chunks missing from it. My next project was making a guard for the end of the hose.



A piece of 1/2" mesh hardware cloth was cut as shown. The long ends were bent over to grip the end of the hose with no need for additional fasteners. Voila! No more eaten intarsia parts!

side view







In addition to the equipment mentioned, wearing a dust mask is advisable while sanding your projects. Some species of wood are toxic, and others may create allergic reactions in some individuals.


Finally, use safety glasses or goggles to protect your vision and ear protection when operating noisy machinery, to provide full protection for yourself.

Send your intursia questions to Bob at: www.cob@wildlifeintarsiadesign.com or call: 708-788-6455.

TWO GREAT BOOKS BY ORCHID DAVIS

featured woodburning artist in this issue of Creative Woodworks & Crafts®

How To Woodburn
Wildlife provides
basic information on
burning and includes
five bird and six
animal patterns,
including the very
popular Great Horned
Owl, as well as
the Bobcat shown on
the cover.
\$14.00 plus \$2.00
S&H



Western Wildlife
teaches many of the
same techniques that
are used in How To
Woodburn Wildlife, but
a new group of patterns
are used, including a
Red Tailed Hawk,
Gambel's Quail,
Roadrunner, Great Blue
Heron, plus three more
birds. Animal patterns
include a Cougar,
Mustang, and the Wolf

pictured on the cover.

\$14.00 plus \$2.00 S&H

Woodburning



Both books provide useful information about how to make your own patterns, as well as advice for accessing great reference materials.

BEST BUY: ORDER BOTH BOOKS FOR \$28.00 AND ORCHID WILL PAY FOR THE SHIPPING!

To order: Send check or money order (and make payable) to Orchid W. Davis,

290-G Applewood Center Place, PMB 222, Seneca, SC 29678



Woodburning for Colori

by Orchid Davis, photos by Wes Demarest



This red-tail hawk was gracious enough to pose for me as I took a number of photographs, with hopes that one would be good enough to be the basis of a project. Well, I was not disappointed. All of the photos were good, and I selected this one. That was the easy part! For the next step, the photo just needs to be enlarged to the desired size on a copy machine, then sketched or traced onto the wood (also an easy part).

The main thing to remember when woodburning the hawk is that, just like with the bobcat featured in the April issue, there are no straight lines. This entire hawk design is basically a collection of curved lines. Focus on developing a light touch with the woodburning tool and adjust the amount of heat you use or the tip so you are burning for color, not creating charcoal. You can always go back over a line to darker it, but it is nearly impossible to lighten it. Some folks have asked me, "Why don't you mertion the setting you are using on your dial?" I choose not to mention the setting mainly because no two pieces of wood take the same temperature setting to get the same detail, and there can be variations between tools. On top of that, I am constantly making fine adjustments to the temperature settings, and it would drive you a little crazy and take up a lot more room in the article if I included every adjustment. So just look at the photos and make a bunch of test burns on some scrap wood until you get the hang of getting the shades that please you.

Red-Tail Hawk and the Scerets of Feathering



I refer to both the photograph and the enlarged copied version the whole time I am working on the project. The enlarged version allows me to see just what type of feather there is on the part of the body on which I am working.



This is my lip position for the feathers; it is what you could call a "writing position."



Hook at just how fine the detail is, which way it sweeps or turns, and how dense it is. Then, with a low temperature setting, Hightly burn in the pattern with my trusty "J" handpiece on my Colwood Detailer. It isn't really that difficult.



Here I am going back over the beak to add more depth and contrast. Notice that I'm "shading" using the "J" tip laid on its side this time. That is because the beak is a smooth, hard surface. For feathers, I'd shade with the pen held upright as in the previous photo.



The shading is a matter of three things: temperature, closeness of the lines to each other, and the speed at which you move your tip. No matter what temperature setting you're working at, you're going to get a lighter shade when you move the pen quickly and a more even color if you slow your hand down a bit. The slower you go, the darker the burn will be.



By lowering the tip, I get a more darkened surface and greater contrast. Don't forget, we are going to be adding color, so don't burn too dark.

continued on page 66

continued from page 65



The first step in learning to burn beautiful feethers is lo actually look at a real feather. Notice how the quill tapers from thick, where it joins the bird, and gets thinner and thinner until it disappears at the lip of the feather. Look at the angle at which the barbs grow out of the quill, usually about 45°. Then see how the feather forms a paper-thin arch as it conforms to the curvature of the bird's body. Again, there are no straight lines on the feathers I burn, and that is what makes them look so soft. (One small note: Every part of the bird's body has a different type of feather, so you are not going to get away with studying just one feather!)



By this time, we have made enough lest burns on the scrap wood to see just what temperature sellings we need. Still using the trusty "J" handpiece, outline the quill, and start the barbs. My hand is in a normal writing position throughout the motion in each barb.



The quill and borbs are burned heavier at the bosc, then laper off, and they have a bit of a curve to them. See—no straight lines! The easies! way lo make the line curve is to roll the handpiece in your fingers as you pull towards yourself. Notice the position of the red mark on the pen.




I roll the pen, pressing down with my thumb as I pull and lift off to curve to the right. (If you have studied calligraphy, you will understand just what I am doing.)



We do the same thing for the opposite side. Roll in the opposite direction by pressing down with the index finger and pulling towards you.



As you can see from the position of the pen, making the curved quill lines requires little effort, and once you get the hang of it, you can move along at a good pace.



Just to prove a point, I burned some straight barbs on the top left of the feather using line same tip, angle, heat setting, and spacing. Doesn't look nearly as soft, does it? That is why it's important to use curved lines. (The unevenness of the burned barbs is because Wes and I tried to get the best detail on film for line examples shown here, but it also points out just what happens if you slow down or hold position too long.)



Next, we will add more shading. This is

where the pholograph is particularly important, because

now, the bird will start to come to life. Now that all of the main outline is done, we will go back over it and burn in some depth and shading. This is the transition area from the neck to the wing, and we will add a few dark shoulder feathers.



Seal the wood with a cloar acrylic scaler, such as Deffa Ceramcoat All Purpose Sealer, and let it dry.



Finished (uncolored) burn

You can actually stop here and have a work of art that is sure to impress anyone. But, if you wish to add color, continue with the following steps.



All of these small details make the bird become an actual likeness of the hawk, rether than a collection of burned lines on wood



Luse burnt sienna for the base color, let it dry a bit, and then wash over it with burnt umber to darken it. Luse a brush to apply both colors.

continued on page 68

Creative Woodworks & Crafts September 2005 • 67

continued from page 67



Now we make lifelike eyes. Using a very small sable brush and Liquitex iridescent copper acrylic (or metallic copper nail polish), fill in the iris. Don't put it on too heavy because we want the burnt lines to show through.



Use a toothpick to add some fine glitter. (Wet & Wild nail polish works just fine.) You will only need a few specks, so don't overdo it.



While the eye is drying, add Naples yellow or a medium cadmium yellow paint to the base of the beak.




Once the eye has cured, finish it by glazing it with Treasure Crystal Cate (as described in the April, 2005 issue in great detail). If it takes two coats, be sure to let the first coal dry completely before applying the second one. If you use too much, just lift it off with a toothpick.



Luse the Mini "C" handpiece to sign my work, but use anything that works for you. The Mini "C" can be used for VERY small details.



Here I'm signing my full name on a flat toothpick to impress Wes and Alice! Don't think that you can't make small details with a wood burner, I even did this once on a round toothpick, but only because we didn't have a flat one on hand. Believe me, flat ones are a whole lot easier to write on.





This is another version of a red-tailed hawk that I did on a gourd, so consider surfaces other than wood to provide you with additional challenges, completely different presentations, and a fun change of pace. You might notice that this hawk isn't nearly as detailed. That's because gourds

are herder to burn then basswood, so I usually try to keep my designs strong and simple when burning on Them, There will be more about burning gaurds in my next article, along with some hints from my upcoming book about burning gourds, woodturnings, and other round objects (most of them bigger than toothpicks)!

We've just reviewed how to woodburn facthers. We talked about woodburning fur in the April issue. What's

next? Let's try fish!!!

If you have enjoyed these criticles, please let us know. especially if you would like to see a particular subject or technique demonstrated. If you would like to learn more about woodburning, Orchid has written two fine books on the subject. Flease see page 63 for additional information.



- 5 Precision Control Units
- More than 50 Tip Styles
- · Ultra-Flex Cords
- · Carrying Case
- Instruction Books
- Tip Pullers
- · Helpful Hints Brochures
- · New Cork Heat Shield

Colwood Tools by

The Champions Choice



Projects shown are done by Orchid Davis.

Colwood • 44 Main St. • Farmingdale, NJ 07727 • Ph: 732-938-5556 • Fax: 732-938-9037

www.woodburning.com

Reader's Gallery

Frank A. Droege of Voorhees, NJ won first prize in the New Jersey Art Show with this "Chip Monks" project, which he describes as "painted intarsia." With his considerable talent, it is not surprising to learn that Frank has written four scroll saw books, one co-authored with Pat Spielman and three for Fox Chapel. Frank, we are honored to show your work!



Borry Brookes of Barrie, Ontario, Canada has been doing intarsia for over ten years, and he loves to make his own patterns based upon photographs given to him by people wanting a commissioned piece. Barry favors the use of natural woods and lets "the wood character do the talking about each piece." The Indian War Bonnet is approximately 30" x 14", and it includes 225 pieces and 12 distinct wood species. It won first prize at The Calgary Stampede in 2001. The Clydesdale Horse is approximately 22" x 13" and includes 56 pieces. The horse's harness was painted glossy black to depict the look of patent leather. Barry, your talent is huge!







Warren Flanders of Derry, NH considered Jeff Zaffino's "Family Time" (pictured here) a real challenge. Obviously Warren was up to the challenge! He cut the project from 1/8" Baltic birch plywood, backed it with black velvet, and framed it with pine. An avid reader of this publication, Warren has been scroll sawing for over twelve years. Thanks for sharing, Warren!

Reader's Gallery





Lany Carlson, aka "The Oleguy," is very proud of his 13-year-old Great-Grandson Chris, who Larry has "taken under my wing and introduced to the world of scroll art." Larry says his great-grandson has "taken to the art of scrolling with much enthusiasm, patience, and imagination." The Dragon Clock pictured is Chris' own pattern and, of course, he cut it himself. Chris, your great-grandpa is right to be so proud of you!

continued on page 72

EXPERIENCE HOURS OF PERSONAL PLEASURE WITH WILDFOWL CARVING MAGAZINE



A FREE Black-capped Chickadee kit is yours when you subscribe to wildpowe. CANVING MAGAZENEM dedicated to showing you how to curve and paint all types of birds.

VEST Send my FREE issue of wildfowl.

CARVING MACAZINE for my personal evaluation. Pd
like to review the many bird reference photos, page
after page of sought-after advice, hints, championship
insights, the patterns, and color goldes all for \$29.95
U.S., \$45.50 Canadian. If I decide to subscribe, the
Black-capped Chickadee carving kit (a \$34.00 value)
will be sent to me FREE.

P.S. As always, your complete satisfaction is guaranteed.

A FREE black-capped chickadee kit is yours when you subscribe to wildrows carving magazing.





Van will be delighted you took this opportunity to sample the pleasure of bird carving.

Learn fruit the masters, join in their love of birds and their passion for bird careing. You will be inspired by their will inguise to devote the time necessary to explain secret rechniques to solving carving and pointing challenges.


Explore and expand your interest in birds and bird carving. Send for your FREE issue to lay!








IN THE U.S. CALL 1 (800) 233-9015, in U.S. Funds IN CANADA CALL 1 (877) 462-2604, in Canadian Funds



Reader's Gallery



continued from page 71

Lew Arthur of Las Vegas, NV has been scrolling for over seven years. The three projects shown (from left to right) are: The French Lyre Clock, designed by John Nelson and featured in our August, 2000 issue; Wildwood Designs' Old Fire Engine; and Dirk Boelman's Barn Clock, which was featured in our August, 2004 issue. Impressive work, Lew!

Bill McClernon did a nice job making this chess board and Civil War Chess Set, designed by Ralph Simott and featured in our August, 2003 issue. Thanks for sharing, Bill!





Bobby Underwood of Smithfield, NC has been scrolling for about eight years, focusing on intarsia for about the past two or three years. The dog intarsia pictured here is Bobby's first original design, adapted from a sketch he did as a fourteen-year-old boy. Nice work, Bobby, and thank you for sharing!

Jim DesBiens of Fairfield Glade, TN modified this church pattern from Wildwood Designs so that it could be used as a card holder at his daughter Debbie's wedding. A slot was added to the top for cards to be inserted, and the addition of a back door allowed for removal of the cards. Also added were the bride and groom figures and a light. It is no surprise that their Church Card Holder was "a big hit at the wedding and a wonderful keepsake for our daughter, Debbie, and her new husband, Anthony." Jim, what a wonderful application of your woodworking talents!

ATTENTION READERS:

We invite you to send us photos of your work, whether original or not, to be included in our Reader's Gallery feature. If it is not of your own design, please tell us whose design it is and, if possible, add a few sentences about the piece(s) being shown. Good, clear, flat photos (or slides) are desirable. Please do NOT send the item itself. Send to *Creative Woodworks & Crafts*, 7 Waterloo Road, Stanhope, NJ 07874, Atm: Robert Becker, Digital photographs are also acceptable with a resolution of 300 dpi, at approximately 3" x 4", preferably in jpeg or tiff format. They may be emailed to editors@woodworksanderafts.com.

News Release

www.Steebar.com Woodworking Plans-Clocks-Pens & More

Peapack, New Jersey-April, 2005. Steebar Corp. the catalog and online retailer of Andover, New Jersey announces that it has expanded its operations, moved to a new headquarters location in Peapack, N. J. and changed its name to www.steebar.com, LLC.

The new mailing address is P.O. Box 607 Peapack N.J. 07977 new phone number is 908-204-0095 & fax 908-204-0099.

The new location, located in the rolling hills of central N.J. will serve as our Administrative, Sales, Purchasing, and R&D facility with fully equipped woodworking shop. "After more than twenty years of doing business as Steebar Corp, we changed our name to reflect the growing importance of the Internet to our customers", said Chip Giordano, General Manager.

"The move provides an opportunity for continued growth and will allow us to deliver superior customer service, prompt delivery and innovative new products in the future".

Steebar's New Home




www.steebar.com · www.penmakingsupplies.com · www.woodworkingcrafts.com

Mini Lathe Series



Pocket Watches

by Kathy and Scott Griffith



Introduction

Scott and I would like to thank everyone for all the letters, e-mails, and phone calls we've received in response to our mini-lathe series. It's been wonderful hearing from you, and we are making every effort to answer each inquiry. Remember, we do live in a rural area of southern Lancaster County, PA, where, in order to access our e-mail, we need to take a trip into town to visit our beautiful library! Because of this, and frequent power outages, some things from time to time may get lost. If we fail to answer a question, please contact us again.

A pleasant and unexpected outcome of this series has been the visits from a number of folks who have stopped by our displays at woodcarving and art shows and at the Pennsylvania Renaissance Fair in Swashbucklers Grove. All this response has fueled our continuing effort to share the rewards of creativity, especially with children. Special congratulations are sent out to all the Scort troop leaders, students, teachers, and parents who have been sharing this hobby and are using their skills to reach out to others.

Scott and I have been part of each other's lives for almost 30 years and have learned the importance of positive support, humor, respect, and creative freedom. We hope to continue hearing from all of you because this what inspires us to reach higher. Keep up the good work and, most of all, keep smiling—it is the best advertisement for an activity that makes you happy!


Getting started

The pocket watch kit allows a turner to create a handsome and unique gift item. The variety of clock face styles available and all the species of wood on the market could result in a plethora of one-of-a-kind pocket watches. The outer wooden rim of the watch provides an area for some decorative turning, if you desire. And we are sure some of you could design some creative stands for displaying the completed watches.

When preparing for this project, be sure to order both the chain and the stud, as well as a 36mm-Dia. clock insert. If you choose, substitute a petite stud and gold ring for the heavy duty stud and chain and make a pendant watch. A French-twist rope chain is also available for the pendant watch variation.

If you opt to make the pocket watch using a 2"-Dia, clock insert, your wood blank will need to measure at least 1/2" thick (preferably 5/8" thick) and 2-5/8" square. The 36mm-Dia, clock insert used in this demonstration requires a blank that measures at least 1/2" thick and 2-1/4" square. Our model was made from StaburlizedTM box elder burl.

Turning a pocket watch



Mark 2-1/8"-Dia, circle on blank.

Cut the wood for the 36mm-Dia, clock insert pocket watch to a 2-1/4" square. Find and mark the center point. With a compass anchored on the center mark, draw a 2-1/8"-Dia, circle on the blank.



Tightly chuck up a 1-3/8" forstner bit into a drill press. Secure the blank flat into the drilling center vise and, with the point of the forstner bit on the center mark, drill a 5/16"-deep hole.




Using scroll saw to cut away excess wood from marked and drilled blank.

Use a bandsaw or scroll saw to cut away the wood outside the 2-1/8"-Dia, circle drawn on the blank. This step helps make the turning process safer by removing the corners of the block, which otherwise could catch and grab the gouge.



Mounted blank in lathe with tail stock and scrap wood.

Mount the prepared blank on the 1-3/8" expanding collet chuck and fasten it securely. Bring the tail stock to the blank and place a small wood scrap between the blank and the tail stock. Snug the tail stock against the wood scrap and lock it in place. This extra step is a safety precantion, primarily for the roughing process. The 2-1/8"-Dia. circle is a larger diameter than normally used by pen turners, so a bit of caution is advised. The scrap wood prevents the tail stock from dimpling the blank.




With lathe on low speed, begin to rough out, being sure tool rest is properly positioned.

Position the tool rest. Check that it is properly placed by manually rotating the blank, ensuring that the blank does not strike the tool rest. Make sure that your rough out gonge is sharp. Turn the lathe on to its lowest speed and begin turning. Whenever you stop the lathe to check your progress, also check that the blank has not loosened up on the chuck. Begin to round the edges of the blank. Be careful that you do not hit the tail stock with the gouge, as it will damage the cutting edge of the tool. As the blank rounds up, advance the speed of the lathe and smooth the tool marks.

continued on page 76

Creative Woodworks & Crafts September 2005 • 75



Use the skew gouge for final shaping and contouring.

Switch to the skew gouge for the final shaping and contouring. Slowly increase the lathe speed while using less and less pressure against the blank. Once the shape is satisfactory and the tool marks are uniform across the surface, loosen and slide back the tail stock and remove the scrap piece of wood.



Start sanding using 150-grit cloth-backed sandpaper and the lathe on low speed.

It is time to sand. Check that the blank is secure on the chuck, and turn the lathe to low speed. Starting with a 1" x 5" strip of 150-grit cloth-backed sandpaper, begin smoothing the blank, including the area where the tail stock had been. Increase lathe speed as you progress through finer grits of sandpaper, all the way through 400 grit. As you increase lathe speed, lessen your pressure against the sandpaper, and the surface markings should soften in appearance. Frequently turn off the lathe to check your progress, looking for areas still in need of work on the surface of the blank.



Use Abralon sanding pads for finish sanding.

For finish sanding, use Abralon sanding pads. With the lathe at high speed and using gentle finger pressure against the pad, start with the 500-grit pad and progress through the 1000 , 2000-, and 4000-grit pads.



Apply Shellawax cream finish and buff.

Apply Shellawax cream finish and buff. Repeat this process several times to maximize the depth of the finish.



Secure cloth-wrapped blank in drilling center vise and drill 3/16"deep hole with 9/64" bit mounted in drill press.

Read the assembly directions thoroughly before proceeding. Remove the blank from the chuck. Determine where the stud is to be mounted and where the hole for the stud should be drilled. Wrap the blank in a clean cloth to protect it; then secure it in the drilling center vise. Mount a 9/64" drill bit in the drill press and position the vise, holding it securely in place as you lower the drill bit and drill a 3/16"-deep hole.



Leaving the blank in vise, screw the stud in place using a finish nall.

Leaving the blank in the vise, screw the stud in place using a finish nail. Position it so the hole in the stud follows the circumference of the watch blank.

Set the clock to the correct time. (The clock insert does not get glued in place because it must be removable to facilitate changing the battery.) After the epoxy is set, attach the watch chain and insert the clock, being sure to line up the 12 o'clock and 6 o'clock numbers with the stud.



Completed pocket watch.

Enjoy the one of-a-kind time piece you have just created!

For questions concerning this article, send a SASE to: Kathy and Scott Griffith, 672 Conowingo Rd., Quarryville, PA 17566; Email: griffduchess @ yathoo.com





Orcetive Woodworks & Crafts September 2005 • 17

Welcome to WoodWorkingCrafts.com

There's something special about people who can handcraft a unique and beautiful item working with wood for 1 year or 20, we'd like to help you find answers to

News Portal

Check out our excellent news and information portal for an overview of everything on our site. Share a unique project or original plan design or just browse through different areas and glean information.

Photo Gallery

Would you like to share some photos of your work? Or maybe you just want to glean some ideas from the creativity of your fellow wood crafters. Our Photo Gallery is just the place to do it.

Steebar

Clockmaking Supplies
Scroll Saw, Fretwork,
Woodworking Plans
& Patterns, Yard
Decorations, Tools &
Much More!





WWW.STEEBAR.COM P.O. Box 607 Peapack N.J. 07977

Have something to sell or trade? Check out the WWC Trading Post!

from a quality piece of wood. Whether you're a hobbyist or professional who's been your wood crafting questions and provide a place to share information.

Discussion Forums

Browse our community discussion forums for the latest woodworking craft question & answers along with helpful tips and information. Or just share a bit of yourself with other crafters.

Sell Online

Are you trying to support your habit by selling some of your handiwork? We have web space available to show off your products and provide contact information. If you have an existing web site feel free to post a link to your site in our Links Section

www.steebar.com

Buy Online 24 Hours a Day!







HUNDREDS OF WOODWORKING PLANS TO CHOOSE FROM





Introduction To Scroll Sawing

by Wes Demarest



Thinking About Penmaking?

Absolutely the most definitive guide to turning writing instruments ever published. The best book for both the seasoned pen maker and anyone new to the craft.



Penmaking Starter Kit

Everything you need to start making 7mm pens and pencils - Included are the following items... CT-LATHF-1 Carba-Tec Mini Lathe, #1 MT Mandrel, Slimline Pens pak of 5, Slimline Pencils pak of 5, Barrel Trimmer, Pre Drilled Pen Blanks SG-THICK Super Glue, 1/2" Pen Making gouge 30ml Shollawax polish



Penmaking Super Kit

If you are serious about pen making for profit, then here's the package for you! Includes all the basics needed to get started, plus enough pen kits with a suggested retail value greater than the complete package! Each pen (with box) sells for an average of \$30.00 around most of the U.S. This gives you the chance (especially Insider's Club members) to turn a profit from the very beginning!

Kits include too many items to list...
See our website penmakingsupplies.com for complete details

NEW phone: 908-204-0095 NEW fax: 908-204-0099

NEW From Creative Woodworks & Crafts Exclusive Patterns... GUARDIAN ANGELS WALL CLOCK!

This eye-catching clock is sure to become a family heirloom, and will delight angel lovers everywhere!

Designed exclusively for Creative Woodworks & Crafts' Pattern
Division by Scroll
Saw Artist
Extraordinaire
Dirk Boelman.

Westminster chimes make a delightful sound, while pendulum with lyre attachment enhances the clock's visual appeal.

Plan price: \$15.95

plus \$2.00 S&H

To Order:

Send \$17.95 check or money order (and make payable) to All American Crafts, 7 Waterloo Road, \$2 Stanhope, NJ 07874
Attn. R. Becker. To order by credit card (Visa, MasterCard, & Amex accepted) call Marie at (973) 347-6900 ext.141

Dimensions:
9-3/4" x 25" x 4-1/4"
Top-quality patterns
come in durable cover
wrap. Excellent instructions include detailed
assembly diagrams.
Source is provided to
order all clock parts and
hardware (not included).



Side View Detail

Note: easy-to-order clock parts and hardware package not included. Ordering info provided with pattern.

The Wood Shed

FREE BROCHURE FOR WOOD-WORKING DESIGNS. Write to WOOD TEMPLATES COMPANY. Dept W8460, PO Box 182534, Shelby Twp., MI 48318, or visit www.woodtemplates.com. 1158-9

EASILY ENLARGE PATTERNS!

Take a pattern from your scanner and print it to any size. Large patterns are automatically tiled across multiple pages. Free 14-day trial at www.RapidResizer.com/creative 1160-9



of Exotic & Domestic Hardwoods FROM 1/16" TO 3/4" THICK

13 Species of Plywood PEGAS SCROLL SAW BLADES

For Free Catalog Call: Toll Free: 1-888-751-1400 or 610-381-2286 · Fax 610-381-5155

D & D Woodcrafts

RR 3 Box 3066 Saylorsburg, PA 18353-9617 www.danddwoodcrafts.com



Quality Lumber at Affordable prices



Free Catalog

Toll Free: 1-888-322-2432

Scroll Saw Lumber 1/8 to 3/4 inch thick and 4" to 8" wide and wider!!

26511 County Hy OO Richland Center, WI 53581

www.ocoochhardwoods.com

*Lower Prices

* Fast Service

*Customer Satisfaction

Unsurfaced Lumber Hardwood Planks Carving Stock

FREE **SCROLL SAW BLADES**

Receive One Dozen FREE blades* for life, plus get FREE shipping** with your order of \$25 or more from this ad or our website.

You'll get one FREE dozen of ScrollAmerica® blades every time you place an order of \$25 or more now and in the future. That's right, FREE blades for life when you order from this ad or our website. Be sure to mention Ad Code 6892 to receive this special offer.

Order today and get 10% off, plus free shipping and one dozen free blades with any order over \$25.





CROLL TO Order from this ad or our website, and save 10% off our already low prices on all ScrollAmerica blades!

Call 1-800-220-1152 to order.

Visit us online at www.bladevaluesdirect.com

We also self OLSON at the lowest prices

Premium Double Tooth	Regular Low Prico per dazen \$1.95	Sale Price with this ed \$1.76
Reverse Tooth	\$2.25	\$2.03
Spiral	\$2.35	\$2.12
Precision Milled Tooth	\$3,75	\$3,38
W! Custom Cut	\$4.95	\$4.46

NOTE: All blades are flat end and are available in various sizes. We do not sell pin end blades.

*Choose from AP or RP ScrollAmorica Blades . ** Free standard shipping within the 48 States. Prices valid for 60 days.

BLADEVALUESDIRECT - P.O. Box 430 - Dept 6892 - New Castle, DE 19720





oan's Woodshop e Scroll Saw Store



c Birch Plywood

The Best Grade available: 8/88 #101 - 1/8"x12"x12" - \$1.00 #107 - 1/8"x12"x24" - \$1.90 #102 - 1/4"x12"x12" - \$1.30 #108 - 1/4"x12"x24" - S2.50 #103 - 3/8"x12"x12" - \$1.75 #109 - 3/8"x12"x24" - \$3.40 #104 - 1/2"x12"x12" - \$2.00

#110 - 1/2"x12"x24" - \$3.90 #105 - 5/8"x12"x12" - \$2.95 #111 - 5/8"x12"x24" - \$5.80

#106 - 3/4"x12"x12" - \$3.95 #112 - 3/4"x12"x24" - \$7.80

Finland Birch Plywood

The Best Grade Available III No Patches or Back Face IIII #5241 ~1/32"x12"x12" ~ \$2.35 #5241A -1/32"x12"x24" - \$4.60 #5242 -1/16"x12"x12" - \$2.25 #5242A -1/16"x12"x24" - \$4.40 #5249 - 1/8"x12"x12" - \$1.70 #5249A -1/8"x12"x24" - \$3.30

Italian Poplar Plywood

Great for scrolling & Wood Burning II #5530 - 1/8"x12"x12" - \$1.50

#5530A - 1/8"x12"x24" - \$2.90

We now stock Olson® Band Saw Blades In sizes: 56 1/8", 59 1/2", 80", 93 1/2", & 105" We also have Olson® Genuine Cool Blocks® to fit most band saws. Highly Recommended by Professionals Forstnor Bits - We stock a complete line of forstner bits.

They are available in sizes: 1/4" to 3 1/8" in 1/8" increments.

We also stock the hard to find: 5/16" to 2 1/16" in 1/16" in-

crements. We also have 3 different sets available. Check our

website for a complete listing or give us a call we probably

have the size you need in stock and ready to ship.

2 inch Precision Machine Square A must when stack

cutting, Squares your blade with the table.

SQ-2 - \$4.95



Router Base, Ten High Speed Steel Bits come in a Wooden Storage Box

#D2721 - \$25.00

These bits are also available separately for \$3.65 each



Regular about 1/4" wide, 6" long Mini about 1/8" wide, 4" long Reg - #12pcnf - \$10.95



Needle File Sets 12 piece sets in 2 sizes of files. Mini - #12pcmini - \$6.95



When you call us you'll talk to more than just an order taker !!! We all own and use scroll saws !!!

Premium Grade Hardwoods: Clear on the front face. The back face may contain minor defects. Widths+/- 1/8" MOST WOOD AVAILABLE IN WIDER WIDTHS, 7", 8", 9" & SOMETIMES WIDER !!! GIVE US A CALL !!!

Species	Stock # 1/8"x6"x24"	Cost Each	Stock # 1/4"x6"x24"	Cost Each	Stock# 3/8"x6"x24"	Cost Each	Stock # 1/2"x6"x24"	Cost Each
Red Oak	#RED186	\$3.55	#RED146	\$3.95	#RED386	\$4.60	#RED126	\$4.60
Hard Maple	#MPL186	\$3.95	#MPL146	\$4.45	#MPL386	\$5.25	#MPL126	\$5.25
Basswood	#BAS186	\$3.83	#BAS146	\$4.11	#BAS386	\$5.04	#BAS126	\$5.20
Walnut	#WAL186	\$4.45	#WAL146	\$4.95	#WAL386	\$5.95	#WAL126	\$5,95
Cherry	#CHY186	\$4,75	#CHY146	\$5.25	#CHY386	\$6.25	#CHY126	\$6.25
Purpleheart	#PHT186	\$4.25	#PHT146	\$4.95	#PHT386	\$5.95	#PHT126	\$6.95
Mahogany	#MAH186	\$5.00	#MAH146	\$5.60	#MAH386	\$6.50	#MAH126	\$6.75
Padauk	#PAD186	\$5.15	#PAD146	\$5.75	#PAD386	\$6.75	#PAD126	\$7.25
Canarywood	#CAN186	\$4.95	#CAN146	\$5.45	#CAN386	\$6.25	#CAN126	\$6.75
Yellowheart	#YEL186	\$4.60	#YEL146	\$5.10	#YEL386	\$5.75	#YEL126	\$6.25

To plage an order, call, fax or write us. We accept Visa, MasterCard, Discover, Checks & Money Orders. Sorry No COD's Place Instude Phone # and Street address (No PO Boxes) - Most orders are shipped within 24 hours, We ship by UPS-100% Insulad, No minimum order, No extra insurance charges, Our simple shipping chart is on the next page. Questions? Give us a call. We'll give you a Free Catalog and a Free call on our Toll Free Order Line. Many more items on our Web Site !!!







Sloan's Woodshop - 3453 Callis Road - Lebanon, TN 37090 Phone: (615) 453-2222 Fax: (615) 453-0507 Email: info@sloanswoodshop.com www.sloanswoodshop.com Check out our internet specials !!!



Toll Free: 1-888-615-96

Wood - Great Prices - Where Customer Service is our Jop Priority



"OLSON®" TOP QUALITY SCROLL SAW BLADES

Regular Skip Tooth Blades #3/0, 2/0, 0, 2, 4, 5, 7, 9, 11 \$ 1.70 a Doz - \$17.00 a Gross

Double Skip Tooth Blades # 3/0, 2/0, 1, 3, 5, 7, 9, 12 \$1,70 a Doz - \$17.00 a Gross

Reverse Skip Tooth Blades #2/0, 2, 5, 7, 9, 12, 420R \$1.95 a Doz - \$19.50 a Gross

Spiral Tooth Blades # 2/0, 0, 2, 4, 6 \$1.95 a Doz - \$19.50 a Gross

Crown Tooth Blades # 2/0, 2, 3, 5, 7, 9, 12 \$2,30 a Doz - \$23,00 a Gross

Precision Ground Tooth # 5, 7, 9,

\$3.50 a Doz - \$35.00 a Gross

"NEW" PGT Double Tooth # 5, 7, 9,

\$3.50 a Doz - \$ 35.00 a Gross

"NEW" Mach Series Reverse #3, 5, 7, 9

\$2.75 a Doz-\$27.50 a Gross

"NEW Thick Wood Blades # 408-TW

\$ 2.95 a Doz-\$29.50 a Gross

Metal Cutting Blades #1, 5, 7, 9, 12

\$3.00 a Doz—\$30.00 a Gross

"NEW" Flat End Spiral #2.4

\$2.75 a Doz-\$27.50 a Gross

You may mix or match the same style blades for gross pricing All the blades above are 5" Plain End "OLSON" Blades We also stock:

3" pin end blades -2 sizes 5" pin end blades - 8 sizes 6" plain end blades - 4 sizes 5" Plain End Jewelers Blades

ACRYLIC SHEETS

Solid Colors

\$ 7.95 ca 1/8"x12"x24"

Red, Blue, Light Blue, Green, Yellow, Orange, Black, White, Pink, Ivory, Brown, Purple, Frost White, Turquoise, Gray

Transparent Colors

\$7.95 ea 1/8"x12"x24" Red, Blue, Light Blue, Green, Yellow, Orange, Smoke, Bronze, Purple, Clear (clear only \$ 5.50 each)

Mirrored Colors

\$12.50 ea 1/8"x12"x24"

Red, Blue, Green, Yellow, Orange, Pink, Purple, Peach, Gold, Bronze, Gray, Teal, Clear (clear only \$ 9.00 each)

White Marble **Acrylic Sheets**

\$12.50 ea 1/8"x12"x24"

We have more acrylic available. See our web site for a complete fisting of sizes & types.



Precision Pin Chuck

Use mini bits in a drill press with this quality Pin Chack. With 3 collets, it holds bits #80-#40, # PC-1 \$ 9.95



20 Piece Mini Drill Bit Sct #61 - #80 metal case #20pcDS \$ 9.95

Mini Drill Bits

1/16", 3/32", 1/8" Bits \$4.50 Doz

Numbered Drill Bits

#54, #56, #58, #61, #64, #67, #70, #72

\$ 7.50 per Dozen (sorry no mixing sizes of drill bits)

Top Quality Silcon Brand Inserts



#CK100 - White Arabic #CK103 - Ivory Arabic #CK102 - Gold Arabic



#CK101 - White Roman #CK104 - Ivory Roman #CK105 - Gold Roman

1+ \$4.75~10 + \$4.35~30+ \$3.95~100+ \$3.65 1.7/16" Inserts, Glass Lens, Stainless Steel Back, With Battery NO RUBBER GASKEYS - MIX OR MATCH PRICING !!!



1 7/16" Fancy Gold & Black Dial. Arabic Numbers 1+ \$5.50 - 10+ \$5.20 30+\$4.75 - 100+\$4.40



#PHOTO-1 1 7/16" Photo insert 1+\$1.75 - 10+\$1.55

30+\$1.35 - 100+\$1.25

All Clock & photo inserts have a gold tone bezel. Clocks include battery. All require a 1 3/8" mounting hole 5/16" deep.

1 3/8" Forstner Bit - #FOR138 - \$ 9.00 each We also stock 2", 23/4" & 3 1/2" clock & photo inserts



Blade Storage Tuhes

Clear plastic tubes 3/4" dia. 6" long, tops have hangtabs

\$3.95 dozen #TUBE

Order Toll Free 1-888-615-9663


Sloan's Woodshop


3453 Callis Road Lebanon, TN 37090


SHIPPING CHARGES


Applies to the 48 contiguous states only \$00.00 - \$40.00 add \$ 5.00 \$40.01 - \$60.00 add \$ 6.50 \$60.01 - \$80.00 add \$8.00 \$80.01 and over add 10% Blade only orders \$5.00 shipping TN residents add 9.25% Sales Tax














JLL SIZE PATTERN SECTION NO. 1 SEPTEMBER 2005

leady for Flightfrom page	11
hree Wildcat Portraitsfrom page	16
leim's Wheel intarsiafrom page	51
Bide B	
Vatchful Eyesfrom page	6
ngine 86 from page	22
everent Denomination from page	25
urly Suefrom page	28
en and Pencil Boxesfrom page	32
ug Pupplesfrom page	44

ide A


te: all of the deelgne in Creative Woodworks & Crafte pattern tions are copyrighted. You are permitted to make photocopies LY for your personal use. You may give away or sell the upleted projects you make from them, but you are NOT mitted to make copies of the actual patterns themselves sell, give away or otherwise distribute in any other form.


Metric Conversions:


 $1 \ln ch = 25.4 \text{mm} = 2.54 \text{cm} = 0.0254 \text{m}$


Common Measurements:


1/16" = 1.59mm	5" = 12.70cm
1/8" = 3.18mm	6" = 15.24cm
1/4" = 6.35mm	7" = 17.78cm
3/8" = 9.53mm	8" = 20.32cm
1/2" = 1.27cm	9" = 22.86cm
5/8" = 1.59cm	10'' = 25.40cm
$3/4^{\circ} = 1.91$ cm	11" = 27.94cm
7/8'' = 2.22cm	12" = 30.48cm
1" = 2.54cm	24" = 60.96cm
2" = 5.08cm	36" = 91.44cm
3" = 7.62cm	45° = 1.14m
4" = 10.16cm	60" = 1.52m


















Pen and Pencil Boxes Full Size Patterns from page 32







nomination

Patterns


age 25


B∥∀























FULL SIZE PATTERN SECTION NO. 2 SEPTEMBER 2005

Side A	
Screaming Eagle	from page 8
Chirping Chickadees Wall Pock	et from page 48
Turkey Beard Holder Intarsia	from page 56
Side B	
Whiskers	from page 12
The Tree Swing	from page 30
Fretwork Box	from page 36
Mare and Colt	from page 42
Red-Tail Hawk	from page 64


Note: all of the designs in Creative Woodworks & Crafts pattern sections are copyrighted. You are permitted to make photocopies ONLY for your personal use. You may give away or sell the completed projects you make from them, but you are NOT permitted to make copies of the actual patterns themselves to sell, give away or otherwise distribute in any other form.

Metric Conversions:

1 inch = 25.4 mm = 2.54 cm = 0.0254 m

Common Measurements:


1/16" = 1.59mm 5" = 12.70cm 1/8" = 3.18mm 6" = 15.24cm 1/4" = 6.35mm 7'' = 17.78cm3/8" = 9.53mm 8'' = 20.32cm1/2" = 1.27cm 9" = 22.86cm 5/8" = 1.59cm 10" = 25.40cm 3/4" = 1.91cm 11" = 27.94cm 7/8" = 2.22cm 12" = 30.48cm 24" = 60.96cm 1" = 2.54cm 2" = 5.08cm 36" = 91.44cm 45'' = 1.14m3'' = 7.62cm60" = 1.52m 4'' = 10.16cm



.

852


...




ton.


89

ė











Fretwork Box Front Overlay (F)
Cut 1

Fretwork Box Front/Back (C) Cut 2






Fretwork Box Full Size Patterns from page 36



Fretwork Box Side Overlay (G)
Cut 2
1/8" x 3-1/8" x 3-5/8"




Fretwork Box Side (B) Cut 2





×



.









The Tree Swing Full Size Patterns from page 30

70000

