

- Hideaway bed
- Garden kneeler
- Overhead router
- Sculpture turning



**TAKING A BOW** 



**TAPERED ELEGANCE** 



**CHALLENGE BOWL** 

### Ironmongery Direct

MASTERS OF OUR TRADE

# ORDER BY BPM



**FREE Delivery** over £45

Minimum 5 Year **Guarantee** 

**✓ FREE Returns** 







FREEPHONE: 7am-8pm 7 days a week. ONLINE:

0808 168 28 28



OR TEXT RBA6 to 62244 F with name, address and email

# welcome

he other day I had to make a couple of simple casement window sashes and, thinking about the job the night before, I couldn't remember if I had enough timber in stock to make a ready start or if an early morning trip to the timber yard would be necessary first. Now I always enjoy a visit to my local merchant. They're down by the docks near my workshop, and there's often a boat or two chugging past or some other pleasing nautical business going on; fishermen sorting out their nets against a moving backdrop of forklifts piled with boxes of fish, that sort of thing. All very nice, and just part of the fun that some people call work.

#### **Bright start**

The morning dawned bright and clear, and it was with mixed feelings that I discovered a couple of lengths of joinery-grade softwood in my 'assortments' stack and hauled them out to make a start. I briefly considered heading down to the docks to buy some hardwood, but a combination of a low-budget job and the desire to get started convinced me to stay in the workshop. It was during the milling process, cutting and thicknessing my timber, that I felt The Feeling – familiar to all woodworkers – the feeling of joy and absolute pleasure in the working of this most rewarding of materials. Sustained for the whole day long, the job went (fairly) smoothly and it was with a considerable degree of satisfaction that I locked up that evening with a brace of rebated frames glued up and in cramps


#### Take it easier

Lucky me, I say, and to think that I (mostly) get paid to do it too! Perhaps an attitude change has been responsible... Lately, instead of tearing into the work like some industrious whirlwind, I work at whichever pace suits me that day. I find this makes for a much better job, and for a lot less worry and stress too. Customers no longer browbeat me into barely achievable deadlines. When asked the other day 'how long will the fitting take?' I found myself answering – and truthfully – that I actually didn't know. This was a good sign to me, and an indicator of a relatively worry-free site visit. And so it proved to be; apart from the dry sauna-like conditions and a close shave with some hidden cables, the job went very well and everyone concerned finished each day with a smile.

So, whether you're old or young, novice or vastly experienced, don't forget just how lucky you are to be in this business: the joyful business of working with wood.

mark

You can contact Mark on mark.cass@mytimemedia.com



If you can't always find a copy of the magazine, help is at hand! Complete this form and hand it in at your local store, and they'll ensure that a copy of each issue is reserved for you. Some stores may even be able to arrange for it to be delivered to your home. Just ask!

Subject to availability

Please reserve/deliver my copy of <b>The Woodworker</b> on a regular basis, starting with issue
Title First name
Surname
Address
Postcode
Telephone number







#### **REGULARS**

- Welcome
- 9 News
- 11 News & Diary
- 13 News
- **62** Subscriptions
- 88 Marketplace
- 89 Readers' letters
- 90 Archive

#### **WOODWORK**

#### 14 Sew amazing

Peter Dunsmore presents a stylish cherry box designed to take sewing requisites. It could be used for jewellery too

#### 21 Spot the bed!

Keith Smith fixes the problem of making one room serve two purposes by installing an easy-to-operate hideaway bed

#### 29 Garden comfort

Take some of the strain out of gardening with Ben Russell's ingenious two-way kneeler

#### 34 Mitre magic

Mitre joints look very attractive if cut well, but inaccuracies can cause them to gape open. Andy Standing explains how to get them just right every time

#### 38 British bulldog

Ian Taylor has designed a low coffee table with a shelf that looks as if it has been hewn from a solid slab of timber

#### 45 Taking a bow

Robin Gates shares his passion for the traditional wooden-framed bow saw

#### 49 An overhead router

Bob Darey has spent years developing his own version of this versatile piece of kit

#### **52** Tapered elegance

Mark Cass delivers a family commission - a plain but elegant dining table in beech, designed to have no protruding corners for toddlers to bang their heads on

#### **TURNING**

#### 57 Challenge bowl

After describing the spalting process last month, Alan Holtham introduces some of the techniques you'll need to master to turn spalted wood successfully and creates a stunning bowl in beech

#### 65 Who's the fairest?

Colin Simpson says that hand mirrors are relatively simple to turn. The mirror glass can be bought online, or ordered from your local glass supply shop

#### 71 Turning the impossible

Most turned work is essentially two-dimensional; the shape you see is just a silhouette. But what if you could create something that's truly threedimensional? Rod Tallack can



#### ON TEST

76 Makita DLX2040MJ drill/driver twin pack

78 Scheppach HS100E table saw

80 Proxxon STS/E Super jigsaw



#### March 2015

Published by MyTime Media Ltd Enterprise House, Enterprise Way, Edenbridge, Kent TN8 6HF

Tel: 0844 412 2262 From outside UK: +44 (0)1689 869840 www.getwoodworking.com

#### **SUBSCRIPTIONS**

**UK** - New, Renewals & Enquiries Tel: +44(0)1858 438798
Email: mytimemedia@subscription.co.uk USA & CANADA - New, Renewals & Enquiries

Tel: (001)-866-647-9191
REST OF WORLD - New, Renewals & Enquiries
Tel: +44 (0)1689 869896

#### **BACK ISSUES & BINDERS** Tel: 0844 848 8822

From outside UK: +44 (0)1332 912894 Email: customer.services@myhobbystore.com Website: www.myhobbystore.co.uk

#### **EDITORIAL**

Editor: Mark Cass

Email: mark.cass@mytimemedia.com Production editor: Mike Lawrence Email: mike.lawrence@mvtimemedia.com

#### **PRODUCTION**

Design Manager: Siobhan Nolan Designer: Malcolm Parker Illustrator: Michael Lindley Retouching Manager: Brian Vickers Ad Production: Robin Gray

#### **ADVERTISING**

Business Development Manager: David Holden Email: david.holden@mytimemedia.com Tel: 01993 709545

> Online Sales: David Holden Email: david.holden@mytimemedia.com Tel: 01993 709545

#### **MARKETING & SUBSCRIPTIONS**

Subscriptions Manager: Kate Hall Subscriptions: Sarah Pradhan Tel: +44(0)1858 438798

#### **MANAGEMENT**

Head of Design & Production: Julie Miller Group Sales Manager: Duncan Armstrong Chief Executive: Owen Davies Chairman: Peter Harkness



© MyTime Media Ltd. 2015 All rights reserved ISSN 1752-3524

All fights feserved ISSN 1732-3324

The Publisher's written consent must be obtained before any part of this publication may be reproduced in any form whatsoever, including photocopiers, and information retrieval systems. All reasonable care is taken in the preparation of the magazine contents, but the publishers cannot be hald legally responsible for errors in the contents of this magazine or for any loss however arising from such errors, including loss resulting from negligence of our staff. Reliance placed upon the contents of this magazine is at reader's own risk.

The Woodworker & Woodturner, ISSN 1752-3524, is published monthly with an additional issue in summer by MYTIME MEDIA Ltd, Enterprise House, Enterprise Way, Edenbridge, Kent TN8 6HF, UK.

The US annual subscription price is 59GBP (equivalent to approximately 98USD). Airrieght and mailing in the USA by agent named Worldnet Shipping Inc., 156-15, 146th Avenue, 2nd Floor, Jamaica, NY 11434, USA. Periodicals postage paid at Jamaica NY 11431. US Postmaster: Send address changes to The Woodworker & Woodturner, Worldnet Shipping Inc., 156-15, 146th Avenue, 2nd Floor, Jamaica, NY 11434, USA. Subscription records are maintained at CDS GLOBAL Ltd, Tower House, Sovereign Park, Market Harborough, Leicester, LE16 9EF.

Air Business Ltd is acting as our mailing agent.



Paper supplied from wood grown in forests managed in a sustainable way.



#### THE TOOL SUPE HAND, POWER TOOLS & MACHINERY SPECIA

DM-TOOLS.CO.UK

#### **YOUR TRUSTED PARTNER**

D&M Tools has been family owned and managed since 1978. During that time we have earned a reputation with our customers as a trusted partner. Whether you are a trade professional or a DIY enthusiast, our mission is a simple one - to supply top quality tools at the best value for money, backed up by a service you can trust.

#### **LOW TRADE PRICES!**

Whether you're buying online, by phone, email, post or visiting us in-store, D&M provides you with the widest range of quality hand, power tools and woodoworking machinery all at the keenest prices.

We hold massive stocks, meaning that most items are available for despatch the day you order it. Our website shows up to date stock availablity, so you can order with confidence.

Delivery to UK mainland addresses is free for most orders over £99 and for orders under £99 is only £5.95. See the carriage rates on our website for full details.



We use DPD Predict for the majority of our deliveries (except heavy or oversize items) so you will receive a 1 hour delivery window via email or text meaning you don't need to wait in all day.

#### SHOP ON-LINE 24HRS A D

Visit our easy-to-use website to see what we mean about range and value. Browse and buy with confidence 24hrs a day from the

> biggest brands in the business, all at prices you'll find hard to beat.

Here you will find all our latest offers and deals.

Why not subscribe to our regular emails to keep up with our latest deals and offers or join our D&M Loyalty Scheme and earn valuable loyalty points every

More details on our website: www.dm-tools.co.uk

DATE IN YOUR DIARY..



ASSIVE CHOI BOSCH BOSTITCH FBRITOOL DREMEL Empiré? DRAPER ☐ EVO-STIK FAITHFULL FESTOOL FISCO **KARCHER** JOBINAN KNIPEX Laserliner<sup>6</sup> LED LEDSER malell MAG-LITE Trakita Marples. **Nilfisk** ONUMENT TOOLS LTD ALTO **Panasonic** PROXXON SANKYO (SD) HAND TOOLS STABIL SJÖBERGS SCRIBE-MASTER TACWISE TELESTEPS 🞏 STARTRITE STANLEY No.1 in telescopic work tool: trena **IENGIOOLS** verítasº

THE UK's No.1 BRANDED HAND POWER TOOLS & MACHINERY EVENT



**KEMPTON PARK RACECOURSE** 9-11th OCTOBER 2015

**VISIT OUR EXTENSIVE TWICKENHAM SUPERSTORE** 73-81 HEATH ROAD • TWICKENHAM • TW1 4AW 020 8892 3813 • SALES@DM-TOOLS.CO.UK









We are regularly receiving 5 star reviews on the independent review site Trustpilot, as well as testimonials direct from our customers, here are just a few:

"Amazingly quick, good value, text to the hour delivery time, impressed - Great company, no nonsense, cheap prices, the best delivery service I get alerted by text on the day of the hour of delivery, so I don't have to wait around on site for it to turn up. So useful I will definately be purchasing more from this shop."

#### \*\*\*\*

"Why didn't I find this shop years ago?!! - Excellent stock and service - both in the shop and online. Damaged item replaced promptly with no fuss - great. I'll certainly be going to them first in future."

#### \*\*\*\*

"Excellent service - Great price, great tool, great service won't use anyone else anymore contacted all the way though transaction right up till delivery. Would highly recommend D&M tools."

#### \*\*\*\*

"One of the best I've used - If you need power or hand tools then these are the guys to go to. In store they are a great help. The online shop is top notch as well, if you are not sure about a product give them a call, the staff are knowledgeable and helpful. Delivery is always prompt. I use D&M Tools all the time for kit."

#### \*\*\*\*

"Quality Product at a Fantastic Price - DM Tools had the quality DeWalt tool I was after at the best price. The whole procedure from searching their very user friendly web site, until the delivery by a customer focussed courier was painless. I have to commend the staff at DM Tools and would recommend them if you are after quality products and good customer service at a wallet friendly price"

www.trustpilot.co.uk/review/www.dm-tools.co.uk

**DandMTools** 









### NEW FROM TOOLTEC

# CLICK'N CARVE



- Works with Wood, ABS, Foam, Modeling Wax, Styrenefoam, Epoxy Tooling Board
- Easy to use software
- Ideal for the commercial, professional, enthusiast and educational sectors.



All you need to do is CLICK-CONVERT-COMMAND-AND-CARVE...

Call 01494 523991 sales@tooltec.co.uk

Fax 01494 524293 www.clickNcarve.co.uk



In brief...

#### Irwin makes an impact

The new Impact Performance range from Irwin Tools includes single and doubleended bits, quick-change extensions and a right-angle drill. There are also ten differently configured Pocket and Pro Set cases, all engineered specifically for use in impact tools.

The bits are manufactured with high-grade steel and are designed with precision tip geometry for superior fit and reduced cam-out, so they are able to withstand high torque outputs. They also feature Irwin's exclusive DoubleLok technology, which securely locks both ends of the bit into impact drivers and quick-change chucks. www.irwin.co.uk


#### **Triton triple**

The new Triton T20 range consists of a multi-speed drill driver (£220), a combi drill driver with hammer action (£232), and an impact driver (£226). All three tools have 20V 4Ah batteries,



and charging to 80 per cent capacity takes just 30 minutes. Other features include an over-moulded grip and a built-in LED work light. A twin pack

featuring the combi drill driver and impact driver with two 4Ah batteries and an intelligent charger is available for £300.87. www.tritontools.com



#### Just the drill

Axminster has just introduced its own range of trade-rated hex shank bits under the brand name Axminster Trade Bitz.

Most cordless drills and screwdrivers have a keyless chuck, and some only have a hex fitting. The shanks of Trade Bitz holders, long screwdriver bits and torsion screwdriver bits have a double groove and special machining that makes them compatible with all makes of 1/4in hex quick-change and magnetic bit holders.

Various sets are available. The 11-piece set illustrated comprises an 85mm quick-release bit holder and ten colour-coded bits with a sand-blasted finish. Two 28-piece sets are also available.

All three sets come in a robust steel storage case lined with industrial foam to prevent the bits rolling around. The bits are also available separately. Prices start at £18.96 for the 11-piece set, £2.26 for individual bits and £3.96 for bit holders.

www.axminster.co.uk

Yandles have just announced the line-up of demonstrators for their forthcoming show on April 10-11. Mick Hanbury, Tracey Owen and Mary Ashton will be amongst the turners alongside Rod Page and, new to Yandles, Keith Fenton. Other attractions include Gary Orange (chainsaw carving), Loxtonwood Craft (side axe and adze planking), Lyme Regis Boat Builders and the Japanese Tool Group

The show attracts thousands of visitors from all over the

**Spring show** 



UK and Europe. Joining the demonstrators will be lots of major manufacturers, including Record Power, Brimarc, Sorby and Triton, showing off their latest products and offering special show prices. There is free entry and parking for visitors.

www.yandles.co.uk

#### Festool unplugged

The recent launch of Festool Unplugged sees a combination of new high-performance battery packs and brushless EC-TEC motors, plus the introduction of PowerSelect to offer users more buying flexibility.

The improved battery range sees all 15V and 18V batteries

increasing from 4.2Ah to 5.2Ah, so users can work for 25 per cent longer between charges. This change, plus the new motors, ensures optimal power usage and longer tool life.

PowerSelect offers three different buying variants. The



Basic version includes the cordless tool without battery packs or charger, and comes in a Systainer case with core accessories. The Plus version includes the battery packs and charger. The Set version offers the same as the Plus version but with added extras and accessories. The range is available at specialist retailers now. www.festool.co.uk/unplugged

#### More show news

There 's a tremendous line-up of demonstrators for the Midlands Woodworking & Power Tool Show, including Andrew Hall, Jennie Starbuck, Tony Wilson, Reg Slack, Wayne Mack, Michael Painter, Mick Hanbury, Colin Hickman, Mark Raby, Nic Westermann, Peter Tree, Bob Neill and Peter Sefton.

The show takes place at the Newark Showground, Nottingham on March 27-28, and promises to be an excellent day out with over 50 trade stands to visit as well.

www.nelton.co.uk

### **ORDER BY 8PM** GET IT NEXT DA

Ironmongery Direct

MASTERS OF OUR TRADE





### A great day out full of Demonstrations, Personalities, Trade Stands, Advice & Fun

Advance tickets can be purchased by calling the ticket hotline:

01474 536535

or securely through PayPal at www.nelton.co.uk

Free parking, Showguide and Raffle.
Open Hours:

**10:00am – 4:00pm Both Days.** 

#### **Entry:**

One day £8 / In advance £6
Two days £12 / In advance £8
Under 16's Free

Advance tickets on sale from 5th January 2015
(Ticket Hotline closes 23rd March 2015)

### In brief...

#### More accessories

Dremel has launched a new seven-piece DSM20 compact saw accessory cutting set, a new multipurpose router bit set and new multipurpose and EZ SpeedClic accessory sets.

The DSM20 saw kit includes cutting discs, wheels and blades for a wide range of cutting tasks, and sells for £45. The router set includes seven bits in a smart wooden storage box, and costs £34.99.

The 100 and 150 piece multi-purpose accessory sets are priced at £29.99 and £34.99 respectively. www.dremel-direct.com



#### **More Araldite**

Araldite adhesives' recently increased product range is now stocked by Decco Home & Garden outlets, and are also featured in the RS Components on-line catalogue.

Decco has added to its core Araldite offer with a range introduced earlier this year that includes Araldite Super Glue in both liquid and gel 3g tubes, plus Araldite Instant Fix, Araldite Crystal Fix and Araldite Outdoor Fix 'grab' adhesives.

The Araldite range of carded adhesives was revitalized just a couple of years ago.

www.go-araldite.com

#### Leigh takeover

Axminster has just completed a deal which will give the company exclusive rights to sell Leigh products throughout the UK and Ireland. Leigh Industries

is the most innovative and highest quality manufacturer of dovetail jigs, with a range that includes the awardwinning D4R Pro, Super Jigs and the recentlyintroduced RTJ400 jig.

A demonstration of these machines can be arranged at any Axminster store. There is also the opportunity for customers to have their routers set up for free when they purchase a Leigh jig. For

more information about this and to book a demonstration in advance, customers are asked to contact their nearest store.

Axminster also offers a




one-day introductory course to Leigh jigs in its Skill Centres in Axminster and Sittingbourne. Dates and further details about the course can be found at axminsterskillcentre.co.uk

www.axminster.co.uk

#### Three steps to heaven

Simply Stairs by Mark Milner (an occasional contributor to The Woodworker) guides the reader through all aspects of the design and construction of a wide range of timber staircases, step-by-step. It provides anyone with a basic knowledge of woodwork with the know-how and confidence to construct this most important of building elements from start to finish. The book also features the author's acclaimed 'Rise & Going Calculator' - a unique easy-to-read chart which aids stair calculations by eliminating the need for geometry and trigonometry.

The book is likely to be indispensable for students,



apprentices, college lecturers and tradespeople, and will also become the handbook of choice for all those involved with do-it-yourself and self-build projects. It costs £25.

www.whittlespublishing.com

#### DIARY

#### **FEBRUARY**

#### **Axminster Skill Centre courses**

19-20 Beginners woodturning

21 Sharpening with Tormek \*

23 Pyrography

23-24 Beginners routing

24 Scrollsaw course \*

\* Course held in Sittingbourne, Kent Unit 10 Weycroft Avenue, Axminster EX13 5PH 0800 975 1905

www.axminsterskillcentre.co.uk

#### FFX Tool Show 2015

27-1 March Kent Event Centre, Maidstone ME14 3HT 01303 852692 www.ffx.co.uk

#### **Record Power Road Show**

20-21 Yandles, Martock TA12 6JU 01935 822207 www.yandles.co.uk

#### **West Dean College courses**

20 Turning a wooden bowl 20-22 Turning green wood 27 Gilding furniture and frames 01243 811301

www.westdean.org.uk

#### MARCH

#### **Axminster Skill Centre courses**

3 Introduction to Leigh jigs \*

5 Turning wooden fruit

5-6 Beginners routing

\* Course held in Sittingbourne, Kent Details as above

#### **Record Power Road Show**

13-14 Paskins, Kidderminster DY11 7QP 01562 829722

**14** Snainton Woodworking Supplies Scarborough YO13 9BG 01723 859545

#### **South-East Woodworking Show**

6-7 Kent Country Showground, Detling ME14 3JF 01474 536535 www.nelton.co.uk

### **ORDER BY 8PM** GET IT NEXT D

Ironmongery Direct

MASTERS OF OUR TRADE



### YANDLES 2015 WOODWORKING

#### WOODWORKING SHOW AND SALE



Friday 10th April (10am-5pm)
Saturday 11th April (10am-4pm)

Watch top Wood Turners, Chain Saw Carving, learn how to make a boat, or a guitar and much more.

See demonstrations in lots of different crafts, be inspired, and pick up a bargain!

DON'T MISS THIS OPPORTUNITY TO VISIT AN UNIQUE



FANTASTIC
DEMONSTRATIONS
IN WOOD
AND CRAFT

- TRADE STANDS WITH SHOW OFFERS
- OUTSTANDING
  SELECTION OF
  TIMBER
  WITH SPECIAL
  SHOW DISCOUNTS
- USIT OUR
  GALLERY, CAFÉ,
  HOBBY SHOP
  AND REFRESHMENT
  MARQUEE
- AA SIGN POSTED
  FREE ENTRY
  & PARKING

Check out our website: www.yandles.co.uk for further details.

#### **YANDLE & SONS LTD**

Hurst Works, Martock, Hurst TA126JU Tel: **01935 822207** E-mail: **info@yandles.co.uk www.yandles.co.uk** 



# Distributors of the original RELAX workshop stoves




- Cast iron tops
- Superior air controls
- Unbeatable quality
- Range of 7 stoves
- Best workshop stoves on the market
- Still sold with a personal service

#### Phone: 01889 565411

Dovefields Industrial Estate, Uttoxeter ST14 8GA

Find us on Facebook "thehotspotuk" f

www.thehotspot.co.uk



### What's new from



'THE' TOOL SPECIALISTS • WWW.DM-TOOLS.CO.UK • 020 8892 3813

#### FESTOOL 10.8V CORDLESS DRILL/DRIVERS

MANUFACTURER: Festool **D&M GUIDE PRICE:** See website



Festool have released a pair of 10.8V cordless drill drivers with 2.6Ah batteries – the C-handled CXS Li 2.6 and the T-handled TXS Li 2.6. Both machines offer impressive ergonomics and low weight (0.9kg) for convenient drilling and fastening, and feature both FastFix and CENTROTEC quick tool-change chucks plus an integrated LED light and battery charge display. They have 12 torque settings and 'torque switch off' for precision fastening. They come with a right-angled elbow adapter for drilling at 90°, and two high-quality batteries.



#### **DEWALT DCL060 AREA LIGHT**

MANUFACTURER: DeWalt

D&M GUIDE PRICE: £109.95 (bare)



Also new from DeWalt is the DCL060 LED XR LED area light, which has a 1,500 lumen output and a broad and even beam pattern. It's fitted with a rotatable lamp head for directional control of the light output, and is ideal for lighting work areas with no mains electricity or natural light. When fitted with a 5.0Ah XR Li-ion battery pack (available separately), it offers just over three hours runtime.



#### DEWALT 5.0Ah 6-PIECE KIT

MANUFACTURER: DeWalt D&M GUIDE PRICE: £829.95



DeWALT have launched their first 18V 5.0Ah kit, the DCK694P3. It comprises the DCD995 XRP brushless hammer drill, the DCF886 brushless impact driver, the DCS391 circular saw, the DCG412 angle grinder, the DCS331 jigsaw, the DCL040 work light, three 5.0Ah batteries and a charger, packed in DS300 Tough System kit boxes.

# BRUSHLESS

#### **MAKITA BRUSHLESS ANGLE GRINDERS**

MANUFACTURER: Makita

D&M GUIDE PRICE: See website



Makita have launched a pair of 18V cordless angle grinders, the 115mm (4½in) DGA454Z and the 125mm (5in) DGA504Z, both equipped with highly enhanced brushless DC motors. A built-in controller changes the cutting speed automatically according to load conditions, enabling users to obtain high-speed rotation on light-duty applications and high torque on heavier jobs. With a no-load speed of 8,500rpm, thetools also feature anti-restart and soft start features and a slide switch that's conveniently located for one-handed operation.






**BY PETER DUNSMORE** 

# Sew amazing!

This stylish cherry box was designed to take sewing requisites, but could just as well be used as a jewellery casket. It contains a matching lift-out tray with a clever design feature included in its construction



SEWING BOX CUTTING LIST					
All dimensions are in millimetres					
Part	Qty	L	W	T	
Sides (from)	1	1200	135	14	
Тор	1	350	250	9	
Base (mdf)	1	350	250	9	
Tray sides (from)	1	1200	30	8	
Tray partitions	1	300	19	5	
Tray supports1	400	20	9		
Tray base (mdf)	1	300	200	6	
You will also need enough 3mm square walnut stringing for the edges of the box, cherry veneer to cover					

both sides of the tray base, some suitable material to line the base, two hinges and a box lock.

ost boxes with lids are made as a cube to begin with, and the lid is then severed from the base. This guarantees that the lid will fit the base, and also that the grain will flow through the base and into the lid. It's usual to cut the four sides from one length of timber; this ensures that the grain will flow around the corners of the box too. Obviously one corner where the ends of the board meet will not match perfectly, but if this corner is to the rear of the box it won't be particularly noticeable.

#### **Corner choices**

Most boxes are joined at the corners with 45° mitres, but it's not always easy to cut these accurately. I prefer to use an alternative - a variation on the butt joint (see photo 2), made using a straight fluted router cutter and a router table (or simply the router in conjunction with a straightedge). The joint is simple to make, and at the same time leaves a corner rebate for a length of stringing that conceals the construction.

#### **Preparing the parts**

Most figured hardwood timbers would be suitable for the box so long as the timber is flat and dry. I used a piece of cherry 1200mm long and 135mm wide for the sides, and planed it to a thickness of 14mm.

Fit a straight fluted cutter to the router and cut an 11 x 6mm rebate along both long edges of the timber. Then use a square to mark out the four lengths of timber required, leaving a space of 5mm or so between pieces to allow for the thickness of the saw blade. Cut the four pieces to length and square the ends.

#### **Cutting the corner joints**

Make a simple jig using a couple of pieces of mdf glued together at right angles, photo 1, and cut an 11mm square rebate at each end of the box front and back pieces. The rebates should be cut in two or three passes. Take care to cut them on the correct faces, and mark the timber carefully





Fit the lengths of stringing and hold them in place with strips of masking tape



Note how the lid is secured with shims and masking tape as the lid is separated




Stick abrasive paper to a piece of mdf and sand the sawn edges on it



Drill deep holes in the box sides to receive the ends of the hinge braces



Careful work with a sharp chisel will cut the rebate for the hinge flap



Mark the lock recess, drill out most of the waste and chisel it to shape

so that the pairs of opposing sides are equal in length. Both shorter sides are just cut square at their ends. When the sides are fitted together there should be a 3mm square rebate at the corners, photo 2, into which the stringing will be glued at a later stage. It's always a good idea to try a dry assembly using masking tape so that any slight adjustments can be carried out as required. Then you can cut the 9mm mdf base panel to fit the box.

#### Assembling the box

Brush some pva adhesive into the rebates and assemble the box. The base will keep it square. Use masking tape and cramps to hold the four sides together, photo 3, and

check that the base is pushed firmly into its rebates. Avoid clamping directly over the masking tape, as it's very difficult to remove once it has been pressed into the wood. Use a damp cloth to remove any excess pva adhesive that has squeezed out on the inside of the box before it dries. Allow plenty of time for the glue to dry before removing the cramps.

#### Making the top panel

I made the top panel on this box from a 25mm thick piece of cherry, split down the middle and reverse-matched to produce the mirror image seen on the lid. Begin by planing the board flat on both faces before cutting the board lengthways on the

bandsaw. Both pieces can then be glued together with a plywood tongue to reinforce the join before finishing the panel to a thickness of 9mm. Cut the panel to fit the rebates in the box sides, photo 4. Glue it into place, cramp it securely and put it aside to dry thoroughly.

When the box has dried, fix the stringing into the rebates on all the box edges. I planed some walnut stripwood to a little over 3mm square and glued this in place, using masking tape to hold it, photo 5. When this has dried, sand the walnut flush with the exterior of the box.

#### Splitting the box

This part of the job always tests my nerves... yet I'm always surprised at how easy it is once I've done it. This is my method. Set the fence on the table saw to suit the height of the box lid you require, and check that the blade is set at right angles to the table. Lower the blade and cramp a piece of 12mm thick mdf flat on the table, butted up against the fence. Switch the saw on, raise the blade so it just it cuts through the mdf, and set the depth of cut to 14mm.

#### Safety first

The guard will have to be removed for this stage, and it goes without saying that particular care should be taken to keep your fingers away from the revolving blade. Hold the box against the fence, flat on the mdf, and slowly push it forward to cut the first side of the box.

When you've done this, slip a shim of wood into the saw cut and secure it with masking tape, photo 6. Then rotate the box through 90° and cut the second side. Repeat this process for the remaining sides. The result should be a clean cut on both the lid and base. The packing pieces and the tape keep the two halves together as the fourth cut is made.

You can then peel off the tape and clean off the saw marks using abrasive paper. I use double-sided tape to stick two sheets of paper next to each other on a piece of mdf, and then gently rub the box lid and base in turn over the abrasive to clean up the sawn surfaces, photo 7.

#### Fitting the hinges

Although fiddly and time consuming to fit, quadrant hinges are probably the best type to use for boxes as the stays prevent the lid from tipping too far back. Begin by drilling deep holes in the top edge of the box sides to accept the stays, photo 8. Use a sharp pencil or a craft knife to mark out the shape of the hinge on the box sides. Then chisel out each recess to a depth equal to half the thickness of the hinge knuckle, **photo 9**. Repeat this process for the lid of the hinge.

The secret of success is to ensure that the knuckle of the hinge protrudes at the rear of the box by the same amount on both the base and the lid – in this case, by half the thickness of the knuckle.

#### Fitting the lock body

Now it's time to mark out the position of the brass lock. Use a drill to remove most of the waste wood by drilling a series of perpendicular holes down into the front edge of the box. Then chisel out the recess for the lock, **photo 10**. Careful measuring and the use of a small square will locate the position of the hole required to suit the pin and the key.

#### **Creating the escutcheon**

This is made from a piece of walnut about 3mm thick which will complement the stringing around the perimeter of the box. Mark out the kite shape and the position the keyhole on a vertical line in the middle of the kite. Then use two suitably sized drill bits and a small chisel to form the keyhole, **photo 11**.

Hold the escutcheon in place on the box front and score round the perimeter of the piece with a craft knife. Remove sufficient waste to insert the escutcheon level with the box. An accurate method is to use a very small inlay router cutter – only 2mm in diameter – and to manoeuvre the router very carefully (see **photo 11** again) before using a chisel to trim the remaining waste back to the scored lines, **photo 12**. Alternatively, just cut the kite shape right the way through and fit a thicker insert!

#### Fitting the lock catch

The next job is to cut the recess in the box lid to receive the lock catch. For the box to lock precisely it's important that the catch is located accurately. The method I find





Mark out the escutcheon, cut it to shape and create the keyhole cutout in it



Use a small router cutter to form the recess and finish it with a chisel



Mark the position of the lock catch on the lid and chisel out its recess



Form a bottom rebate and a top bevel on the wood for the tray sides

easiest is to file away the two lugs on the back of the catch. Put a strip of double-sided tape on the back of the catch, fit it to the lock and turn the key to secure it. Close the lid down onto the box and press hard above the lock area. Turn the key and lift the lid, taking the catch with it. This gives you the exact location where the catch needs to be let into the wood. Mark round the catch, remove it and use a sharp chisel to cut the recess so the catch fits level with the surrounding timber, **photo 13**.

#### The tray design

The lift-out tray sits on two pieces of cherry that have been cut and glued in place on the inside faces of the box sides. The tray is



Use a sharp knife to score a line on each piece where the mitre will be

a little fiddly to make, but the end result is worth the effort. In the past I've made trays with small handles or rings at the ends of the box, but for something different this time I decided to make an opening in the middle of the tray into which a hand could be inserted to lift it out.

The base of the tray is mdf covered on both sides with cherry veneer to match the box. The tray sides are 6mm thick cherry, with a rebate cut along the lower edge to receive the base and a shallow bevel formed along the top inside edge to soften its overall appearance, **photo 14**. A similar piece is made for the internal wall of the tray, which sits around an opening made in the base using a coping saw.



Sand back to the scored line with the disc sander table set to 45°



Cut V grooves to accept the dividers in the centre of each tray side





#### Mitred corners

For corner mitres to look attractive they need to be cut accurately, and I find the following method works well. Establish the lengths required by measuring the inside dimensions of the box and subtracting about 1mm from each measurement. Use a very sharp knife to score a line across the ends of the timbers, photo 15.

Now set the table on your disc sander to exactly 45°. To check this angle, mitre the ends of a couple of offcuts and bring them together to see if the join is at right angles; if it's not, adjust the table angle accordingly. When you're satisfied with the setting, hold the timber against the fence and push it against the sanding disc. A small burr will appear by the score line. As soon as this falls off, photo 16, pull the timber away from the disc.

#### Making up the tray

Mark out the centre vertical on the inside faces of each of the eight components that make up the walls. Cut a V notch using a mallet and a sharp chisel, photo 17, to suit a corresponding insert piece also shaped on the disc sander. Join the four walls together to form the inside and outside part of the tray.

A method I like is to lay the four pieces together end to end against a suitable straight edge and to pull some masking tight over the joins, photo 18. Turn this over, put a little adhesive in the mitres and fold the pieces into a rectangle; the joins will close up beautifully. The wall around the centre opening is a little trickier to make as the V notches are on the outside.

The partitions are made from 4mm thick cherry, bevelled at the ends either with a chisel or on the disc sander. A shallow bevel is cut along the top edge using a small block plane to blend the partitions into the walls of the tray.

Finish off by applying the finish of your choice. For this box I applied three coats of finishing oil and allowed this to dry. Then glue some suitable lining material into the base of the box and you're done.

#### **FURTHER INFORMATION**

#### **Brass hardware**

- Restoration materials
- **1** 0161 746 2741
- www.restoration-materials.co.uk

#### **Router cutters**

- Trend
- **01923 249911**
- www.trend-uk.com



### DRAPER TOOIS

www.drapertools.com
























### the NEW Draper Tools Catalogue

Ask your local Draper stockist for a copy.





drapertools.con



face







Draper publications are available as a free digital editions app.



\*Prices are typical, may vary in-store and include VAT @ 20%. Correct at time of going to press. E. & O. E.





OPEN HOURS:
10:00AM - 4:00PM BOTH DAYS.
ENTRY:
ONE DAY £8 / IN ADVANCE £6
TWO DAYS £12 / IN ADVANCE £8
UNDER 16'S FREE
ADVANCE TICKETS ON SALE
FROM 5TH JANUARY 2015

(TICKET HOTLINE CLOSES 1ST MARCH 2015)



A Show full of Demonstrations, Personalities, Trade Stands, Advice and Fun. ADVANCE TICKETS: Ticket Hotline 01474 536535 or buy securely Online at www.nelton.co.uk

Jennie Starbuck





**BY KEITH SMITH** 

# Spot the bed!

Space is something we're all short of, and the idea of making a room serve two purposes is not a new one. It nearly always ends up in a compromise, but here's a potential solution that really works


ake sofa beds, for instance. The downside of using one is that it's normally in the living room, so when it's in use the main part of the house is off-limits until your guests get up. So when a customer asked how she could create a sewing room, without building an extension, I suggested fitting a hideaway bed in the spare bedroom.

She wanted a really comfortable bed that was easy to fold away. Ideally she wanted to buy her own mattress, rather than be tied to a thin one specifically designed to work with the bed, and after a search of the

internet we found a company called Hideaway Beds based in Devon, offering a range of beds which fitted the bill. It was too far to travel down to visit their showroom, so I gave them a call to ask their advice on which of their models would work best. They recommended their Alpha Bed as the most suitable for our requirements.

#### Too clever by half

This bed kit costs £550 for a standard double bed, which includes VAT and delivery, and for that you get just two boxes of various metal components. When they



I prepared all the mdf parts in the workshop, starting with the side panels which featured shaped cut-outs to fit over the skirting boards



I biscuit-jointed the top panel to the top fascia to give it extra strength and to make alignment of the components easier



Marking the position of the lift mechanism on the side panels was critical, as any inaccuracies would make its assembly impossible



I then bored deep countersinks to house the large machine screw heads, so they wouldn't be so noticeable when the bed was assembled



On site I started out by assembling the outer frame where it was to be fitted

first launched the bed they had several returned when customers, thinking it was like an Ikea flatpack, bought the bed but couldn't assemble it. So now it's sold only to the trade, as it takes a degree of woodworking skill and equipment to make the housing and assemble the frame. However, they will sell the kit to competent

woodworkers if you give them a call and tell them you know what you're doing!

In reality, it's not that difficult to make a simple mdf frame and assemble the bed; it just needs a few tools, a bit of space to cut the panels to size and a degree of patience. The kit comes with a set of comprehensive instructions, written in clear English, which

makes the job much easier than trying to follow the pictorially incomprehensible set of drawings you usually get.

#### **Design options**

Of course it's possible to make a more complicated frame and completely hide the bed in a run of units, or even to disguise it as a bookcase for instance, and the company's website has plenty of examples to spark off your creativity.

For this bed we went for the middle of the road as regards design; it has an mdf carcass which I spray-painted in the workshop, and a single-piece front panel. This turned out to be the only major problem, as it was a nightmare trying to manoeuvre this large pre-painted panel through the house and up the stairs!

#### **Preparing the parts**

The bed consists of a simple housing; it's designed so a site carpenter can make it up on the premises and the kit comes with various brackets, so there's no need to even cut a joint. However with my customer wanting a painted finish, I cut everything in the workshop and test-assembled it there before spraying the parts.

The instructions that come with the kit



The rear base panel is fitted slightly forward to accommodate the skirting board



The number of springs counterbalances the weight of the mattress and panel



The heads of the fixing bolts are visible on the outside face of the side panels



It was easier to have a single front panel as the metal bed frame was bolted together section by section...



...but I had to buy some shorter screws that wouldn't penetrate the face of the panel to fix the cross braces in place

include a full cutting list for the various bed size options. All the panels are cut from 18mm thick mdf.

The instructions recommend making four panels for the front of the bed in order to make it look like two pairs of wardrobe doors, but my customer wanted a single panel (measuring 1964 x 1460mm) as she intended to fit a large magnetic noticeboard extending almost the full width of the bed. Thankfully, the beauty of this kit is that you're not really constrained at all over the final look of the unit.

#### **Workshop operations**

After cutting the side panels to size, I used a router cutter to form the cut-outs over the skirting boards, **photo 1**. The kit comes with brackets which allow simple assembly, but I biscuit-jointed some joints – to attach the top panel to the top fascia, **photo 2**, for example.

The next step was to mark out for the position of the lift mechanism on the side panels, **photo 3**; it was absolutely critical to get this right. I then bored deep countersinks on the outside of the panels to house the large machine screws which will attach the lift mechanism, **photo 4**. Finally, I cut biscuit slots in the side panel to help fix and locate the various parts of the bed frame.



Access to the screws was awkward in places; using two hex bit holders in line helped

#### Starting the installation

I assembled the mdf frame in the room where it was to be fitted, **photo 5**. The room has tall skirting boards, and I had previously created cut-outs in the side panels to clear them. At this stage it's rather wobbly, but it's extremely important to get it square before attaching it to the wall. I found it was best at this stage to just fix it to the wall loosely (but securely) with a couple of brackets, ideally ones that allow a bit of adjustment.

In **photo 6** you can see the cut-outs in the side panels abutting the skirting board.



Once the metal frame was attached, the short arm of the lift mechanism was angled forward

The base panel has been fitted slightly forward to accommodate the skirting board, but there was still plenty of clearance between it and the mattress.

#### Adding the lift mechanism

The lift mechanism comes with a number of springs, **photo 7**. After reading the instructions I made an educated guess as to which ones to fit to counterbalance the weight of the mattress and panel I was intending to use. It is possible to alter the springs once the bed is fitted, but this time I was fortunate in



Despite my careful positioning of the frame, the bed did not fit perfectly squarely to start with



Next, I fitted the mattress and added the cover plates which hide the mechanism



The angled headboard prevents pillows from falling down behind the bed



that, for once, I guessed right!

One thing I hadn't initially realised (although it makes perfect sense when you take into account the loads that the lift mechanism has to cope with) is that the fixing bolts are visible on the outside face of the side panels, **photo 8**. This wouldn't matter if the bed was to be built into a run of units, but as a stand-alone unit they were going to show unless a decorative panel was

fitted over each side of the bed frame. That said, mine were neatly countersunk into the side panels, and in the end my customer chose to leave them on view rather than lose any more space along the wall.

#### Assembling the frame

It was probably easier at this stage to have the single front panel as the metal frame for the bed was bolted together, **photo 9**. However, this is when things became a little bit trickier. If we had fitted the four 'doors' recommended in the instructions, I would have had eight stiles to screw into, but with my single door I had to screw the metal cross braces to the centre of the thin panel, **photo 10**. This meant a trip out to the ironmongers to get some shorter screws to ensure they didn't show on the front face.

Access to the screws was a bit awkward in places, and I found using two hex bit holders in line helped, **photo 11**. A power driver is vital as there are a lot of screws to drive...

Once the metal frame was firmly fixed to the panel, I positioned the lift mechanism so the short arm was angled forward, **photo 12**. The bed frame was then slotted onto the lift mechanisms and a single bolt fitted to each side. This was definitely a two-person job!

#### **Final adjustments**

Despite all my careful initial positioning of the frame the bed did not fit perfectly squarely, **photo 13**, and I had to fit a couple of packers under the sides and reposition the top of the frame slightly to one side to get it to fit perfectly.

Once the panel was fitted squarely within the frame, I installed the mattress onto the bed; without its weight the bed will swing up alarmingly quickly. At this point it may be necessary to adjust the springs so the bed swings up and down with little effort. I think this would be quite a tricky job, and I was very relieved when I found that I'd guessed correctly with the spring settings. Once I was happy that the springs were set in balance, I fitted the cover plate that hides the mechanism, **photo 14**.

The angled headboard prevents pillows from falling behind the bed and also helps to brace the two side panels, **photo 15**. If you felt inclined you could make this far more decorative, so long as it cleared the bed when it was folded up. The kit comes with a pair of fold-down feet which help to keep the mattress in place when the bed is folded up, as you can see in the final photo.

My customer has been using the bed for a few months now, and has found it very easy and convenient to use. It's still awaiting its magnetic noticeboard though, as she hasn't yet plucked up the courage to drill into the pristine front panel!

#### **FURTHER INFORMATION**

- Hideaway Beds Ltd
- Plympton, Devon PL7 4JH
- **■** 01752 511111
- www.hideaway.co.uk



Quality • Innovation • Performance • Beyond all expectation





For extended rail use two guide rails, which can easily be fitted together with the connection piece.



The MT 55cc works with or without a rail - simply turn the pointer to show the exact cutting depth.



Mafell offers the fastest blade change worldwide. Simply press the release button and lift the lever.













#### GET YOUR FREE COPY lOW!

- **IN-STORE** ONLINE
- PHONE

**0844 880 1265** 





#### Record WY7

	MODEL I	MOUNTING			
		(V	VIDTH/OPENIN		
			/DEPTH)mm		
	Clarke	Bolted	150/152/61	£13.49	£16.19
	CHT152				
	Stanley	Clamped	72/60/40	£16.99	£20.39
	Multi Ángle				
	Record V75B	Clamped	75/50/32	£18.99	£22.79
Ų	Clarke WV7	Bolted	180/205/78	£24.99	£29.99

#### Clarke WHETSTONE SHARPENER



#### **TURBO AIR** airmaster **COMPRESSORS**

Superb range ideal for DIY. hobby & semiprofessional use





JINC.VAI		- 10		0/	230
MODEL	MOTOR	CFM	TANK	EX VAT	INC VA
Tiger 8/250	2Hp	7.5	24ltr	£79.98	£95.9
Tiger 7/250	2 Hp	7	24ltr	£89.98	£107.9
Tiger 8/36	1.5 Hp	6.3	24ltr	£109.98	£131.9
Tiger 11/250	2.5Hp	9.5	24ltr	£119.98	£143.9
Tiger 8/510	2Hp	7.5	50ltr	£129.98	£155.9
Tiger 11/510	2.5Hp	9.5	50ltr	£149.98	£179.9
Tiger 16/510	3 Hp	14.5	50ltr	£219.98	£263.9
Tinor 16/1010	3 Hn	1/15	100ltr	80 0903	£333 0

#### Clarko TABLE SAW WITH **EXTENSION** CTS14 TABLES (250mm)



mechanism for table extensions • 0-45° tilting blade • Cutting depth: 72mm at 90° / 65mm at 45° | 230V/50Hz. Motor: 1800W

Motor: 1000vv, No load speed: 4700rpm Shown with optional leg kit CLK5 £22.99 exc.VAT £27.59 inc.VAT

#### 10" SLIDING Clarke MITRE SAW For fast, accurate cross, bevel & mitre cutting in most hard & soft woods 1800w £129 £155i98 CMS10S2

#### Clarke Mitre SAW STAND



#### **Clarke** DOVETAIL JIG

Simple, easy to set up & use for producing a variety of joints • Cuts work pieces with a thickness of 8-32mm • Includes a 1/2" comb template guide & holes for bench mounting



#### Clarke ROUTERS



* DIY	1			
MODEL	MOTOR	<b>PLUNGE</b>	<b>EX VAT</b>	<b>INC VAT</b>
	(W)	(mm)		
CR1C*	1200	0-50	£39.98	£47.98
Bosch	1400	0-55	£74.99	£89.99
POF1400ACE				

#### **Clarky** scroll saws



		SPEED	EX	INC
MODEL N	IOTOR	RPM	VAT	VAT
CSS400B	85w	1450	£64.99	£77.99
CSS16V	120w	400-1700	£79.98	£95.98
CSS400C*	90w	550-1600	£99.98	£119.98
* Includes flex	ible drive	e kit for grind	ing/polishi	ng/sanding

### MITRE SAWS TH-SM 2534 Quality Range of Mitre saws and blades avail

55/120mm £54.99 £65.99 210/30 TH-MS 2112 Fury 3 210/25.4 Einhell 250/30 TH-SM2534 Makita 260/30 60/200mm £119.98 £143.98 75/340mm £159.98 £191.98

95/130mm £199.98 £239.98

#### LS1040 **ROTARY TOOL** Clarke KIT



Height adjustable stand with clamp • Rotary tool
 1m flexible drive • 40x accessories/consumables

#### Clarke 6" BENCH GRINDER WITH SANDING BELT



.



7,400-21, 600 rpm • 2100w motor • 0-60mm plunge depth. CR3 Router with 15 Piece Bit Set also available only £94.99

£113.99 PIECE SET WOI OVER £20

#### Clarke ROUTER TABLE



table . Suitable for most routers (up to 155mm dia, Base plate)

#### DUST EXTRACTOR/ CHIP COLLECTORS Clarke





50 litre tank capacity 183 m3/h flow rate 1000W wattage

#### £119:98 Clarke BENCH GRINDERS



eatures
" whetstone &
"drystone.
With sanding belt

	5		_	
MODEL	DUTY	WHEEL		
		DIA.	<b>EX VAT</b>	INC VAT
CBG6RP	DIY	150mm	£27.99	£33.59
CBG6RZ	PR0	150mm	£37.99	£45.59
CBG6RSC	HD	150mm	£47.99	£57.59
CBG6SB#	PR0	150mm	£49.98	£59.98
CBG6RWC	HD	150mm	£54.99	£65.99
CBG8W (wet)	HD	150/200mm	£55.99	£67.19

#### **evolution** 255mm MULTI-**PURPOSE** TABLE **SAWS** 149 179

VA DEPTH CUT SIZE (mm) 781 VAI 45° 90° FURY5\* 54mm 73mm 625x444 £149.98 £179.98 AGE5‡ 55mm 79mm 868x444 £269.00 £322.80

FURY power: 1500w (110V available) RAGE power: 1800w/230V (110V available) table extensions included

\* was £191.98 inc.VAT ± was £334.80 inc.VAT

#### QUALITY CAST IRON STOVES





#### **Clarke** Circular Saws



ODEL MOTOR MAX CUT 90/45	ncludes ser guide		1	
(mm) EXC.VATING		MOTOR	90/45	INC

			90/45 (mm) l	EXC.VATI	NC.VA
7	Clarke CCS185B	1200W	65/44	£34.99	£41.9
ı	Clarke CC52	1300W	60/45	£59.98	£71.98
ı	Clarke	1000W	00/40	CEO 00	074.00

#### Clarke HARDWOOD WORKBENCH

Includes bench dogs and guide holes for variable work positioning • 2 Heavy Duty Vices
 Large storage draw • Sunken tool trough
 LxWxH 1520x620x855mm



#### Clarke SPCE FORSTNER BIT SET

**CHT365** 

• Contains 15, 20, 25 35mm bits • Titanium nitride coated for improved cutting finish



#### OPEN MON SAT 8.30-5. VISIT VOLID I 392 256 744 91 493 2520 41 332 9231 452 417 948 1472 354435 1482 223161 08 518 4286 1473 221253

AISII AOOU F	UCA
BARNSLEY Pontefract Rd, Barnsley, S71 1EZ	01226 732297
B'HAM GREAT BARR 4 Birmingham Rd.	0121 358 7977
B'HAM HAY MILLS 1152 Coventry Rd, Hay Mills	0121 7713433
BOLTON 1 Thynne St. BL3 6BD	01204 365799
BRADFORD 105-107 Manningham Lane. BD1 3BN	01274 390962
BRIGHTON 123 Lewes Rd, BN2 3QB	01273 915999
BRISTOL 1-3 Church Rd, Lawrence Hill. BS5 9JJ	0117 935 1060
BURTON UPON TRENT 12a Lichfield St. DE14 3QZ	01283 564 708
CAMBRIDGE 181-183 Histon Road, Cambridge. CB4 3HL	
CARDIFF 44-46 City Rd. CF24 3DN	029 2046 5424
CARLISLE 85 London Rd. CA1 2LG	01228 591666
CHELTENHAM 84 Fairview Road. GL52 2EH	01242 514 402
CHESTER 43-45 St. James Street. CH1 3EY	01244 311258
COLCHESTER 4 North Station Rd. CO1 1RE	01206 762831
COVENTRY Bishop St. CV1 1HT	024 7622 4227
CROYDON 423-427 Brighton Rd, Sth Croydon	020 8763 0640
DARLINGTON 214 Northgate. DL1 1RB	01325 380 841
DEAL (KENT) 182-186 High St. CT14 6BQ	01304 373 434
DERBY Derwent St. DE1 2ED	01332 290 931
DONCASTER Wheatley Hall Road DUNDEE 24-26 Trades Lane, DD1 3ET	01302 245 999
EDINBURGH 163-171 Piersfield Terrace	01382 225 140 0131 659 5919
EDINDUNUM 109-11 I FIGISIIGIU IGITAGE	01910999919

	OPEN MIC
L SUPERSTORE	■ SAT 8.30-5
EXETER 16 Trusham Rd. EX2 8QG	01392 256 744
GATESHEAD 50 Lobley Hill Rd. NE8 4YJ	0191 493 2520
GLASGOW 280 Gt Western Rd. G4 9EJ	0141 332 9231
GLOUCESTER 221A Barton St. GL1 4HY	01452 417 948
GRIMSBY ELLIS WAY, DN32 9BD	01472 354435
HULL 8-10 Holderness Rd. HU9 1EG	01482 223161
ILFORD 746-748 Eastern Ave. IG2 7HU	0208 518 4286
IPSWICH Unit 1 Ipswich Trade Centre, Commercial Road	01473 221253
LEEDS 227-229 Kirkstall Rd. LS4 2AS	0113 231 0400
LEICESTER 69 Melton Rd. LE4 6PN	0116 261 0688
LINCOLN Unit 5. The Pelham Centre. LN5 8HG	01522 543 036
LIVERPOOL 80-88 London Rd. L3 5NF	0151 709 4484
LONDON CATFORD 289/291 Southend Lane SE6 3RS	
LONDON 6 Kendal Parade, Edmonton N18	020 8803 0861
LONDON 503-507 Lea Bridge Rd. Leyton, E10	020 8558 8284
LONDON 100 The Highway, Docklands	020 7488 2129
LUTON Unit 1, 326 Dunstable Rd, Luton LU4 8JS	01582 728 063
MAIDSTONE 57 Upper Stone St. ME15 6HE	01622 769 572
MANCHESTER ALTRINCHAM 71 Manchester Rd. Altrincha	
MANCHESTER OPENSHAW Unit 5, Tower Mill, Ashton Old F	
MANCHESTER SALFORD* 209 Bury New Road M8 8DU	0161 241 1851
MANSFIELD 169 Chesterfield Rd. South	01623 622160

N-FRI 8.30-6.00, .30, SUN 10.00-4.00 *NEW S	TORE
MIDDLESBROUGH Mandale Triangle, Thornaby	01642 677881
NORWICH 282a Heigham St. NR2 4LZ	01603 766402
NOTTINGHAM 211 Lower Parliament St.	0115 956 1811
PETERBOROUGH 417 Lincoln Rd. Millfield	01733 311770
PLYMOUTH 58-64 Embankment Rd. PL4 9HY	01752 254050
POOLE 137-139 Bournemouth Rd. Parkstone	01202 717913
PORTSMOUTH 277-283 Copnor Rd. Copnor	023 9265 4777
PRESTON 53 Blackpool Rd. PR2 6BU	01772 703263
SHEFFIELD 453 London Rd. Heeley. S2 4HJ	0114 258 0831
SIDCUP 13 Blackfen Parade, Blackfen Rd	0208 3042069
SOUTHAMPTON 516-518 Portswood Rd.	023 8055 7788
SOUTHEND 1139-1141 London Rd. Leigh on Sea	01702 483 742
STOKE-ON-TRENT 382-396 Waterloo Rd. Hanley	01782 287321
SUNDERLAND 13-15 Ryhope Rd. Grangetown	0191 510 8773
SWANSEA 7 Samlet Rd. Llansamlet. SA7 9AG	01792 792969
SWINDON 21 Victoria Rd. SN1 3AW	01793 491717
TWICKENHAM 83-85 Heath Rd.TW1 4AW	020 8892 9117
WARRINGTON Unit 3, Hawley's Trade Pk.	01925 630 937
WIGAN 2 Harrison Street, WN5 9AU	01942 323 785
WOLVERHAMPTON Parkfield Rd. Bilston	01902 494186
WORCESTER 48a Upper Tything. WR1 1JZ	01905 723451
alls from mobiles and other networks may vary.	

7 DAYS EASY WAYS TO BUY IN-STORE

ONLINE

**MAIL ORDER** 

CLICK & COLLECT





# CELEBRATING 100 YEARS TRADING NOW WITH OVER 100 TOOLS IN 18V LI-ION



#### LEADING THE CHARGE: UNBEATABLE CHARGE TIMES ON ALL 18V LI-ION



22 minute charge 3.0Ah BL1830



36 minute charge 4.0Ah BL1840



45 minute charge 5.0Ah BL1850



Makita Lithium-ion Range Scan the QR code or visit www.makitauk.com



Visit www.makitauk.com to register for your Makita 3 Year Warranty. Terms and conditions apply.






# Garden comfort

Take some of the strain out of those garden chores with Ben Russell's stylish and ingenious kneeler/stool combination


ow the gardening season is fast approaching, we'll all have to reactivate some muscles we've forgotten about over the winter! When I was a bit younger, I hardly noticed the prolonged periods of squatting or crouching that are often required to keep everything in the garden in shape. These days I'm more liable to stiffen up (or put certain jobs off!) if there's too much discomfort involved.


I made this kneeler/stool for my wife, who does far more gardening than I'll ever do, and I hope she'll get a lot of use out of it. One way



When setting out the legs with the template, allow space for the 30mm diameter holes that will be bored at each end to produce a snug fit with the rake-handle grips

#### WOODWORK | Garden kneeler







The radiuses at the ends of the legs can be sawn, but will need less cleaning up if you can drill them. A Forstner bit in a drill press is ideal



Cut the legs to shape with either a bandsaw or a jigsaw. The former is more likely to produce square sides, but you'll need to fit a fairly narrow blade

# GARDEN KNEELER CUTTING LIST All dimensions are in millimetres Part Qty L W T Seat 1 474 240 19 Legs\* 4 350 50 19 Feet/grips 4 240 30 dia Use 40 x 19 wood for straight legs



Clamp the legs together when shaping and smoothing them so they match. I planed the outer surface, then used 80 and 120 grit abrasive to shape the radiused top

#### Did you know?

Spokeshaves can have flat or radiused soles. The flat-soled versions are used on external curves, or very gentle internal curves, while the radiused version is perfect for tighter internal curves. While the mouth openings can't be adjusted like a plane, metal shims can be placed under the blade to reduce the opening for finer work, or to cut difficult grain. Compare the gap on the left, which is shimmed, to that of the sliver-handled spokeshave on the right, which isn't.





#### Tech tip

Like every other edge tool, spokeshaves do their best work when the cutting edges are very sharp. It's worth making a broad handle with a notch in the end to hold the comparatively short blade securely when you're sharpening it with a bench stone. A Tormek wet grinder has a clever jig that clamps the blade in place at a constant angle, making the sharpening process very easy and quick to carry out. The water-soaked stone keeps the edge of the blade cool during the grinding process, to ensure that the metal isn't softened by overheating. The second wheel is surfaced with leather which, with its dressing of polishing paste, is used to hone the edge to super-sharp condition.



I used two spokeshaves to clean up the inside curves: mostly a flat-soled one, but I also needed one with a curved sole to smooth the tighter radius at the top



Mark out the leg notches carefully – ideally with a marking knife, for accuracy. This small Veritas saddle square is a convenient tool to use where a larger square would feel cumbersome



Use a mortise gauge set to the thickness of the legs to mark out the housings on the seat into which they locate. File its points to score more distinct and accurate grooves

up, it's a sturdy low stool; the other way up it's a kneeler with cushioning for the knees and grips that can provide support to older gardeners while they lower themselves into place or get back on their feet.

#### **Design considerations**

The kneeler looks quite elegant, either way up. Interestingly, this arises almost entirely from functional considerations. The ideal

Clean up the radiuses on the legs with coarse abrasive wrapped round a foot/grip offcut. Do each pair together, and check that the ends are square to ensure a tight fit





There are several ways to cut the notches in the legs. I used a bandsaw, then cleaned the sides with a chisel. The bottom of the cut isn't seen and needs minimal cleaning



With a little care, you can set up a table saw with a cross-slide to cut the leg housings and also to saw up to the holes drilled to help form the cutouts at each end of the seat

specification included a range of ergonomic considerations: an appropriate height and width; light weight; robust construction; stability, and ease of handling. It should be a pleasure to use, starting with picking it up and carrying it to wherever it's needed. The graceful splay on the legs gives more stability to the stool, while also making the kneeling area less restricted than it would be with straight legs.



Make a simple jig to hold the grips while you drill them. The jig runs against a back fence, ensuring that the holes are drilled centrally. Drill a 10mm diameter x 10mm deep hole to take the plug, then a 4mm clearance hole for the screw



An easy way to keep the legs parallel while the grips are fitted is to place them in the seat housings, and to cramp a spacer at the other end. The grip can then be cramped in position while you drill the 3mm pilot hole for the screw



The seat feels better if the edges and the central notches at each end are radiused. A 6mm radius cutter with a bearing guide makes this an easy task. Non-slip matting on the bench holds the timber without the need for clamps



When the legs and grips are assembled, check that the notches fit. Cut plugs from 10mm dowel rod and chamfer one end to help them go in smoothly



The dimensions used here are right for my wife and me, who are of fairly average build and height. Someone carrying a bit of weight might choose to make the seat and legs a little broader.

Finally, the materials have to suit the function: they must be strong but not too heavy, and durable enough to survive casual handling and inevitable soaking. I used chestnut for the seat and legs, and recycled a broken rake handle for the feet/ grips. The kneeler pad is a cut-down garden kneeler – available very cheaply from garden centres - made of closed cell foam, so it won't absorb water, and is stuck to the underside of the seat.

#### **Assembly notes**

The seat has three notches cut at each end. The outer two are housings for the leg assembly, and the middle one gives hand clearance around the grip. The edges of the seat can be radiused with a router, or chamfered by hand; likewise the central notches at each end.

The curved legs are cut from broader 50 x 19mm wood, and the key to success is to make an accurate template by enlarging the pattern in the drawing. The curves present a few challenges, and beginners should probably stick to the straight alternative in the drawing, which is both easier to mark out and to cut and finish. The radiuses at each end can be formed very simply if you have a 30mm drill bit (and leave some spare material); otherwise cut them with a bandsaw or jigsaw. For convenience and accuracy, the alternative straight legs can be notched for the seat joint before they're shaped.

The four feet/grips are drilled for screws and counter-bored so that the screw heads can be sunk and plugged with 10mm dowel. If you have a pillar drill, It's worth making a simple jig (see photo 11) to help you drill the holes accurately.

Bearing in mind that the kneeler will get left out in the rain, assemble it with polyurethane glue that's both waterproof and gap-filling.

#### **FURTHER INFORMATION Forstner bits**

- Axminster Tool Centre
- **03332 406406**
- www.axminster.co.uk

#### Tormek grinding system Veritas saddle square

- BriMarc
- **03332 406967**
- www.brimarc.com



#### Precisa 6.0 / 6.0 VR / 4.0 - Professional Precision Sawbenches Designed in Germany - Manufactured in Germany - Proven in Germany

No other classic circular sawbench comes close when compared to the Scheppach Precisa 6.0. This ultimate circular sawbench boasts a massive solid cast iron table; accuracy to within 1/10th mm; 110 mm depth of cut on solid timbers; up to 1100 mm cutting width and 1400 mm length of cutting stroke with appropriate optional attachments. An adjustable 8-15 mm grooving cutterhead and pre-scoring with integral motor unit is also available on request. Scheppach Precisa Series circular sawbenches are simply the best investment you can make in a classic circular sawbench if quality, precision and performance are included in your priority list. Why would you even consider compromising?



Model	Product Group Series	Specification includes (as per quoted price)	HP 240v / 415v	Depth of cut & Length of stroke	Price Exc VAT Plus Carriage	Price Inc VAT Plus Cardage
Precisa 3.0 P-1	Workshop	Inc STC + TWE + TLE (see below for explanation)	3.5 / N/A	90 mm × 1400 mm	£1207.50	£1449.00
Precisa 4.0 P-1	Professional	Inc 1.4m STC + TLE (ditto)	3.5 / 5.2	87 mm x 800 mm	£1775.00	£2130.00
Precisa 4.0 P-2	Professional	Inc 1.4m STC + TWE+ TLE (diffo)	3.5 / 5.2	87 mm x 800 mm	£1980.00	£2376.00
Precisa 6.0 P-1	Professional	Inc 2m STC + TLE (ditto)	4.0 / 6.5	110 mm x 1400 mm	£2416.67	£2900.00
Precisa 6.0 P-2	Professional	Inc 2m STC + TWE + TLE (ditto)	4.0 / 6.5	110 mm x 1400 mm	£2590.00	£3108.00
Precisa 6.0 VR P-1	Professional	Inc. 2m STC + TWE + TLE + scrorer (ditto)	4.0 / 6.5 + HP scorer	110 mm x 1400 mm	£2890.00	£3468.00

STC = Sliding Table Carriage, TWE = Table Width Extension, TLE = Table Length Extension.

Scheppach Precisa 3.0 is designed by scheppach in Germany but made in China where scheppach resident englineers oversee manufacturing quality control. Precisa 3.0 has the same warranty as Professional Series. Scheppach machines have been sold and serviced in the UK by NMA since 1972. Go to nmatools.co.uk and see what users say about NMA unprecedented service.





BY ANDY STANDING

# Mitre magic

Mitre joints can be some of the most troublesome woodworking joints. They look very attractive when cut well, but inaccuracies can cause them to gape open. Here's how to get them just right

itre joints appear in many forms, ranging from the simple version with both components cut at  $45^{\circ}$ to meet at a right angle to the more complex joints needed for shapes such as octagons where the mitre angle must be carefully calculated - see the panel, right.

The joint allows two components to be assembled without showing any end grain. It's a vital joint when making up moulded frames as it lets the moulding's profile flow through the joint without distortion. It's a

#### CALCULATING MITRE ANGLES

This is done by dividing 360° by the number of sides your project has and then halving the result. Here's how to calculate the mitre angles for a hexagon.

- Divide 360 by the number of sides;  $360 \div 6 = 60$
- Halve this figure;  $60 \div 2 = 30$
- Therefore the mitre angle required is 30°

demanding joint to cut, as even the smallest inaccuracy shows up as an open joint.

Mitres are extensively used in joinery, though never on the internal corners of skirting boards. The reason for this is that invariably the timber shrinks after jointing, causing the inside of the joint to open and show a marked gap. These joints should always be scribed. Whenever you can, strengthen your mitre joints with tongues or biscuits; this also makes them considerably easier to glue up and assemble.

#### MITRING A FRAME



1 Mark out the 45° cutting angles on the two components using a mitre square



2 Make the cut on both parts. A mitre saw is the most accurate way of doing this



3 Bring the components together and mark the biscuit position across the joint



4 Set the jointer to position the biscuit centrally in the thickness of the timber



5 Apply some pva glue to the biscuit and insert it fully into one of the slots



**6** Glue the mating surfaces of the components and bring the joint together: perfection!

#### MITRING A SKIRTING BOARD



Use a mitre square to mark the position of the corner mitre on the workpiece



Extend the line onto all faces so you can line up the cut with your saw blade




Clamp the workpiece securely in position on the saw table and make the cut



Insert a biscuit to strengthen the joint. Mark its position on both parts



Cut the slot close to the inside edge on each part and insert the biscuit into one slot




Apply glue to the mating surfaces and assemble the external corner joint

#### MITRING UNEQUAL WIDTHS

If the two pieces to be joined are not the same width, the mitre angle will not be  $45^{\circ}$ , even if they are to be joined at a right angle. You have to work out the angle, but this is quite simple.



Mark the width of one piece on the end of the other, using a try square for accuracy



Mark the diagonal. This is the angle of the mitre you need to cut on the first part



Use a sliding bevel to take the angle. This is the mitre angle for the second part



Transfer the angle from the sliding bevel to the mitre saw and make the cut



Re-set the sliding bevel on the second piece, transfer the angle to the saw and make the cut



Assemble the right-angled joint, after adding a biscuit if you need extra strength



#### **Treatex Hardwax Oil**

protects and enhances the appearance of all types of internal wood surfaces including floors, stairs, doors, furniture and worktops. Treatex Hardwax Oil is manufactured on a base of natural sustainable raw materials: jojoba oil, linseed oil, sunflower oil, beeswax, candelilla wax and carnauba wax.

- Brings out the timber grain
- Adds warmth to wood
- Easy to apply
- Quick drying
- No sanding required between coats
- Low odour
- Resistant to spills of water, wine, beer, coffee, tea and fizzy drinks
- Withstands high temperatures
- Very durable
- Easy to clean and maintain
- Spot repairable
- Safe for use on children's toys

tel: 01844 260416

PARCEL --- FORCE



**TURNERS TOOL BOX** 

#### CREATIVE WELSH WOODTURNING LTD.

Turners Tool Box.Com WOODTURNING – WOODWORKING – WOODCARVING **TOOLS & ACCESSORIES** 



Order online Open 24hrs - All at the click of a button and delivered straight to your door

Email: info@turnerstoolbox.com - Tel: 01873 831 589 - Mobile: 07931 405 131



# EXPORE ONLY ES.99! ON SALE NOW!

**explore** is a NEW monthly magazine bursting with extraordinary features, including science, history, technology, space, the environment and much more...

Discover everything from dinosaurs and dungeons to lava and lasers. 100 packed pages each month with beautiful photography and detailed illustrations with easy to understand features for all ages.

DISCOVER YOUR WORLD AND BEYOND

WHY IS
PLUTO NOT
A PLANET
ANYMORE?
INSIDE THE
MIND OF
A SPACE
TRAVELLER

OUR SOLAR SYSTEM AND BEYOND

THE SPACE
TIMELINE
LIVE IN
SPACE?

\*Content is subject to change

Follow us on

### Look out for Issue 2, SPACE, on sale 20th Feb

To advertise in any of the issues, please call David Holden on +44 (0) 1933 709545, or email **david.holden@mytimemedia.com** for details.



BY IAN TAYLOR

## **British bulldog**

My son had been requesting a coffee table for some time, but I was always a bit sceptical about the design he had in mind. He wanted a low table with a shelf, looking as if it had been hewn from a solid slab of timber - the coffee table equivalent of the British bulldog: four-square, thick-set and immovable. So I eventually gave in! I think the end result proves he was on the right lines...



■ his is a really quick project to make. There are no conventional joints; the legs and matching spacers are simply butt-jointed to the top and shelf. Given the huge area of contact at each joint, the butt joints are more than strong enough. However, accuracy is important so I used my Joint-Genie dowelling jig to ensure the alignment was perfect.

This design works better in a timber that doesn't have a very marked figure, because then the legs and spacers tend to blend together with the shelf and top. I chose utile, which has a subdued figure and a rich brown colour when it's finished.

Work started with the boards for the top and shelf panels, which will both measure 945 x 475 x 25mm when prepared. I had in

stock a couple of long utile boards 305mm wide and about 32mm thick, which would be ideal for the top and shelf panels.

I'd hoped to be able to get away with a single butt joint for each panel, but there was a small amount of twist on the boards so I ripped them down the middle to minimise the loss of thickness in squaring them up. If you're careful in re-joining two ripped boards, you can get a seamless end product with virtually invisible joints. I used biscuit joints every 250mm or so to help maintain alignment of the panels during the gluing stage, photo 1.

I glued the top and shelf up in two stages, first re-joining the ripped, squared and thicknessed boards, photo 2, then gluing these up in pairs to give the full-width panels, photo 3. The timber for each panel came from a single board to ensure a good colour match.

The panels needed cleaning up after the gluing stage - a little bit of levelling of the surface, followed by squaring up and matching the size of the top and shelf. Flattening up a panel is best done by planing diagonally across the face, first parallel to one diagonal, photo 4, then changing direction and planing parallel to the other. A finely tuned bench plane helps.

Once I was happy with the flatness on both sides, I trimmed the top and shelf to size and fine-tuned them to exactly the same dimensions. Since they're joined by rectangular blocks at the corners, both components need to be precisely matched



Biscuit joints positiioned every 250mm or so help to align the boards during glue-up



I use an artist's palette knife to spread the pva adhesive evenly on the board edges



I clamped up the boards in pairs first, then paired up the pairs to make up the full-widths








Diagonal planing is the best way to flatten the glued-up panels and remove any squeeze-out



I trimmed the panels to size and fine-tuned them with a small block plane



I did most of the cleaning up work on the legs with a No 3 smoothing plane



in size, and of course perfectly square, if the assembly is to come together accurately. I cleaned up the ends with a small block plane, **photo 5**, then smoothed off the surfaces with a random orbit sander.

#### Simple blockwork

The legs and spacers are all 175mm square and 75mm thick. For a level table the height of each spacer block needs to be identical. I squared up two 750mm lengths, one each for the spacers and legs. However, since my thicknesser can only cope with a maximum thickness of 150mm, I had to do some bench work to ensure a consistent 175mm thickness.

I used one of the beams for the spacers and the other for the legs. That way it was easier to ensure that the components within each group of four were the same height. I cut each component to length on the bandsaw, leaving a sawn edge to be cleaned up with a plane. I did most of the work with a No 3 smoothing plane, **photo 6**, and finished off with a small block plane.

It's important to check regularly that the end-grain edges are square to all long-grain faces. I cleaned up the inside end-grain faces of all the spacers and legs with my random orbit sander at this stage, because they are difficult to get at after the assembly.

#### **Perfect dowels**

The Joint-Genie dowelling jig shown in **photo 7** below allows you to drill precise vertical dowel holes, accurately positioned relative to the edges by use of fences and shims. I positioned two dowel holes on the outside long edge of each leg and spacer, and one at the inside corner adjacent to the long grain edges of the panels.

It's very easy and quick to drill precisely matching holes in the panels and the mating leg or spacer using this jig – see **photo 7** again. I made sure that there was no interference between the dowel holes on either face of the shelf, by simply using different holes in the Joint-Genie array for each side.

Because the top of the shelf and the underside of the top would not be too easy to get at for finishing, I then applied one coat of finish to each face, making sure that the gluing areas for the butt joints were masked off first, **photo 8**.

#### The final glue-up

Although the dowelling jig ensures perfect alignment, the resulting glue-up is a pretty hefty task, simply because of the size and weight of the finished article – the 1.4 cubic feet of utile I'd used weighed around 25kg! So I did the glue up in two stages – building

the upper sandwich of shelf, spacers and top first, **photo 9**, then gluing on the legs.

Once the glue on the full assembly was dry, I cleaned up the faces and end grain round the leg and spacer assembly with my big random orbit sander, again working through the grits, before finishing off with hand sanding to 240 grit. Finally, before finishing, I planed a small chamfer round the top and the vertical edges at the corners to take off the sharp edges.


#### **Finishing touches**

The final finish was several coats of my wipe-on oil/varnish mixture. I gave the top surface five coats, to protect it against spills and hot cups. I rounded it off with a couple of coats of well-buffed wax polish.

I think the end product does indeed achieve the design goal of appearing to come from a solid block and, apart from the timber preparation and finishing, the whole construction took only about two days. But I'm afraid it takes two people to move it easily – just like a bulldog, then!

#### **FURTHER INFORMATION**

- Joint-Genie Ltd
- **01460 57202**
- www.joint-genie.com



The Joint-Genie jig is an invaluable aid for positioning the dowels accurately




I applied one coat of my oil varnish finish to each panel face before starting the assembly



I did the final glue-up in two stages, adding the legs to the panel sandwich in turn

## New premier tool joins the team

The extra-small cordless drill. Available in C-shape or T-shape.





Light, amazingly strong and now available in the classic T-shape, these impressive cordless drills offer exceptional high-power torque, even in hard-to-reach spaces. The compact construction and even weight distribution make them ideal for working overhead. Complete with lithium-ion battery packs, CENTROTEC quick-change system and SERVICE all-inclusive, both C-shape and T-shape cordless drills are perfect for the professional user.

For more information visit your local Festool dealer or www.festool.co.uk/xs

FESTOOL
Tools for the toughest demands

oots for the toughest demands

www.**festool**.co.uk

### The Wood Veneer Hub

After three decades of being at the forefront of supplying the automotive. aviation, marine and design industries, Freed Veneers has introduced The Wood Veneer Hub, an exciting online one stop shop bringing a wonderful selection of high quality natural, coloured, smoked and constructional veneers as well as all the tools and accessories a woodworker would need along the way...



and Stick range. Available in a variety of different species, all pre-sanded, these fully flexible sheets offer an easy solution to the application of wood veneer for any given job.

The Wood Veneer Hub assures that no job is to big or small whether you need one sheet or a thousand. With our factory in Valencia, Spain there is no service that cannot be provided whether it be a panel you need produced or an image etched into a veneer sheet.

Visitors are always welcome to the fully stocked warehouse in Leighton Buzzard, Bedfordshire where you will receive the warmest of welcomes as well as the chance to view the large variety of different species.

So whether you are an antique restorer, furniture maker, boat builder or anyone else after high quality veneers then please do not hesitate to give us a call.









Introducing our beautiful Coloured Veneer Range!

Unit 4 Eden Court, Eden Way, Leighton Buzzard, Bedfordshire LU7 4FY Tel: +44 (0)1525 851166

E-mail: sales@thewoodveneerhub.co.uk

www.thewoodveneerhub.co.uk

### hamilton beverstock

CNC sharpening & metal cutting specialists



#### **BAND SAW BLADES**

Welded to any length



With over 33 years experience in the saw industry, and as a supplier to major machine manufacturers, we know, like thousands of other satisfied customers, you'll be happy with our high quality band saw blades for cutting wood, metal, plastics, food...

... If you're a hobbyist or a professional, call us today for a friendly service, free advice and competitive prices.

#### Hamilton Beverstock Ltd.

Grange Industrial Estate, Llanfrechfa Way, Cwmbran, Torfaen NP44 8HQ.

Tel: (01633) 838900 • Fax: (01633) 873803 email: sales@hamiltonbeverstock.com
















The Old Hyde, Little Yeldham, Nr Halstead, Essex CO9 4QT

Tel 01787 237291 Fax 01787 238522 www.peterchild.co.uk











BY ROBIN GATES

## Take a bow

The bow saw is one of the woodworker's oldest tools, and also one of the most versatile. Here Robin Gates shares his passion for this traditional wooden frame saw

ith its light wooden frame, twisted cord and tensioned steel you could almost believe the bow saw to be an early design of flying machine from the Wright Brothers. In fact its ancestry goes back to the Roman era and beyond, when the wooden frame served to prevent a narrow forged saw blade from buckling as its teeth met resistance from the timber. When advances in casting steel enabled production of a much wider saw blade, the supporting frame was no longer required for rigidity, and frame saws were displaced by the familiar handsaws and backsaws of recent times

#### **Ancient and modern**

Nothing challenged the versatile bow saw, however, until the bandsaw came along. Even now, for many small jobs, the bow saw earns a place in the workshop. Its speciality is cutting curves, and to achieve this it has a blade which is not only narrow for negotiating a tight radius, but which is mounted in brass spigots so it can be rotated by a full 360°.

Add to that the possibility of mounting the

blade to cut on the push or pull stroke and you have the most accommodating saw imaginable. Partly out of habit from using other hand and tenon saws, and partly because I like to have a good view of where the blade enters the kerf, I usually fit the blade to cut on the push stroke.

#### Not really coping

In principle the bow saw works much like the coping saw, in that its frame allows a deep cut and can also be angled in a different plane to the blade when following a curve. Unlike the smaller coping saw, the blade of the bow saw is held in the spigots by loose pins. When your fingers are cold it can be a fiddly business adjusting the blade without dropping the pins, but if the pins are lost they are easy enough to replace - a couple of small wire nails will do the job.

Another difference from the coping saw is that the bow saw's frame allows better adjustment of blade tension. The H-shaped wooden frame has two uprights or cheeks joined by a stretcher fitted using loose mortise and tenon joints. The blade is fixed between the lower ends of the cheeks, while their tops are linked by a loop of cord which is twisted by a wooden toggle, making a windlass and drawing in the tops of the cheeks whose leverage then tensions the blade. The toggle is fitted asymmetrically between the strands of the cord so its long end bears on the stretcher and prevents the cord untwisting. To avoid stretching the cord unnecessarily, I'm in the habit of slackening it by one turn of the toggle before hanging up the saw.

In place of the windlass, some variants were fitted with two threaded rods joined by a bottle screw that was turned using a small



When cutting out a circle, use a two-handed grip with your thumbs on the near cheek



Although the teeth have a rip profile they must cut both with and across the grain when sawing curves



The bow saw can be dismantled in a few seconds for transport or storage



It's a surprisingly child-friendly saw. My son Tom, 10, used it to cut the heel slot for a boot jack



The boot jack does a tricky job with precision, and using it requires minimal effort



Mark a half-thickness line round the edge of a small board with a gauge, ready for resawing

The frame is angled to one side to clear the work, but is unbalanced and needs some extra support from the left hand



tommy bar. Although this arrangement is less primitive, its mechanical advantage may result in over-tensioning and perhaps damaging the frame of a lightly built saw.

Getting a grip

Typical of a traditional hand tool, the bow saw only shows its true colours when it's in the hand and engaged with the timber. The first question arising might be: how do you hold this saw?

Looking at the style of it and perhaps influenced by the way you use a hacksaw, it might appear that you place a hand on each handle, one each end of the blade. However, the furthest handle - the smaller of the two – is there only for rotating the blade to the desired angle. For most purposes I find an overlapping two-handed grip on the nearer - larger - handle is effective, with thumbs either side of the near cheek to prevent the frame capsizing if you're sawing with the frame not vertical.

The saw's round handle and high centre of gravity can make it prone to twist in the hand if it's not well supported but, that said, the very length of the saw's cheeks provides a useful indicator of the angle of cut when blade and frame are in the same plane. Sometimes, sawing a tricky curve slowly, I place one hand on the handle and the other on the frame. At other times, when cross-cutting a greenwood log or when speed is more important than precision, one hand on the frame alone is good enough. It's all down to experimentation: if it feels right, it is right.

#### **Coming apart**

Take a close look at the blade. Although the teeth have the steep pitch and chisel edge of a saw designed for ripping, it also works efficiently across the grain. This should come as no surprise given its intended purpose of sawing curves, the ultimate example of this being an enclosed aperture. To cut one you simply drill a pilot hole on the waste side of the line and assemble the saw with the blade running through the hole, then disassemble the saw when the aperture has been cut.

For anyone who enjoys taking things apart, it's one of the secret pleasures of this saw that it can be dismantled completely in a few seconds, making it easier to stow in the toolbox than it might appear. Untwist the windlass, unpin the blade, remove the cheeks from the stretcher, pull the handles free of the cheeks and you can pack this saw neatly inside a large cardboard tube.

#### Trying it out

If you abide by the adage of using the right tool for the job, you'll probably reserve the bow saw for what it was designed for cutting curves. But if you succumb to curiosity, you'll find yourself using it to tackle a wide variety of cuts in both seasoned and green wood, and to the exclusion of other saws. Even disregarding the sheer delight of its handling, the way it steers so precisely, responding to the slightest change in pressure, and the superbly unobstructed view of the workpiece it allows, who can resist its elegant form?

More confident hands than mine use it to cut the waste from dovetail sockets (I'll use a finer toothed coping saw for that), while chair makers use it for the somewhat coarser work of sawing the seat of a Windsor chair to shape before planing its edges smooth. Both uses exploit the bow saw's lightness and manoeuvrability.

The only caveat I'd add with regard to using a bow saw for straight cuts of any length is that it responds almost too well to the worker's hand. If your mind wanders for even a second its narrow blade will dart off course like a bicycle with loose handlebars, whereas the wide blade of a handsaw in a well-established kerf is more forgiving of a temporary lapse in concentration.

That said, I'd suggest that the adventurous woodworker will go on finding new uses for this saw for as long as it hangs in the workshop.

#### **Child friendly**

When our son Tom was having a difficult time at school in Year 7, we decided to give him a break from the system with a year of home schooling. We included a good spell of woodwork in the Design & Technology component of the National Curriculum, placing emphasis on making things that would be useful around the home.

Following a muddy walk in January and the usual frustrations of getting your boots

off when you're ten years old, cold, tired and hungry, we decided on a boot-removing device as his spring term project.

Having tactfully considered the feasibility of Tom's preference for a voice-activated robot, we settled on the sort of boot jack you find on sale in any garden centre. This required him to saw a largish notch in one end of a 3/4 in thick board to grip the heel of the boot being removed. Suspecting that he might find this hard going with the coping saw, I showed him the larger bow saw. He took to it in an instant, ripping down the tapering sides of the notch and cutting its curved base without a hitch.

Our daughter Annie, 13 at that time, said she was having trouble with the coping saw in her own school DT lessons. I wondered if this was because the coping saw is so light and she was pushing down too hard to make it cut, twisting the blade in the process. I wonder if the more substantial bow saw with its solid wood frame, requiring only the easiest of pushes to keep it cutting, would be a better tool for school workshops.

#### **Book-matching**

A bow saw isn't designed for resawing, that is reducing the thickness of a board by ripping along the lengths of its edges. However, it does have features which recommend it for this job with small boards; the rip tooth blade, the narrowness of the blade reducing friction and allowing good sight of the line, and the ability to angle the frame to pass clear of the board. I used the bow saw to resaw a salvaged elm board when making the candle box (shown right), then used it again to cut its curved edges.

To resaw the board, I first scribed around it to the required thickness using a marking gauge, not forgetting that perhaps 1/16in of thickness would be lost in saw dust. Next I popped the board into the large hand screw and sawed it alternately from each corner, rotating the board 90° after each cut, until the four kerfs met in the middle. Now I had two boards for the price of one, with the grain pattern of one mirrored by the other.

The bow saw has less to recommend it for resawing a long board. Sawing for any length with the frame tilted to one side – so as to pass clear of the board – the saw is unbalanced and requires one hand high on the frame for support. As the narrow blade is prone to wander it can leave a lot of cleaning up to do with the plane. A frame saw designed for resawing has a wider blade spanning the centre of a rectangular frame, so that the stretchers on either side pass clear of the timber and the tool remains balanced



Having sawn from all four corners in turn, the kerfs are about to meet in the middle



I sawed the arched back of this candle box while holding it in a hand screw cramped to the bench



The candle box

completed; all

the other

curves were

also cut with

the bow saw

My bow saw dates from the 1960s and is of unknown make, but it appears identical to Marples saws of that time. The wooden frame is solid beech, which is typical, although I've seen some lovely examples in ash, a timber known for its spring and shock-absorbing character, so well suited to a tool which must be tensioned. On better quality vintage saws, the handles may be of fine-grained boxwood.

Old British tools were made to imperial measurements, so the blade on mine is 12in long and 3/16in wide, with 9 teeth per inch (tpi). The distance between blade and stretcher allows a maximum depth of cut of 6in, but remember you can rotate the blade so in theory the depth of cut is infinite.

Some people have made their own bow saws using a length of bandsaw blade, but you would probably need a bow saw (if not a bandsaw) to cut out the cheeks. Bow saws in various states of repair appear



The resawn boards are book-matched, and are shown here after initial clean up

The narrow blade of the bow saw allows excellent visibility of the work





The saw is good for green woodworking too. I use a one-handed grip and a tall bench dog for support

regularly on eBay, but with an old saw bought 'as seen' you run the risk of it being damaged or blades being hard to find. It's best to avoid disappointment by buying new.

Crown Hand Tools in Sheffield make a bow saw like mine, in beech with a 12in blade, which is available from Mortens Hardware Store in Yorkshire at £59.99. Tools For Working Wood in the USA offer the Gramercy saw in hickory with three interchangeable blades having 10,16 and 24tpi, at \$150. For \$49.95 they will also sell you a kit of brass spigots, handles and blades if you fancy making the wooden frame yourself.

#### **FURTHER INFORMATION**

- Mortens Hardware Store
- **1** 01943 609131
- www.mortensofilkley.co.uk
- Tools for Working Wood
- www.toolsforworkingwood.com

The Woodworker March 2015











### **WOODWORKING IN ACTION**

12th and 13th September 2015

Cressing Temple Barns, near Braintree, Essex CM77 8PD

The European Woodworking Show is an amazing showcase of craftsmen and women from around the world. Set in the beautiful grounds of Cressing Temple Barns in Essex.

The European Woodworking Show, now in its sixth year, will have over 100 exhibitors representing a diverse range of woodworking disciplines. A demonstrator led show supported by quality tool makers.

telephone: 01473 785946

email: enquiries@europeanwoodworkingshow.eu www.europeanwoodworkingshow.eu




## Look what you can do with an Overhead router

I've been a dedicated woodworker all my life, and in my 83rd year I'm still avidly reading The Woodworker and planning various projects. Here's something I've worked on for a long time...

he impetus for my latest overhead router project was driven by necessity. My workshop has limited space - and my bank balance has limited funds! - so purchasing a standard overhead router was not an option. My own overhead router is the culmination of around ten years of development work, during which time I've made refinements to the initial prototype and improved various elements, problem solving as I've gone along.

#### In the beginning

It all started with my floor-standing drill to which I added a compound table (a fixed bed of waterproof ply) and fixed table fences. Searching through my workshop, I rediscovered a stirrup for converting drill



**1** The collet extension was purchased from Record Power. The collets - a 1/4 in TA54 and an 8mm TA32 - and the spiral downcut cutters came from Wealden Tools



2 The cross vice table is mounted on the drill stand and holds the compound table - a fixed bed of waterproof plywood



3 The router is mounted on the stirrup on a Tufnol base. The fine-height adjuster consists of two locknuts, a winding handle and a fixing bracket. I engineered the steel bush to project 2mm below the base of the router



4 The router is controlled by an NVR switch located conveniently below the table



**5** The Tufnol table is attached to the plywood sub-base, which I drilled and tapped in a 40mm square grid. This photograph also shows the dust extraction arrangement



**6** The extension table increases the work capacity dramatically. I made this from 10mm clear acrylic sheet, which I also drilled and tapped in a 40mm square grid



**7** To prevent the extension table from sticking and to ensure a smooth movement, I made the side runner with a spring adjustment. The extension table is locked in place with two 6mm screws, driven into the drilled and tapped holes

mortises to cutting mortises. I realised that the collet extension would be critical to the success of the overhead router. Taking a regular 12mm shank, I used my small Axminster lathe to reduce it to 8mm. Being hardened steel, this was achieved by taking a succession of small cuts and utilising the lathe's auto-feed.



8 The extension table allows me to secure and rout relatively large work pieces - such as those involved in making the ornate cabinet shown on page 49 - with ease and accuracy

#### Mix and match

At this stage I thought I'd cracked it. However, an annoying vibration appeared. This, it turned out, was the result of the reducing collets being plundered from various machines which were in retrospect old and possibly worn. A swift phone call



**9** The finished overhead router is the culmination of many years development, and is a joy to use!

later and with new reducing collets purchased from Wealden, the vibration disappeared.

I sincerely hope this brief account and the accompanying photos are of interest to readers, and that it spurs people on to have a go themselves.

## John Davis Woodturning Centre

... a working woodturning centre run by Woodturners for Woodturners not just a shop

Order on-line via the website, by phone or email













Tel: 01264 811070













Open: Mon - Sat 10am - 5pm, Sun 10am - 2pm

The Old Stables, Chilbolton Down Farm, Stockbridge, Hampshire SO20 6BU

email: admin@johndaviswoodturning.com

hand tools and wood chisels specialist

Ashley lles - Henry Taylor - Robert Sorby - Joseph Marples

Veritas - Clifton - Thomas Flinn - Titebond - Ice Bear...

All items in stock, ready for dispatch.

Junies marked otherwise.

Tool

Saw horses

turning tools carving tools chisels drilling measuring and marking

Order online today at

WWW.toolnut.co.uk

or call to order on 01424 224269



**BY MARK CASS** 

## Tapered elegance

With a new home to fit out, it came as no surprise to me to hear the words "Dad, will you make us a table?" Obviously the answer was yes. One advantage of this type of gratis job is that the deadlines can be a little bit more flexible than usual, the work generally being fitted in around other projects

ontemporary looks were called for here, and I felt that this could be a good time to try out one of my pet safety ideas – a table with no protruding corners for toddlers to bang their heads on. My design approved, it was time to head down to the timber recyclers to pick out some wood. Beech had been mentioned as a possibility - low-key appearance, goes with everything – and so I was pleased to see a few lengths among the rack of mainly joinery-shop offcuts and rejects.

#### Check the quality

Although you can get a bargain at this type of establishment (check your Yellow Pages), the quality can be variable to put it mildly, so make sure you buy more than you think you'll need. If you are making just for the pleasure of it, you can afford the extra time on careful machining to avoid the defects, unlike the busy wood machinist who finds it cheaper just to throw the dodgy bits away.

#### Don't spare the rod

The first step of any job like this should always be making a rod. A rod is nothing more than an accurate, full-size drawing of the piece. It's both a way of confirming dimensions and proportions of the design and a permanent reference for checking components as they are fashioned throughout the job.

I'll usually make use of any old offcut of thin mdf, but if you really want to push the boat out, white faced hardboard will make a very nice job of it.

#### Planning the taper

850

1115

665

1300

1220

Tapered legs always make a piece look that little bit lighter, especially if they are splayed out a touch too. That was the plan for this table, and I've found that an angle of as little as 2° past square (90°) is sufficient to lend a touch of elegance to a piece of furniture.

While pleasing to the eye, this type of design does introduce a complication or

45

65

65

25


770

45

25

25

12 25



two to the construction. No longer are the tenon shoulders square, but slanted, and not even at the angle of splay, as the taper increases this angle still further. All this becomes clear while drawing out the rod.

#### **Calling up the Domino**

It's good to have the luxury of time on a job, and to craft every joint by hand in the ongoing search for something approaching perfection. With other work stacking up around me and family pressure slowly increasing, it soon





With the cutting list drawn up, it was time for some machining of the various components

This simple taper jig will produce matching legs on the table saw





Marking out for dominos is similar to that for biscuits. Note the mark on the leg top denoting inside faces



Clean up the tapers with a sharp plane; note the tapered off-cut helping in the vice



The Festool Domino makes a super-clean mortise each time, albeit with rounded ends



With each component securely clamped, machine the rail ends for the dominos



You can now make the final angled cut on the rail, removing only the absolute minimum



This excellent WolfCraft band cramp made all the difference during the glue-up



...and the new cut edges chamfered gently with a small block plane to match the rest

became clear that this particular job didn't quite belong in this category.

Although I'm proud of my handiwork, I'm a big fan of technology, and so it was with considerable pleasure that I reached for my Festool Domino jointer. This is a terrific tool, able to cut mortises for ready-made loose tenons (the dominos) in just about any situation a woodworker could imagine.

#### Work begins

With my cutting list drawn up, it was time for a spot of machining, photo 1, and an opportunity to familiarise myself with the timber. This is when you get to spot the good pieces, the also-rans, the spares and the 'only if desperate' pieces, as the cutting list gets slowly ticked off.

Over the years I've made most of the mistakes in the woodworker's manual of 'things not to do'. So instead of steaming in and shaping the legs straight away, as I would once have done, this time I left them



With all the parts machined, apply the chamfer to the edges with a palm router



Once the frame is ready, the leg-tops can be trimmed flush with the side rails...



Plane the edges of the mdf top perfectly square, ready to take the lipping

over-length and resisted the temptation to taper them until I had carefully inspecting and marked them as follows, photo 2:

- Outside faces the best two out of four for each leg;
- Orientation I like to group them together and draw a square on the tops to show at a glance which way round they go;
- · Rail positions;
- Dominos

#### **Mortise time**

After a final check, it's time for some mortising. Here I'm going to use the Domino. While the legs are still a uniform section, cutting the mortises for the loose tenons is straightforward. As long as each component is securely clamped down, the job is done in a surprisingly short time. Eagle-eyed readers will observe that the width setting on the Domino is on 'medium' for this part of the joint, photo 3, and has been selected so as to allow for the angled ends of the rails.

#### **Tapering off**

I always cut my tapers on the table saw, but there is no reason why a similar technique can't be used on the bandsaw. First make the simplest of jigs – nothing more than an offcut with the leg profile cut out of it. To mark it out, simply measure out the desired thickness of the leg top, the overall length required, the thickness of the leg bottom, join the dots and there you are, photo 4.

Note that this jig will produce tapers on two adjacent faces of a leg. If you want to taper all four (something I have never felt the need to), then a different technique will be required. Do a spot of careful adjustment on the saw, set up the guards and the dust extraction, and away you go. As long as all your components are of the same overall dimension, you'll have no trouble producing duplicate elegant tapers.

#### Plane sailing

Accurate machining with a sharp blade should produce good clean results, but there will always be saw marks to remove, so now is the time to get that lovely freshly-sharpened plane off the shelf and to put it to good use. Check that it's set up properly on a piece of scrap, as you don't want to undo your good work by planing one of the legs out of square. In fact, just the bare minimum needs to be taken off here, photo 5, and only on the newly tapered inside faces at that.

#### Taking the rails

With the legs cleaned up and put to one side, it's time to address the rails. Although the ends will be slightly angled, I found it was best to leave the rails ever so slightly over-length, with the ends cut square. This makes the domino mortising easy, photo 6, with standard-width mortises (Domino setting: small) being employed for this stage, giving a pleasingly snug fit.

By referring to the hallowed rod, the correct angle can be measured - or simply 'copied' with a sliding bevel - and transferred to a chop saw.

A final check of the lengths required and the rail ends can now be cut to the final angle, photo 7. By trimming off just the bare minimum, the domino joint will go together cleanly.

#### Adding the chamfers

One of the key features of this design is the 2mm chamfer on every edge, and, while this is not a particularly taxing task with a hand plane, there's something about the perfect regularity of a machined edge which led me to employ my nifty little Bosch palm

router and a chamfer cutter, photo 8. It ensures rapid progress and a fairly low risk of a routing disaster.

#### Framing up

With the legs and rails machined, jointed and cleaned up, it's time for the assembly. I've learnt the hard way just how important it is to have a dry run at this. Take the time to put all the joints together and prepare all the cramps that will be required.

When you're satisfied that everything is going to fit, go ahead and start the glue-up. Although there is a strong case for using polyurethane glue in this situation - for what is effectively a mortise-and-tenon joint – I much prefer the more sedate pace of work afforded by pva glues.

#### **Cramping square**

The combination of a WolfCraft band cramp and a variety of F and sash cramps enabled me to get the table frame together with little difficulty - something that's not always possible with an angled or tapering workpiece, photo 9.

Before stepping back with satisfaction, it's essential to check for square and winding, and to make any necessary adjustments while the glue is still soft.

The next day it was time to trim the tops of the legs, **photo 10**, chamfer the newly created edges by hand, photo 11, and give the whole frame a general clean-up something's that much easier to do before the top has been fixed on.

#### **Preparing the top**

With the table top needing to be stable any shrinkage would be immediately apparent with this design - I decided to lip some 25mm thick mdf and to get it veneered at my local veneer presser. It's a fairly straightforward job, involving some accurate measurement and truing up the board edges, photo 12.

I always take the precaution of sealing the edges of raw mdf with diluted pva adhesive to ensure a better 'take' when gluing on the edging material, photo 13.

I mitred the lipping carefully, photo 14, then glued and taped it to the squared-up and still sharp edges of the board, photo 15. Once that was cleaned up, it was down to Steve's place and his hot veneer press.

#### Bringing it all together

When the top was ready, I was at last able to offer it up to the base in a variety of ways to see how it would look best. With the orientation decided, some careful handplaning matched the edges with the slope



Seal the raw mdf edges with dilute pva adhesive to help counteract their natural absorbency



...and glue and tape the four lengths into place along the board edges



Mitre the lengths of edge trim carefully to fit round the perimeter of the top



Match the edges of the table top with the chamfer on the outer corners of the legs



the frame with screws driven up through some hand-cut pocket holes into the underside of the top.

#### The big finish


It was now time to apply the finish. The table was sanded to 240 grit on the frame and 320 grit on the top. When not left in its natural state, beech is rarely given much more than a factory-applied spray lacquer coat. With its uniform and fairly bland appearance, plus an irregular micro-grain structure designed to defy the French polisher's skills, I knew I had my work cut out to get it looking half-way decent.

I started with a coat of grain sealer (Behlen's Pre-Stain), to give myself a better chance, then painstakingly applied sundry coats of colour and varnish until I was almost satisfied. With careful rubbing-down between coats, the end result was finally reached... I only had to re-do it twice!

All's well that ends well, however, and the table was delivered in good shape and immediately pressed into active service. Another satisfied customer...









BY ALAN HOLTHAM

## Challenge bowl

Last month I took a look at the spalting process and the way it turns ordinary wood into a material with dramatic colour and figuring that turners love. This month I'll show you some of the techniques you need to master in order to work it successfully

> The term 'spalted' is used to describe wood in the first stages of rot, a state that causes it to develop a totally fascinating variety of colours and patterns not normally characteristic of that timber. These patterns can be quite magnificent, with zones of different colours separated by fine black lines in a highly ornate pattern. The extent of the patterning varies enormously, depending on the number of different fungal attacks that have infected the wood. One of the best ways to exploit this natural phenomenon is to cut the wood into blanks and then turn it on the lathe. I've chosen a beech blank, photo 1, to illustrate some of the problems of turning spalted timber.


#### **Potential problems**

For a start, it can sometimes be a bit tricky to season spalted wood. If it's evenly infected and discoloured, then all the stresses seem to have been equalised. But if the spalting is more varied, or has occurred in definite planes, then splits will often develop along the boundaries, with the stresses obviously now overcoming the weakened timber.

There are no specific techniques involved when working spalted timber, other than keeping your tools sharp and being patient. The continual tearing of soft areas causes frustration, particularly when a fine finishing cut leaves a smooth surface but with a couple of deep tears. Trying to fill these just highlights the problem, so there's often no alternative to lots of sanding. The only snag to this is that the different densities sand out unevenly, the soft areas often getting quite



This spalted beech blank had some promising surface figuring



Problems also occur when a soft area adjoins a sound, harder one



The best tool to use for shaping small bowls is a bowl gouge sharpened to 45°



You'll get clean cuts on hard patches and jagged tears on softer ones

hollow compared to the harder surrounding timber. To even this out I find it's best to use a powered sanding pad, which spreads the wear more evenly.

#### **Health issues**

The dust from spalted wood is often cited as a particular health hazard. I have seen no scientific evidence that the dust is any




Even with the sharpest tools, little patches can be plucked out to quite a depth



If the blank appears soft, use a faceplate and attach it with plenty of big screws



The wood is fragile, so proceed by taking initial cuts as gently as possible



Try turning the gouge upside down to produce a fine shearing cut

more injurious than dust from normal wood. I do know, however, that they are both potentially hazardous, so I always wear some personal protection in the form of an air-fed helmet as well as running my air cleaner when I'm turning spalted wood.

Although it has developed through the initial phases of rotting, spalted wood is quite stable once it has been dried. With

no moisture in the wood the rot can't survive, and the timber won't deteriorate any further unless it gets wet again.

#### **Uneven textures**

The downside of spalting is that as the wood starts to decay, it becomes softer. Generally speaking the heavier the spalting, the softer and more difficult the wood is to cut cleanly. The main problem is that little patches are plucked out to quite a depth, photo 2, no matter how sharp your tools are. However, there are a few tips that can minimise some of these difficulties

A more awkward situation occurs where there is a distinctly soft area next to a much sounder section, photo 3. Although the effect of this may be visually quite dramatic, it is much more difficult to work, as the turning tools tend to bounce when they encounter the different densities of wood as the blank spins, and you end up with a very uneven surface. The problem becomes even more acute when you start sanding the wood.

#### The chosen one

Nevertheless, I've selected just such a bowl blank to try to illustrate the turning process. Sadly, although it appeared to be well spalted, closer inspection revealed that the patterning was all on one surface and the underside was relatively plain. I was then faced with the dilemma of which way to mount it. Making the well-marked side the top will result in most of it being turned away. In the end I settled on putting the better spalting to the underside in the hope that I could turn down into it in the base of the finished bowl.

#### Beginning to turn

The first problem is physically mounting the blank on the lathe, particularly if the wood is very soft. If there's a reasonably sound section, you can use a large woodscrew chuck and rely on just the one fixing. If it's softer, use a faceplate with plenty of big screws to get an adequate hold, photo 4.

You can then start the turning process. Remember that the internal density can vary tremendously, so keep the lathe speed down to minimize any vibration. I've found that the best tool to use for these small bowls is a 1/4in bowl gouge with the bevel sharpened to about 45°, photo 5. Bear in mind the fragile nature of the wood and make the cuts as gentle as possible, photo 6. This is the key to working spalted

wood. You simply can't lay into it with heavy cuts as you can with sound timber. Slow and easy are the watchwords here. Above all, keep the pressure of the tool down on the toolrest, rather than on the wood, to minimise bouncing.

#### **Mixed results**

No matter how sharp your gouge is, the finish will be extremely variable, with clean cuts on the harder patches and jagged tears on the soft ones, **photo 7**. This blank revealed a couple of quite major splits along the zone boundaries too. I reduced its diameter to get rid of some of the splits, but left the rest to be dealt with later on.

As you get near to the finished profile, start taking finer and finer cuts to reduce the tearing damage. Re-sharpen the tool regularly as well; it's amazing just how abrasive this very soft timber seems to be, and anything less than a razor-sharp edge will tear rather than cut.

Another old trick that's worth trying is to turn the gouge almost upside down to produce a very fine shearing cut that slices cleanly through all but the softest patches, **photo 8**. However, you have to accept that you're not going to get a perfect surface straight off the gouge with this wood. Just do the best you can with the last few finishing cuts.

#### Getting a grip

I prefer to use a recess for re-chucking, as I find it more secure than gripping onto a spigot which can be rather unpredictable in density. Use a narrow parting tool to mark out the recess, and try to make the diameter as close as possible to the true diameter of the chuck jaws to maximize the amount of grip, **photo 9**. If the material is well spalted, allow some extra depth to the recess to compensate for the weaker material.

Even a sharp parting tool will rag the edges of the recess, **photo 10**, but you can clean these up with a slicing cut made holding the skew on its back, **photo 11**. The waste within the recess can then be cut away with a steeply bevelled spindle gouge using a pull cut, **photo 12**. Aim to end up with the recess as clean as possible off the tool, and with a sharp corner to maximise the chuck's grip, **photo 13**.

#### Glue and sand

Once you've finished shaping the outer profile of your blank, your next job is to check it all over carefully for cracks and severe tears. The best way to stabilise these is to flood them with very thin superglue,



Cut the chucking recess to match the diameter of your chuck jaws



...but you can clean these up with a light slicing cut made with a skew chisel



Aim to end up with a square-edged recess that will maximise the chuck's grip

Spalted wood dust is nasty stuff, so fix up an extraction pipe nearby



**photo 14**, letting it soak well into the defects. This dries hard in a few seconds, hardening up those very soft patches and sealing any cracks.

You can then start to sand the surface carefully, but avoid overdoing it or you'll wear away the softer areas more than the harder ones and the surface will become very irregular. Power sanding is best as it



Even a sharp parting tool will leave somewhat ragged edges to the recess...



Cut away the waste in the recess with a steeply bevelled spindle gouge



them with very thin superglue



To minimise black dust stains, rub in some thinned-down sanding sealer

seems to spread the wear more evenly.

Some form of dust extraction as close as possible to the surface you're sanding is essential here, as the spalted dust is particularly offensive. I've found that the best way to get the extraction pipe near to the action is to bolt a large spring clip on the end, which can then be clamped onto the bed bars just where you need it. It's very



Repeat the sanding and sealing process several times to get a clean surface



After sealing the outside of the bowl, apply some pastewax with a small pad of steel wool



Start turning out the inside of the bowl with light, gentle cuts...



I charred the bowl's rim lightly for contrast by holding a block of hardwood against it

satisfying to see the dust being sucked straight down into the pipe, photo 15.

#### **Keeping it clean**

The other problem with sanding spalted wood is that a lot of the black dust from the zone boundaries gets deposited in the torn grain of the soft light-coloured areas, giving it a very dirty appearance. To overcome this,



In sanding the bowl, I inadvertently rounded over the edges of the chuck recess!



Make sure you reverse the work back onto the chuck perfectly square



...and don't be tempted to cut the walls of the bowl too thin; they may crack



Wax the interior once more and buff it up to a soft natural sheen with a soft cloth

do a little sanding, stop the lathe and rub in a coat of thinned-down cellulose sanding sealer, photo 16. This dries in no time and you can then sand again, but now the black dust is reduced and the grain is filled a bit. Keep repeating this procedure until you get the finish you want. You may have to do it five or six times to get a smooth and clean surface, photo 17.

During the power sanding I accidentally rounded over the internal edge of the chucking recess, photo 18, which makes a nonsense of what I said earlier about maximising the grip. However, I rather liked the effect it created, so I decided to risk carrying on rather than turning it again. Fingers crossed!

#### **Outside finish**

With spalted timber I nearly always finish the surface with pastewax, so after building up a good basecoat on the outside of the bowl with several coats of sanding sealer, I applied the wax with a small pad of 0000-grade steel wool, photo 19. I find that oil finishes tend to go very patchy on spalted wood, even after so much sealing, and the high gloss finishes tend to look inappropriate anyway with such extreme decorative figuring.

#### **Back to the turning**

Take care when you reverse the work back onto the chuck that you get it dead square, photo 20, particularly if like me you have reduced the recess depth. Go steady when turning out the inside of the bowl, photo 21, just taking gentle cuts until you get a feel for how even the timber is. Don't be tempted to try for over-thin walls, photo 22. Spalted timber has no real strength, so it's better to leave the walls a bit fuller, and to keep stopping the lathe to douse soft patches with superglue as you get near to the final thickness you want.

#### A minor disappointment

As I'd feared, the finished bowl revealed two coloured areas with a disappointingly small amount of spalting. So, in an effort to try to tie these two contrasting areas together, I charred the rim lightly by holding a piece of hardwood against it as it was spinning, photo 23. I'm still not sure if this works or not! Finally, repeat the sanding sealer procedure on the inside; then wax it again, photo 24, buffing the wood to a natural sheen with a soft cloth.

After much frustrating, time-consuming and dusty work you should now have a beautifully finished piece of spalted timber. My finished piece was a little disappointing, but every day is a learning day!

The bonus is that you don't need many tools to turn spalted wood, as you can see in the main picture on page 57. I used just a 1/4in bowl gouge for most of this project, with a little help from a 1/8 in parting tool, a 3/4in skew and a 1/4in spindle gouge. A few simple tools really do go a long way!



### SKELTON SAWS

AN ENGLISH SAW MADE IN THE ENGLISH COUNTRYSIDE

PRECISION

CRAFTSMANSHIP

DESIGN





UNIQUE

+ DETAIL + DEDICATION + BESPOKE + TRADITION

SUPERIOR HANDMADE SAWS OF PRECISION THAT HAVE BEEN CRAFTED BY SHANE SKELTON IN THE OLD TRADITION

TELEPHONE NUMBER: 01723 448202 EMAIL: SKELTONSAWS@GMAIL.COM

WEBSITE: WWW.SKELTONSAWS.CO.UK 📙 THE SAW MAKER'S WIFE @SKELTON SAWS



#### Sussex Oak & Restoration Materials

The one stop shop for all your oak needs



Large stocks of fresh sawn and kiln dried oak PAR and mouldings made to order

Kiln Dried-1" from £32 a cubic foot 2" from £39 a cubic foot 3" from £49 a cubic foot

Fresh Sawn-Lengths up to 10m Sections up to 500mm x 500mm Price from £21 a cubic foot

Small orders/hobbyists welcome, self selection available

Unit 1, New Road Newhaven East Sussex BN9 OHE

Call 01273 517013 or visit www.oakandreclaim.com



### Woodworker subscription order form

#### DIRECT DEBIT SUBSCRIPTIONS (UK ONLY)

	s, I would like to subscribe to The Woodworker
	Print + Digital: £10.50 every 3 months  VE 34% on shop price + SAVE 75% on Digital Download + FREE GIFT)
	Print Subscription: £8.50 every 3 months (SAVE 34% on shop price +
	EE GIFT)  OUR DETAILS MUST BE COMPLETED
IV	/Mrs/Miss/MsInitialSurname
Д	ddress
	stcode
	MobileMobile
Е	nail D.O.B
I WOULD LIKE TO SEND A GIFT TO:	
Ν	/Mrs/Miss/MsInitialSurname
	ddress
	stcode Country
INSTRUCTIONS TO YOUR BANK/BUILDING SOCIETY	
C	iginator's reference 422562
	ame of bank
	ddress of bank
	Postcode
	count holder
S	gnature Date
_	
S	ort code Account number
th	structions to your bank or building society: Please pay MyTimeMedia Ltd. Direct Debits from account detailed in this instruction subject to the safeguards assured by the Direct Debit Guarantee. aderstand that this instruction may remain with MyTimeMedia Ltd and if so, details will be passed ctronically to my bank/building society.
F	eference Number (official use only)
	ease note that banks and building societies may not accept Direct Debit instructions from me types of account.
	CARD PAYMENTS & OVERSEAS
Yes, I would like to subscribe to <i>The Woodworker</i> , for 1 year (13 issues) with a one-off payment  UK ONLY:  Print + Digital: £47.50 (SAVE 23% on shop price + SAVE 75% on Digital Download + FREE GIFT)  Print: £39.50 (SAVE 23% ROW Print: £59.00	
PAYMENT DETAILS	
Р	Postal Order/Cheque Visa/MasterCard Maestro ease make cheques payable to MyTimeMedia Ltd and write code V703 on the back
	ardholder's name
C	ard no: (Maestro)
\/	lid from Expiry date
	Posts

TERMS & CONDITIONS: Offer ends 13th March 2015. MyTimeMedia Ltd & The Woodworker may contact you with information about our other products and services. If you DO NOT wish to be contacted by MyTimeMedia Ltd & The Woodworker please tick here: \(\text{\text{\text{}}}\) Email \(\text{\text{\text{}}}\) Post \(\text{\text{\text{}}}\) Phone. If you DO NOT wish to be contacted by carefully chosen 3rd parties, please tick here: \(\text{\text{\text{}}}\) Post \(\text{\text{\text{}}}\) Phone. If you wish to be contacted by email by carefully chosen 3rd parties, please tick here: \(\text{\text{\text{}}}\) Email

POST THIS FORM TO: THE WOODWORKER SUBSCRIPTIONS, TOWER HOUSE, SOVEREIGN PARK, MARKET HARBOROUGH, LEICS LE16 9EF.



#### **PRINT + DIGITAL SUBSCRIPTION**

Free Hitachi 102pc Drill & Driver Bit Set\*

myhobbystore.co.uk

13 Issues delivered to your door
Save up to 34% off the shop price
Download each new issue to your device
A 75% discount on your Digital subscription
Access your subscription on multiple devices
Access to the Online Archive dating back
to January 2007
Exclusive discount on all orders at



#### PRINT SUBSCRIPTION

Free Hitachi 102pc Drill & Driver Bit Set\*
13 Issues delivered to your door
Save up to 34% off the shop price
Exclusive discount on all orders at myhobbystore.co.uk

### SUBSCRIBE TODAY

## Receive a FREE

## Hitachi 102pc Drill & Driver Bit Set

when you subscribe today



- 20 x HSS black oxide drill bits 1x5, 1.5x5, 2x4, 3, 3.5, 4, 4.5, 5
- 4 x Masonry bits carbide tipped 3, 4, 5 and 6mm.
- 1 x Countersink insert bit 12.7mm.

AND MASONRY.

- 3 x Phillips 50mm insert bits PH1, PH2 and PH3.
- 3 x Pozidriv 50mm insert bits PZ1, PZ2 and PZ3.
- 2 x Torx 50mm insert bits T20 and T25.
- 19 x Phillips 25mm insert bits PHOx3. PH1x4, PH2x8 and PH3x4.

- 11 x Pozidriv 25mm insert bits PZ1x3, PZ2x5 and PZ3x3.
- **14 x Slotted 25mm insert bits** 3 x3, 5 x3, 6 x4 and 6.5mm x4.
- 3 x Square 25mm insert bits S1, S2 and S3.
- **14 x Torx 25mm insert bits** T10 x2, T15 x2, T20 x 2, T25 x2, T27 x2, T30 x 2 and T40 x2.
- **7 x Hex 25mm insert bits** 1.5, 2, 2.5, 3, 4, 5 and 6mm.
- 1 x Magnetic insert bit holder 60mm chrome plated.

TERMS & CONDITIONS: Offer ends 13th March 2015. \*Gift for UK subscribers only, while stocks last

SUBSCRIBE SECURELY ONLINE

(h) www.subscription.co.uk/twwl/V703

CALL OUR ORDER LINE

0844 543 8200



FFX have yet again brought together all the biggest manufacturers to give you the best hands on tool show for the professional and DIYer.

Building on the success of our previous shows at Bluewater, 2015 is set to be twice the size having moved to the brand new Maidstone Exhibition Hall in Kent. Set in approximately 50,000 ft² of first-rate indoor exhibition space (that's large enough for over 200 lorries!), you'll be able to enjoy live tool demonstrations from industry experts, see new product releases, and have a chance to compete in exclusive competitions from our powerhouse brands.

WANT TO MISS OUT ON THESE DEALS!

#### **EXHIBITORS**

In 2015 we've outdone ourselves by playing host to the biggest international manufacturers of tools, accessories and equipment.

Over 100 major brands will be exhibiting, including Festool, Bosch, DeWalt, Milwaukee, Stanley (we can't list them all, but everyone that matters will be there!) and with Makita celebrating their 100-year anniversary this event promises to be like no other.

For the complete exhibitor list and full details please visit ffx.co.uk

#### **FACILITIES**

The Kent Event Centre is ideally situated between two major motorways and is only a 50 minute trip by car or train from central London. The main Maidstone Exhibition Hall provides  $32,000 \text{ft}^2$  of first-rate indoor exhibition space – fully ventilated with a permanent walkway to the Hendry Pavilion.

With free parking, food stands and disabled toilet access, everything is provided at ground level to make sure all your needs are catered for.



#### **EASY ACCESS**

Conveniently located between the M2 and the M20 in Kent.

#### FREE ENTRY

There will be free entry all day every day to our show – more cash for you to buy tools!

#### **FREE PARKING**

Free parking on site for cars and coaches, there is capacity for up to 30,000 cars so rest assured you will be able to park on the day.

There will be car park attendants to offer assistance should you have any additional needs.

#### CATERING

There will be hot and cold beverages at various stations throughout the showground with the main cafeteria being located in the Astor pavilion which is adjacent to the main exhibition hall.

#### **DISABLED ACCESS**

There is disabled access throughout the exhibition halls and the show is located on the ground floor, so all of the events are fully accessible to people with reduced mobility.

Download your FREE ticket now at FFX.CO.UK and we'll reward you with a special discount booklet worth hundreds of pounds, a free bacon roll, and entry into an exclusive prize draw - all available to collect when you arrive.\*

#### ABOUT FFX

FFX began trading in 2003 from a small store in Folkestone and has never looked back. By 2010 we were eBay's largest supplier of tools and our new web site ffx.co.uk sprung into life in 2011. In 2013 we hosted our first ever tool show. Every record was smashed last year with the opening of branches throughout the South East and exponential growth on eBay and ffx.co.uk, which is why this autumn will see the opening of our huge new distribution centre.

We are now proud to be one of the UK's largest independent suppliers of high-quality tools, fixings and building supplies with hundreds of thousands of loyal customers across the country. But no matter how big we grow we promise our standards will never change - we will always offer the best possible prices, unrivalled customer service and quick delivery.

We look forward to seeing you at our show!

\*Make sure to visit ffx.co.uk for full details

27th Feb | 28th Feb | 1st March 2015 Kent Event Centre, Maidstone, Kent





## Who's the fairest?

Hand mirrors are relatively simple to make and incorporate both faceplate and spindle turning. The mirrors can be bought online, or you could ask your local glass supply shop to cut one for you

> hile the turning is simple, it's important to choose your wood carefully. We all know that wood will move due to changes in the relative humidity of its surroundings, and we also know that glass is inflexible and fragile. Therefore dry wood is essential for the mirror frame. If possible choose quartersawn wood - that is wood that has been cut so the growth rings are at approximately 90°

to the sawn surface. Quarter-sawn timber is more stable and far less likely to cup.

Any species of timber can be used, but keep in mind the weight of the overall piece. It's best not to choose very heavy species. I used brown oak.

The wood for the handle should have the grain running parallel to its length. Avoid timber where the grain emerges from the side of the blank, photo 1. This short grain,

### TURNING | Hand mirror



Avoid this type of short grain. The grain should run the entire length of the handle



Stick the frame blank to a scrap wood disc screwed to a faceplate



True up the top surface using a pull cut with a fingernail profile gouge



Then true up the edge using the same gouge, but this time with a push cut



Mark the diameter of the mirror on the face of the piece with a pencil



Use a parting tool to cut a groove just to the right of your pencil mark



Use a square-ended scraper to ensure that the bottom of the recess is flat

as it's known, will considerably reduce the strength of the handle.

I used a 145mm diameter mirror and my frame was 190mm across. The handle started as a 25mm square 210mm long, finishing at just under 200mm.

#### **Preparing the frame**

Screw a 100mm diameter disc of scrap wood or mdf to a faceplate and glue the blank to it, photo 2. True up the top surface using a pull cut with a fingernail profile gouge, photo 3. Then true up the edge of the blank using the same gouge, but this time use a push cut with the shaving coming off the tip of the tool, photo 4.

Mark the diameter of the mirror on the face of the piece, photo 5 and use a parting tool to cut a groove fractionally to the right of this mark, photo 6. Now remove the waste wood inside the groove to make the recess for the mirror. You can continue to cut successive grooves next to each other with the parting tool, but it's quicker to use a bowl gouge.

#### **Checking the recess**

When the bulk of waste material has been removed, use a square-ended scraper to ensure that the bottom of the recess is flat, photo 7. Now cut a smaller dovetailed recess in the middle to fit the jaws of your chuck, photo 8. Check for flatness using a straightedge, photo 9; I'm using a small cabinet scraper here.

The mirror needs to be a tight fit in the recess, but this means that any movement of the wood could cause the mirror to crack. To reduce this problem I like to undercut the bottom of the recess a little and I do this using a spindle gouge, ground to a long point. Keep the tool well over on its side and rub the bevel of the tool on the bottom of the recess. The tip of the tool makes the cut, photo 10.

Now shape the rim. I opted for a very simple continuous curve which I cut with a



Cut a smaller dovetailed recess in the middle to fit the jaws of your chuck



Check for flatness with a straightedge; I used a small cabinet scraper

spindle gouge, **photo 11**. Continue the curve to round over the top of the recess. Here I used the spindle gouge on its side with a pull cut, **photo 12**.

#### Finishing the back

With the rim finished, remove the piece from the glue chuck and mount it on your four-jaw chuck so you can complete the back. I cut a convex shape, again using a pull cut, and blended it into the rolled rim. For decoration I cut a few beads using a skew chisel, **photo 13**, and then slightly concaved the very middle of the back, **photo 14**, to prevent the mirror from rocking on the dressing table.

Sand the piece down to 400 grit and apply the finish of your choice. I like to use an acrylic lacquer of these pieces because it's hard-wearing. A couple of coats sprayed on and gently knocked back with wire wool between coats will do the trick, **photo 15**.

#### **Drilling the frame**

**Photo 16** shows a simple jig that I use to hold circular pieces vertically for drilling on my drill press. It's simply a piece of mdf glued and screwed at 90° to an mdf base, with two pieces of softwood glued to the upright at 45° to the base. It's essential to clamp the workpiece to the jig and also the jig to the drill's table.

I first made a small flat on the edge of the mirror frame by drilling with a 16mm Forstner bit. Then I drilled a 10mm hole in the centre of this flat to receive the handle spigot.

#### **Turning the handle**

Mount the handle base between centres and turn it to a cylinder with a spindle roughing gouge, **photo 17**. Wherever possible I like to work from the tailstock end towards the headstock when doing spindle work, **photo 18**. You could, of course, use callipers to check the diameter as you work, but on this occasion I used a handy 10mm open-ended spanner.



Undercut the edge of the recess a little to allow for movement of the wood



Continue the curve to round over the top of the recess using a pull cut



Now shape the rim. I opted for a simple curve cut with a spindle gouge



Cut a few decorative beads at the centre using a skew chisel as a scraper



Then slightly dish the middle to stop the mirror rocking when it's put down on the dressing table


### TURNING | Hand mirror



Turn the lathe at a very low speed or by hand when spraying on a lacquer finish

Mount the handle base between centres

and turn it to a cylinder



This simple home-made jig holds the workpiece truly vertical for precise edge drilling



Starting at the tailstock end of the piece, turn a 10mm diameter tenon

You can turn the handle to whatever shape you like, but I opted for simplicity. I first turned a few beads next to the tenon, photo 19, and then cut a flowing cove, photo 20. Finally I rounded over the end of the handle and turned a small ball end, photo 21. Before parting off the ball, I sanded and lacquered the piece. Then all that remains is to turn or saw away the waste wood by the ball and sand away the last little stub by hand.

#### **Assembly time**

I glued the handle spigot into the frame using pva adhesive, and cramped it in place until the glue had dried. There are specialist glues for mirrors on the market, such as Mirror Mate, that are said not to attack the mirror backing. However, I've always used a clear standard silicone mastic and have never had any problems with it. Apply about six small dabs of mastic in the recess and insert the mirror, press it down gently so it's level with the rim all round, and then let the mastic cure.

On reflection, this has turned out to be a very attractive little project!



Begin shaping the handle with a few decorative beads next to the tenon



Then create a smoothly flowing curve along the rest of the handle



## BUY ONE, GET ONE FREE!

## Why not treat yourself or a friend with this special offer?

If you love hobbies then this is a great offer for you or someone you love.

Treat yourself to any of the titles below and choose another one absolutely free!\*

Our 'love' series of craft specials are one-off magazines bringing you the best of all your favourite crafts, featuring easy-to-make projects, tutorials and great inspirational ideas. These essential guides take you through the basics to the finished product, giving you advice and tips along the way from all the experts.

Don't forget you can download our free patterns too for our projects in all our love series online today at www.myhobbystore.co.uk/templates













Or why not treat yourself to one of our historical or practical project titles?











Online: www.myhobbystore.co.uk/BOGOF15

By Phone: 0844 848 8822 (Phone lines open Mon-Fri 9am – 4.30pm) quoting BOGOF15 telling our customer services team which issues you would like.
\*Cheapest issue free. Limited stock so don't miss out!



LSHOW.CO



### STANDS STAFFED BY THE MAJOR BRANDS INCLUDING:






























































**KEMPTON PARK RACECOURSE • SUNBURY-ON-THAMES • TW16 5AO** 

D&M TOOLS, TWICKENHAM • 020 8892 3813 • WWW.DM-TOOLS.CO.UK

first came across ornamental turning many years ago when I was scanning some old woodworking magazines in a library one afternoon. The author of an article in one of the magazines was the owner of a Holtzapffel lathe. Together with describing this, he added some images of work that he had produced.


#### **Original inspiration**

In addition, and much more important for me, was a short discourse on a book - Le Manuel du Tourneur by L E Bergeron together with copies of some of the plates. The shapes that Bergeron had drawn astounded me, as they implied that it was possible to produce such shapes on the lathe that he illustrated.

It had never occurred to me that such work was possible on a one-off basis. As an experienced and qualified woodworking machinist, I was familiar with a wide range of machines designed to mass-produce complex wooden shapes, but I had no idea it was possible for a lathe to produce individual pieces shown in these albeit schematic drawings. The idea that one could produce three-dimensional work on a wood turning lathe set me on a course that has lasted many years.

#### Three good reasons

A picture is worth a thousand words, as the old saying goes. It's true; a tremendous amount of useful information could be gathered from Bergeron's drawings.



## Turning the impossible

Most turned work is essentially two-dimensional; the shape you see is just a silhouette. But what if you could create something more complex and truly three-dimensional? Rod Tallack can

However, for me one thing was becoming clear: this was not a machine to produce work rapidly. I was beginning to understand why three-dimensional woodturning was not a familiar everyday practice. There were at least three reasons I could see:

- the sheer number of complicated mechanisms involved;
- the cost involved in building these mechanisms;
- the amount of time it would take to produce anything of interest on the lathe as illustrated.

What I had in mind was a lathe that could


produce three-dimensional woodturning of a high standard but without the intricate detail, and in a reasonable time. This brings me to the point of this article; how the design of the lathe evolved that produced the work illustrated.

#### The big end

The headstock has to be central to any lathe design, and was the logical place to begin. The primary requirements are mass and rigidity, together with provision for a rotary-linear bearing for the main shaft/ mandrel. Steel and cast iron would provide the necessary mass; the choice of bearing would be critical to the design.

Some research located a firm that manufactures a range of suitable bearings, and I selected two that might meet my requirements. However, it was down to me to design the mandrel. The bearing people would machine it to my dimensions and then harden it to suit the chosen bearings.

The length of the mandrel was the next decision. Bergeron's plates for the linear action showed a leaf spring controlling the movement via a rear-mounted cam; the alternative would have to be a coil spring



Bergeron's original drawings were the inspiration for my first attempts at making a sculpture turning lathe and creating work like the pieces he illustrated

mounted concentrically on the mandrel. After a discussion with a spring maker, I made an intelligent guess as to the strength required and the expert decided the gauge.

I now had enough information to design the headstock. I made a suitable wooden pattern, had the headstock cast in iron and took it to a local engineer for machining. Fortunately, at the time (some 20 years ago) there was an iron foundry and engineering works nearby, but they've all vanished now and the area is a housing estate!

#### Creating the bed

This was to prove quite straightforward. A trip to the local scrapyard produced two 5ft lengths of steel channel with a 6 x 3in cross-section. These were part bolted and part welded together, giving a good strong base on which to mount everything. It did require that the top face be flat, and a local engineer did this for me. Then, using some slotted angle iron framing, I made up a leg assembly to carry the bed.

#### The difficult part

The next challenge was to work out how to achieve anything other than circular movement when rotating the work on a common axis. The wood being machined needs to move horizontally while at the same time rotating; in other words the workpiece must cross the lathe bed and

rotate at the same time. I returned to Bergeron's plates for inspiration.

I ignored the mechanisms using complex gear trains as being much too intricate and costly. However, there was an illustration showing a series of cams mounted on the mandrel, with a fixed cam follower selecting a particular cam. This caused the mandrel together with the headstock to move horizontally across the lathe as it rotated.

To achieve this, the headstock had to be pivoted roughly level with the lathe bed, meaning that the movement was part of an arc (although the amount of curvature would be so small as to be unnoticeable). The idea of a selection of different cams as opposed to gear trains seemed the way to go, and it was this idea that initiated the conception of a primary faceplate that could be controlled by cams – in other words, an intermediate faceplate moving horizontally across the lathe bed while rotating.

#### The primary faceplate

The initial design for this unit consisted of a disc mounted on the end of the mandrel. Radiating from this disc were eight spring-loaded pins, which engaged with an outer drum. The function of the pins was to keep the outer drum concentric with the disc. The drum had front and back plates screwed to it, enclosing the disc and keeping the two constant in one plane but



Image A shows a piece of laburnum 180mm square and 50mm high. Along with the square shape, the effect of the end movement of the rear cam is evident with the sloping top of the piece.



Image B is a piece of sapele 210mm square and 70mm high. This shows that the effect of the cam can be cancelled, with the lathe returning to circular cutting.



Image C features a piece of mahogany that has been shaped using random settings together with a seven-sided cam, also utilising the compound slide facility on the primary faceplate.

allowing limited free movement in the other two planes. On the front plate, a screw thread had to be built in to facilitate the mounting of a conventional faceplate to carry the work.

Various cams were made from plywood and bolted to the drum. The assembled unit, when rotating, would be controlled by a fixed cam follower set at the same height as the cutting tool, thereby generating the shape of the cam onto the work.

I made wooden patterns for the disc and the drum and had them cast in aluminium. The front and back plates were fashioned from mild steel. It seemed a good idea at this time to fit the front plate with a compound slide-way, enabling the main faceplate to be re-positioned in relation to everything else.

Incidentally, a couple of tool rests would be necessary, so wooden patterns were cut and these were cast in iron at the same time as the headstock.

#### The first trials


With all the parts made and assembled, the Mark 1 Sculpture Turning Lathe was set for its first trials, which sadly were not at all successful. The shape of the cam proved too ambitious; there were too many changes in the shape, and the rate of change from the mean circle was too rapid. No problem: cut another cam. With a revised cam fitted the first piece of turning was completed. It wasn't brilliant, but it did prove this was the way to go.

The next problem was rather more serious. The primary faceplate didn't work as anticipated. The fault lay with the springs; essentially they were too short for the job. The solution was one of necessary expediency, a question of making do. From a pivot point bolted to the side of the lathe bed I fitted a spring-loaded arm carrying two ball races/ball journals that were positioned to apply pressure to the outside of the primary faceplate drum assembly. The spring was good and long, a cannibalised front fork from a motorbike.

After several more trials another problem arose. The wooden cams were not up to the job as they couldn't stand the buffeting. Aluminium was chosen as being the next best material, so I made wooden patterns of some cams for casting in aluminium.

# More trials

After a variety of modifications and further trials, using hand-held chisels proved unsatisfactory. The workpiece was moving back and forth across the lathe bed; also, the work was accelerating and decelerating



These early engineering drawings illustrate some of the components of the Mark 1 lathe

as the cam passed the cam follower. However long a handle was fitted to a chisel, it was very difficult to maintain any sort of control. It became necessary to replace the chisels with a powered cutter.

A trip to the breaker's yard produced a parting-off slide unit from a capstan lathe. This was adapted to carry a router and fitted onto the lathe bed. The router, fitted with a

suitable cutter, proved much more satisfactory. I now had a working lathe on which three-dimensional turning could at last be fashioned.

# A helping hand

Shortly after this stage of development, a friend of one of my sons came and asked if he could gain some experience using the

# WHAT SCULPTURE TURNING CAN CREATE



This section of oak had been in store for a long time. The shrinkage cracks were filled with a brass/resin mix, and both end and side cams were used to create the shape



Odd pieces of ash and laburnum were glued together to produce this bowl, using the same cams as before





Both side and end cams were used on this piece of yew. In an effort to create a bit more interest, both cams were then cancelled and the lathe was returned to circular work



This pentagonal cherry bowl is mounted on a circular mahogany base. The unusual profile at the top was created by using an end cam when cutting on the outside but removing it when cutting the inside

A gift of some iroko was appreciated, but the sizes required a lot of cutting and gluing to create a piece for turning. The plainness of the wood needed lifting, hence the introduction of the ash and aluminium inserts

lathe. This was agreeable, as he did not want any payment, other than having half of whatever he made that was in any way interesting. It meant I could get on with earning my living while still overseeing the progress of the lathe. Images A, B and C on page 72 show three of the pieces he made.

# Creating the Mark 2 lathe

Over the years my own business operation expanded. I was able to take on extra workers, so I had some free time. With the experience I had, it was time to think about a new lathe.

The design of the Mark 1 lathe was influenced by Bergeron's drawings, which with hindsight was not such a good idea. It was back to the drawing board... again.

The lathe that is the subject of this article was developed to produce woodturning that is not only different to either traditional woodturning or ornamental turning, but also creates turnings that cannot be done by either group. To my mind, there was a gap between ornamental and traditional turning to be filled, and the rationale behind this exercise was to fill that gap.

I think there is a need to introduce a facility to turn in three dimensions and create a new challenge for the artist turner. Whether a machine manufacturer would invest in adapting the lathe for a small production run remains to be seen.

The Mark 2 lathe (shown below) could really do with redesigning, but the facilities and time required are no longer available to me. Nevertheless the lathe, as it is, is a challenging piece of equipment to use and serves its purpose in keeping me occupied in my retirement.

For recent developments in sculpture turning work, please take a look at the site www.sculptureturnery.co.uk



The Mark 2 lathe, finshed and ready to take its place alongside any other machine; it does what it's designed to do remarkably well

# THE NEW MICROCLENE MC280 & MC560

# A UNIQUE DESIGN FOR AN ALL IN ONE



IDEAL FOR WOODWORK, TURNING, CARVING, MARQUETRY, PYROGRAPHY & SCROLL SAWING,

OR ANY WORK THAT NEEDS LIGHT AND DUST REMOVAL

IDEAL FOR NAIL SALONS

FILTERS 280 & 560 M/3 OF AIR PER HOUR THERE ARE 60 BRIGHT WHITE LED'S TO PROVIDE A NICE EVEN LIGHTING SOURCE. NO HEAT FROM THE LIGHTS AND NO DANGER OF DUST BURNING. THE MC280 HAS ONE MOTOR AND THE MC560 HAS TWIN MOTORS

THE MC 280 & MC560



THE BODY IS MADE FROM STEEL THAT IS POWDER COATED FOR A LONG LIFE

VERY EFFICIENT AIRFLOW WITH LITTLE NOISE.

ONLY 48 WATTS POWER WITH FILTER AND LIGHTS ON FOR THE MC280 AND 96 WATTS FOR THE MC560 THE SIZE IS ONLY 73 X 48 X 20CM, WEIGHT IS 8.8KGS & 10KGS

A CARBON FILTER IS AVAILABLE FOR REMOVING FUMES ETC

### MADE IN ENGLAND

ACROL UK LTD WWW.ACROLLTD.CO.UK 0044 (0) 2392 502 999

# A NEW MICROCLENE AIR FILTER FROM ACROL

Acrol UK have launched the new MCP filter for pyrography or any other task that might create fumes, smoke or dust.

It has more than double the power of the current very popular MCP, with an increased airflow of over 250 cubic metres per hour through a dual EU4 grade cartridge dust filter. If that were not enough, air is then pushed through a high grade carbon filter which removes all fumes.



#### SPECIFICATIONS

Air flow through the filter 250 cubic metres per hour
Dual filter in cartridge
A white EU4 grade dust filter, down to
0.4 micron particle size. Together with high grade carbon filter for removing fumes etc.
Size 26 x 20 x 16cm, weight 5 kgs.

For more details call: (02392) 502 999 or visit the website: www.acrolltd.co.uk



# The Wood Workshop



Woodworking Courses in the beautiful Lake District

# **Woodwork Course 1**

(Tools and Things)

A self-interest woodwork course where the aim is to give you the confidence and the knowledge to use basic hand tools and some of the more common power tools.

You will be able to pick from a list of projects before you arrive that I believe you can complete in 5 days or less so that you will go home with one of them and you can proudly say "I made that".

I cover the teaching of how to handle tools by getting you started on your project and, as you need to use a new piece of equipment, I show you how. This means that the instruction is fresh in your mind and you do the task there and then.

On all courses there will only be a maximum of 4 at a time, this will mean that I will be available when you need help and advice.

# **Woodwork Course 2**

(Wood and Things)

This is a continuation of course 1 (tools and things) with the emphases on timber, what are acceptable defects in timber and what isn't, how do you write out a cutting list that means something to your supplier, what to look for when buying wood and what to avoid.

You will ideally have done course 1 (tools and things) or have a good working knowledge of how to use hand tools and have used hand held power tools.

The projects for you to pick from will be more complicated and will involve the use of the more sophisticated hand tools and hand held power tools and will include using some of the static power tools in the workshop. We will also be looking at buying timber, making cutting lists and drawing plans.

www.woodworkshop.co.uk

# Woodwork Course 3 (Things)

The advanced course is rather different from the previous two.

To come on this course you will need to have done both the other courses and have used your skill at home on your own projects and be ready to take on something more difficult.

# **WoodRat Courses**

This course will teach you all the principles that you need to know!

Visit our website for more information & updates on **2014** course information:

www.woodworkshop.co.uk

t: 01768 899895

e: enquiries@woodworkshop.co.uk

# The Wood Workshop

7-8 Redhills Business Park, Penrith, Cumbria CA11 ODT

18V cordless tools tended to be bulky and tiringly heavy to use. The latest Li-ion batteries are lighter, and compact motor design has slimmed down the machines to make them more powerful and more manageable

Makita DLX2040MJ drill/driver twin pack

£395.47



The combi's compact size rather belies its impressive performance. It is 20mm shorter than previous models, and its brushless motor is capable of providing up to twice the runtime of traditional motors. The body is extensively covered with softgrip rubber and finished in the familiar Makita blue. There is a metal keyless chuck and behind it a pair of adjustment rings. The first has 21 positions for selecting the screwdriving torque, and the second is used to select one of the three modes: screwdriving, drilling or hammer drilling.

On top of the tool is the two-position gear selector. The main handle houses the variable speed power trigger and the sliding direction-of-rotation switch. There is also an LED worklight mounted just above the trigger. The battery slides easily onto the base of the tool and a charge indicator is integrated into its mounting. There is also a clip to hold a pair of screwdriver bits on one side and a metal hanging hook on the other.

The drill is supplied with an extremely long side handle. This clamps to the nose and incorporates a depth stop for accurate drilling.

## Using the drill

This is an impressive tool to use. It feels light and well balanced, and is comfortable to hold. The side handle is a real bonus, giving excellent stability and control especially when using large-diameter





The useful hook allows you to hang the tool from a belt or pocket

makita



There's a handy stowage space on the base for a pair of screwdriver bits



The long side handle greatly improves control when drilling large holes



The compact body on the impact driver facilitates one-handed operation when appropriate

bits or holesaws. The LED light provides bright illumination and, rather handily, remains on for 10 seconds after the trigger has been released. The hanging hook is also a very useful feature, making it easy to park the tool on your belt or hang it on your pocket.

#### The impact driver

This is another compact tool. It has a short body with a locking bit holder. It also has an LED worklight and a variable speed trigger with a sliding direction-of-rotation switch. Again the body is extensively covered with softgrip rubber, and there's also a hanging hook on the end of the handle. There is no battery charge indicator.

## Using the driver

This is a wickedly powerful tool. I used it to make some car ramps using scaffolding boards and treated timber. Very long screws were needed for strength and safety, and the Makita drove them deep into the timber without hesitation, or any pre-drilling. In fact, they were so secure that it was impossible to remove them!

# Summing up

Both these machines perform faultlessly. They are powerful, convenient, well balanced, and can be charged in less than an hour. They are robust, thoughtfully designed and supplied in a sturdy storage case. There is little to criticise here. If you want a top-quality pair of professional tools, try these. **AS** 

# **SPECIFICATION**

COMBI DRILL

BATTERY		18V 4Ah Li-ion
СНИСК		13mm keyless
SPEED RANGES	0-550	0 & 0-2100rpm
MAX TORQUE		125Nm
MAX DRILLING CAPACITY	wood	76mm
	masonry	16mm
	steel	12mm
WEIGHT		2.7kg

#### IMPACT DRIVER

BATTERY	18V 4Ah Li-ion
NO-LOAD SPEED	2500rpm
IMPACT RATE	0-3200bpm
MAX TORQUE	160Nm
WEIGHT	1.5 kg

ACCESSORIES MacPac case, two batteries, charger

#### **VERDICT**

These are two remarkably powerful machines that are well made and easy to use.

**PROS** Plenty of power

Fast charging

■ Robust construction

**CONS** Not cheap!

VALUE FOR MONEY PERFORMANCE



## **FURTHER INFORMATION**

■ Makita

**01908 211678** 

www.makita.com



The LED worklight stays on for 10 seconds after the trigger is released



The short body on the impact driver allows it to fit in tight spaces



The compact yet powerful batteries slide into place easily on the base of the tool

Good though a hand-held circular saw is, a saw bench is so much better with its height-adjustable and tilting blade and cross-cutting facility, all combined with a good-sized work table

**Scheppach** HS100E table saw

These features can all be found in the recently launched Scheppach HS100E table saw, aimed primarily at the home workshop. It is constructed almost entirely of pressed steel, with the rip and mitre fences being alloy extrusions. Some simple assembly work is required, but this is straightforward enough, All the top surfaces of the three-part table are powder-coated for a long life.

# Fence performance

The rip fence will locate to either side of the blade, and is held in place by a cam lever which locks it to the rail at the front. This rail only extends along the front of the main table so the ripping width is limited, although a temporary fence could be cramped to the right-hand extension table if required.

The supporting rail is graduated, with the anchor part of the fence having a useful magnifier built in. The fence itself can be used with either the high or low edge guiding the wood, and it can also be adjusted forwards and backwards. The mitre fence too will locate to either side of the blade, and can be adjusted by up to 60° to the left and right. The fit of the fence in either of the slots is not the best, however.

### **Blade adjustment**

The blade is raised and lowered by operating the large handwheel at the front of the machine, with a second knob on the same spindle as this handwheel being used to control the tilt setting of the blade. This is up to 45° to the left only, with a protractor scale being provided as an aid to setting this angle, and a small lever to lock the setting.



The rip fence anchors firmly to the front rail and features a useful magnifier



The mitre fence can be installed to either side of the blade



The access panel is easily removed when needed for blade changing



Mitre cuts can be made at up to  $60^{\circ}$  to the left and right

#### Using the saw

Rip cuts were where I started my trials, my first cut being close to the maximum width possible using the fence. Setting this is easy, thanks to the magnifier and the cam lever. The high speed of the blade make the saw a little on the noisy side, but cutting was smooth and effortless. Thinnish material automatically raised the crown guard, allowing the wood to pass readily forwards, but with thicker pieces, a little manual help was needed to raise the guard.

Next it was on to some bevel ripping. Inevitably when the angle of tilt is at its maximum, the depth of cut is reduced, but the sawing remains just as straightforward and effective.

## Using the mitre fence

Cross cutting can take place with the mitre fence located to either side of the blade, and while the face of the fence offers good support to the wood, there is a hint of slack between the bar of the fence and both the corresponding grooves in the table. This can be countered by always adopting a slight clockwise twist to the fence and the wood as the cut is made. Because of the fairly large size of the teeth on the blade, the surfaces produced when cross cutting are less smooth than rip-sawn surfaces.

Bevel cross-cuts can also be made by keeping the mitre fence set at 90° and tilting the blade. Compound cuts can be produced by a combination of a mitre cut and a bevel cut.

## Summing up

So did the HS100E live up to expectations? I would like to see a longer front rail included, so that the fence can be operational across the right-hand table extension; this would greatly increase the ripping width. Secondly, an improved fit of the mitre fence in the table slots would promote cross-cutting accuracy.

It has to be remembered that this is a basic machine with limited refinements, aimed at the woodworker who needs a saw bench with good capacities but does not need the finest performance. GW

# **SPECIFICATION**

MOTOR		1500W
BLADE DIAMETER		254mm
NO-LOAD SPEED		2000rpm
TABLE SIZE		640 x 445mm
	with extensions	640 x 945mm
MAX DEPTH OF CUT	at 90°	75mm
	at 45°	65mm
MITRE RANGE		± 60°
WEIGHT		24.5kg

### **VERDICT**

This saw represents good value for money, and is sufficiently robust to give years of service.

- **PROS** Simple assembly
  - Easy adjustments
  - Good cutting performance
- **CONS** Front rail a little short
  - Poor fit of mitre fence in table slots

VALUE FOR MONEY **PERFORMANCE** 



### **FURTHER INFORMATION**

- NMA Agencies
- **1** 01484 400488
- www.nmatools.co.uk

Bevel cross-cutting is carried out by tilting the blade as required





Ripping was smooth, but the width is reduced by the short front rail



The maximum cutting depth is still a generous 65mm when bevel ripping



Cross-cutting can be done with the mitre fence at either side of the blade

If you do a lot of small-scale woodworking – making models or ornamental boxes, for example – you may find a standard jigsaw a little unwieldy. This compact model from Proxxon could be the answer

# Proxxon STS/E Super jigsaw



This Proxxon jigsaw has an overall length of 200mm with a 50mm diameter body. The 100W motor is not rated for continuous use and should be rested every ten minutes. The reinforced polyamide body has a strong hanging loop at the rear. Like most of Proxxon's range of similar-sized machines, this one comes in a strong plastic storage box with a fence, two Allen keys and four blades. These are not standard jigsaw blades, however, and only Proxxon spares will fit.

#### **Standard features**


The saw has a die-cast aluminium head with a small soleplate that can be tilted to the left or right and locked by means of an Allen key. The fence is secured with two screwed knobs. The soft grip on the underside makes the jigsaw very comfortable to hold.

The on/off switch and the variable speed dial are located at the top rear of machine, and are awkward to use here. It would be much better if they were at the front within easy reach of the fingers, so the saw can be turned off instantly.

### **Preventing vibration**

When you cut with any jigsaw, it's essential that the wood is cramped securely to the edge of the bench so that it overlaps slightly. If the wood is thin and the overlap too great, the material will vibrate. If you have a Workmate-type bench, you can position the wood over the centre gap and cramp each side securely. This is a safer way of cutting and greatly reduces the vibration.

There is no guard on the upper part of the blade between the



The blade is inserted into the head and locked with a small hex grub screw



The fence is secured with two screwed knobs and is held reasonably firmly



Thin workpieces must be securely cramped to the workbench to reduce vibration



Internal cuts needed fairly large entry holes to admit the saw blade

blade holder and the soleplate. One *could* be provided, whereas it's not possible to guard the part of the blade under the table. The operator needs to be aware at all times, when the machine is running, that the unguarded blade is out of sight under the work. If you use your right hand to operate the jigsaw, keep your left hand well out of the way.

### **Keeping straight**

The machine was quite difficult to use with and without the fence because there is no dust blower. It's almost impossible to follow a marked line because it quickly becomes obscured by sawdust. Any jigsaw creates sawdust, but as a mask is required the operator is unable to blow away the dust when using this machine.

The fence is held reasonably firmly, but the blade can wander and therefore a straight cut can't be guaranteed. When cutting some 4mm thick plywood, the cut was rather rough and the wood vibrated too much. It was easier to use the saw without the fence.

Some woodworkers may consider purchasing this jigsaw for cutting out shapes such as doll's house window openings. After drilling a hole in the corners of the rectangle first and making four separate cuts, the results were satisfactory but some cleaning up was necessary. The hole drilled had to be quite large for the blade to pass through.

### Summing up

The conclusion must be that, although the machine is well made and finished, this jigsaw is an example of a scaled-down version of a popular workshop tool which is not really suited to downsizing. There is little to be gained in miniaturising a jigsaw, and quite a lot to lose in stability and accuracy.

This model is presumably designed with the modeller in mind who wishes to cut thin material. It is useful to have a small machine which can easily be stored when not in use, but the high price of this tool would be much better spent on a small scrollsaw which would give a superior cut and offer greater versatility. *IW* 

# **SPECIFICATION**

MOTOR		100W
NO-LOAD SPEED	200	0-4500spm
STROKE		3mm
BASEPLATE TILT		± 45°
MAX DEPTH OF CUT	wood	12mm
	non-ferrous metal	3mm
	steel	0.5mm
WEIGHT		700g

ACCESSORIES moulded case, fence, four blades

### **VERDICT**

Disappointing: the money would be much better spent on buying a small scrollsaw.

- **PROS** Well made
  - Comfortable to hold
- **CONS** Takes only Proxxon blades
  - No dust blower
  - Awkwardly-placed controls
  - Blade tends to wander

VALUE FOR MONEY PERFORMANCE



### **FURTHER INFORMATION**

- Brimarc
- □ 03332 406967
- www.brimarc.com



Viewing the cutting line is awkward, and there is no dust blower




The saw is easier to use freehand, and cut curves satisfactorily



The on/off switch and speed control would be better sited at the front of the tool

# Thomas Flinn & Co.

Saw & Hand Tool Manufacturer Sheffield, England



The UK's last remaining traditional saw manufacturers



Now also manufacturing Clifton Planes!







Tel: 0114 2725387

orderonline@flinn-garlick-saws.co.uk

www.flinn-garlick-saws.co.uk

# FREE!

# **DREMEL MULTI-TOOL KITS**



To celebrate the launch of the improved Dremel 8200 cordless multi-tool, we're giving you the chance to get your hands on a complete kit of tools and accessories worth £145 that will help you to tackle a wide range of workshop and site jobs.

The Dremel 8200 now contains a

compact and powerful 2.0Ah 10.8V Li-ion battery, a high-power 36mm electric motor to ensure ease of cutting, a slide speed switch providing full variable speed control up to 30,000rpm, a motor brake to ensure that the accessory on the tool stops spinning immediately after switching off the tool for extra safety, an LED battery gauge to show accurate battery status, a separate on/off switch with collet lock-out function to ensure no accidental

actuation of the collet lock, EZ Twist to change accessories without a wrench, and a soft grip making the tool feel comfortable to use.

# WHAT'S IN THE KIT

The Dremel 8200-20 kit contains

- a Dremel 8200 high performance cordless multi-tool
- two 2.0Ah 10.8V Li-ion batteries
- a 30-minute charger
- 20 Dremel cutting, grinding, sanding and polishing accessories including Dremel EZ SpeedClic, all packed into a soft kit bag.

To enter, simply complete the coupon below and send it off. The first two coupons drawn from the postbag on closing day will each win a kit

## **HOW TO ENTER**

Fill in your personal details, then cut out the coupon (or photocopy it) and send it to:

# Dremel kit draw 0315

The Woodworker MyTimeMedia Ltd PO Box 269 Haslingden Rossendale Lancashire BB4 0DJ

The first two entries drawn at random will receive a kit

### The closing date for entries is 13th March 2015

Only one entry per person; multiple entries will be discarded. Employees of MyTimeMedia Ltd and the Dremel are not eligible to enter this prize draw.

Name
Address
Postcode
Daytime telephone
Mobile
Email address

Please ensure your personal details are correct, as they will be used to contact you if you win. By supplying your email/address/telephone number, you agree to receive communications from MyTimeMedia Ltd and other carefully selected third parties.

If you do NOT wish to be contacted by *The Woodworker* and MyTimeMedia Ltd, please tick he

If you do NOT wish to be contacted by *The Woodworker* and MyTimeMedia Ltd, please tick here: email 

post 

phone 

p

For our full Privacy Policy and Terms and Conditions, please go to www.getwoodworking.com

# TIMBER SUPPLIES & SPECIALIST EOUIPMENT





TEWKESBURY SAW COMPANY LTD

# Spindle Moulder Cutters & Limiters

Made to Order!

- Quick turnaround
   Able to supply to fit most types of blocks
  - Many low priced standards from stock

**Tewkesbury Saw Co. Ltd.** 

Newton Trading Est. Tewkesbury, Glos. GL20 8JG Tel: 01684 293092 Fax: 01684 850628 www.tewkesburysaw.co.uk

# Allan Calder's Ltd Sandpaper Supplies

Unit 2B, Churnet Works, James Brindley Road, Leek, Staffordshire ST13 8YH.



We are supplying top quality brands of sanding abrasives for all types of Wood Turners, Joiners & Cabinet Makers.

Web: www.sandpapersupplies.co.uk

email: sandpapersupplies@yahoo.co.uk

Tel: 01538 387738

# SURREY TIMBERS Ltd

Your One-Stop Wood Shop

Hardwood Timber Merchant stocking local & Imported Timber



Please come & select from our range:

OAK, YEW, WALNUT, SAPELE, APPLE, MAPLE, SYCAMORE & More!

• Woodturners • Joiners, • Cabinetmakers Call in and see our huge range at: Loseley Park, Guildford GU3 1HS

01483 457826 or 07795 663792 www.surreytimbers.co.uk

# Unloved? Unuseable? RESTORE IT!



Stanley No.5 'before & after' photo courtesy Peter Hemsley - The ToolPost

Restore Rust Remover & Restore Rust Remover Gel Remove <u>only</u> the rust leaving sound metal unaffected. Cleans and brightens brass and nickel plating. See more stunning 'before & after' examples on our website photo

stunning 'before & after' examples on our website photo galleries. Find local and international stockists on the website.

Shield Technology Limited. Unit 69, Grimsby Business Centre King Edward Street, Grimsby, DN31 3JH Tel: +44 (0)1472 360699 Fax: +44 (0)1472 324685 Email: info@shieldtechnology.co.uk www.shieldtechnology.co.uk

Distributor enquiries welcome

SHIELD TECHNOLOGY
Guarding Against Corrosion

# WOOD SUPPLIES/FINISHES, TOOLS & SPECIALIST EQUIPMENT

# Scawton Sawmill Ltd

Hardwoods Supplier





Soft Close Drawer Runners - Concealed - Easy Fit - Quick Release - Full Extension

Lengths from 300mm to 500mm available— From £13.00 a Pair inc. Free Fast Delivery

www.scawtonsawmill.co.uk - 01845 597733 - info@scawtonsawmill.co.uk

# **Dowelmax**

The ultimate doweling jig for furniture makers

Brings production technology to the small shop "Fast, accurate and a joy to use, a superb tool"

Visit: www.dowelmax.co.uk

or telephone: 01352781168 • 07773718758

Dowelmax Classic Metric and Junior Metric in stock



# TOOLS WANTED

Top Prices Paid For Quality Hand Tools carving tools, chisels, turning tools

norris planes (and similar), metal planes green tools, any nice old hand tools...


email photos to: info@oldtools.co.uk or bring tools to: Bexhill - 01424 217893





# WOOD SUPPLIES/FINISHES & SPECIALIST EQUIPMENT





# Scawton Sawmill Ltd

Hardwoods Supplier







Kiln Dried Oak - Air Dried Oak - Green Oak - Cherry

Nationwide Delivery - 20mm to 100mm - Oak Boards, Oak Beams, Oak Sleepers

 $www.scawtonsawmill.co.uk - 01845\ 597733 - info@scawtonsawmill.co.uk$ 

# STEPCRAFT

BECOME AN EXPERT

Fast, accurate and simple fabrication of your parts.

1 machine - 1000 possibilities!



www.stepcraft-systems.com

distributed exclusively by

**STONEYCNC** 

Happy to help at all times: info@stoneycnc.co.uk

+44 (0) 1432 607 908

# INCHMARTINE TOOL BAZAAR

Visit our successful website for constantly changing tools for sale

www.toolbazaar.co.uk





Sole Propriator: Mr Andrew Stephens



THE LEADING SUPPLIERS OF ANTIQUE AND QUALITY OLD WOODWORKING TOOLS FOR BOTH CRAFTSMEN AND COLLECTORS IN THE COUNTRY

# BRAND NEW WEBSITE NOW LAUNCHED

THE MILL ROOM, RAIT ANTIQUE CENTRE, RAIT, PERTHSHIRE PH2 7RT

> Tel: 01821 670770. Mobile: 07734 345652

E-mail: toolbazaar@googlemail.com



# Maintains the natural colour of the wood and limits the greying process

- > Prolongs wood lifetime
- > Algae and fungal decay protection
- > Transparent 425 Oak finish and 428 Cedar finish now available



Call or visit the web for stockists.

+44 (0)1296 481 220 www.osmouk.com





### **SHOP GUIDES**

MAIL ORDER NARROW BANDSAW BLADES MANUFACTURED TO **ANY LENGTH** PHONE NOW FOR QUOTATION **OR PRICE LIST** 

# TRUCUT

Spurside Saw Works, The Downs, Ross-On-Wye, Herefordshire HR9 7TJ www.trucutbandsaws.co.uk

Tel: 01989 769371 Fax: 01989 567360

## TOP QUALITY - LOW PRICES VSM - VITEX ABRASIVES

KK532F Starter Pack (4 Metres) £12.95 inc. VAT and UK post. 1/2 metre each of grits 80, 120, 150, 180, 240 320, 400, 600 Also the NEW \* GRIP - A - DISC \*

Power Sanding/Finishing System

Plus lots of Belts, Discs, Stars, Low cost KK114 We also stock WOODTURNERS SUPPLIES Timber/Bowl Blanks/Tools/Waxes/Finishes Glues/Chucks/Glassware/Cutlery/Sundries.

SAE FOR CATALOGUE Jill Piers Woodturning Supplies 2 Kimberley Villas, Southmill Road, BISHOPS STORTFORD, HERTS CM2 33DW Tel/Fax: 01279 653760

## BERKSHIRE

# WOKINGHAM TOOL COMPANY LTD

97-99 Wokingham Road Reading, Berkshire RG6 1LH Tel: 0118 966 1511

www.wokinghamtools.co.uk

H. P. W. CS. BS. A. D. MO.

### LEEDS

## **D.B. KEIGHLEY MACHINERY LTD**

Vickers Pleace, Stanningley, Leeds, LS28 6LZ Tel: (0113) 257 4736 Fax: (0113) 257 4293 www.dbkeighley.co.uk P. A. CS. BC. MO.





# **WEB GUIDE**





# MUSICAL INSTRUMENT MAKERS

Musical Instrument Makers' & Repairers' Supplies

TOUGHSTFORE THOMEWOODS

Largest selection of tonewoods, tools & parts in the country. Visit our website or order our catalogue. Callers welcome

Touchstone Tonewoods, Albert Road North, Reigate, RH29EZ Tel: 01737 221064 Fax: 01737 242748 www.touchstonetonewoods.co.uk

# **CLOCKS**

# **Woodworking Materials** Large selection of products!

 Clocks & Accessories (Quartz and Mechanical) ✓ Barometers ✓ Thermometers

✓ Cabinet furniture ✓ Screws ✓ Plans ✓ Kits

✓ Polishes ✓ Adhesives ✓ Abrasives etc.

For FREE catalogue please contact:

Chris Milner Woodworking Supplies (Dept.TW) Beresford Lane, Woolley Moor, Nr. Alfreton Derbyshire DE55 6FH Tel/fax: (01246) 590 062

Email: milnerwoodwork@aol.com

HERMLE / KIENINGER MECHANICAL **CLOCK WORKS. DELIVERED EX STOCK** Retirement Sale - All prices reduced Martin H Dunn Ltd

The Clock Gallery Clarkes Road, Killingholme, North Lincolnshire DN40 3J0 www.martinhdunn.co.uk FREE PRINTED CATALOGUE m Open Mon- Fri 10am - 5pm. Sat 10am Tel: 01469 540901





# **DIAMOND SHARPENING & CHAINSAW DISCS**



# RKEIPLA

Our FREE classified advertisement service

Send or email a photograph of your item and we'll include it with your ad for FREE!

# FOR SALE



Shopsmith Mark V plus bandsaw and planer, little used so in very good condition, can be dismantled for transport; £750.

01536 771455 (Leics/Northants)

DeWalt 678 planer, 82mm cutter, 25mm rebate, with spare blades, little used so as-new condition; £60. Buyer collects

01294 673236 (Ayrshire)



Stanley Bridges 1960s XK/ **SA 300W sander**. 97 x 218mm baseplate, hardly used, some paint scratches, scuff marks, but in full working order; £20.

07881 914323 (Hampshire)

Bosch table saw, 240V model GTS10; £320.

020 8248 0335 (West London)

Hollow mortiser chisels, set of 8, 10 and 12mm sizes with 3/4in shanks, boxed and as new; £18. Hollow mortise chisel sharpener set (Multico No 1/539), in good condition; £18. Each price includes p&p.

0161 220 8511 (Manchester)



Makita LXT kit, 18V Li-ion, including hammer drill driver, impact driver, circular saw, reciprocating saw, iigsaw, angle grinder and torch, with manuals and storage bag; £400.

01322 386204 or 07592 590436 (North Kent)



Woodworker magazines, over 100 individual issues dating back to 1924, full of fascinating articles. Offers please.

07747 868740 (Oxfordshire)

Kity 419 table saw with 200mm rip and cross-cut blades, extension tables and stand, in good condition; £225. Buyer collects.

01926 313787 (Warwickshire)

Triton router/jigsaw stand complete with overhead routing attachment and instruction manual, new and unused; £75.

01526 388685 (Lincolnshire)

Woodworker Annuals, complete set of 45 volumes from 1930 to 1974, most with original dust iackets: offers please.

01547 529305 (Powys)

**Exocet woodturning tool**, unhandled, in manufacturer's box

with instructions; £75.

01526 388685 (Lincolnshire)

Myford planer thicknesser, cast iron, 5in wide with three cutters; £100 ono.

01395 263218 (South-east Devon)

Storage cabinet, partially restored, with plywood frame, solid wood drawers and brass handles; £70. Buver collects.

01977 647675 (West Yorkshire)

English hardwoods, seasoned woodturner's surplus – planks, logs, squares and discs. Please call for details or inspection. Buyer collects. 01400 282690 (Lincolnshire)

Yew: 15cu ft planed and cube offcuts; widths 4 to 9in, thicknesses 1, 11/4 and 21/8in; £480. Buyer collects.

01723 360340 (Yorkshire)

Hollow chisel mortiser, model Sedgwick 571, lightly used; £650. Woodrat WR900 in first-class condition with cutters, dust control and full instructions: £250.

01865 858241 (Oxfordshire)

# **WANTED**

Woodworker magazines, pre-1951 plus 1984-1986. Grandfather collecting for cabinetmaker grandson.

01493 368180 (Norfolk)

Spiers / Norris / Henley planes wanted by private collector; any quote beaten. Ring Ron Lowe on 01530 834581 (Leics)

Woodworking hand tools, especially old wood and metal

planes, wanted by collector. Write to Mr B Jackson, 10 Ayr Close, Stamford PE9 2TS or call

01780 751768 (Lincs)

Woodworking tools: planes by Norris, Spiers, Mathieson, Preston, Slater etc, brass braces, interesting rules and spirit levels; top prices paid, auction prices beaten. 01647 432841 (Devon)

# USE THIS FORM TO BOOK YOUR FREE AD



- This space is available only to private individuals wishing to buy or sell woodworking machinery and tools.
- The maximum value of any item for sale must not exceed £500. A small fee is payable for items offered at over £500; please ring 01689 869852 for details.
- Each coupon is valid for one free insertion in the next available issue.

•	The	publisher	accepts no	responsibility	for	errors	or	omissions	in	this	sectio
---	-----	-----------	------------	----------------	-----	--------	----	-----------	----	------	--------

Name		
Address		
Postcode	Daytime tel no	
Signature		

Please	publish	this	adver	tiseme	nt in	the	next	availa	ıble e	edition	ı of	
The Wo	oodwork	er. I	am a	orivate a	adver	tiser	and I	have n	o trac	de con	nectio	ns

The Woodworker. I	I am a private	advertiser	and have	no trade	connections

My advertisement (max 20 words please) reads as follows:

PLEASE TICK: FOR SALE WANTED

# In your own write...

Here are just a few of the latest letters we've received since the last issue. Drop us a line on paper or via screen and keyboard to add your voice to the woodworking crowd; you might be one of the lucky few who will manage to get their hands on a coveted *Woodworker* badge!

#### **SNAIL MAIL OR EMAIL?**

You can write to us at The Woodworker, MyTime Media Ltd, Enterprise House, Enterprise Way, Edenbridge, Kent, TN8 6HF or send an email to mark.cass@mytimemedia.com





# **IMPERIAL RETURNS**

Dear Mark

I bought these 1in No 8 screws the other day from a well-known supplier on an industrial estate near where I live. I was amused to see that they have recently started putting Imperial sizes back onto their boxes after a very long absence. Does any other reader find this peculiar?

Keep up the good work, I'm currently making a pair of small tables like the ones you had in the magazine not long ago.
Regards

# **Charles Bennet, Guildford**

That's funny, Charles. It seems like a bit of a backwards step to me. I occasionally hear of 'eights' and 'tens' when I'm on site, but most tradies I know are very comfortable with metric fixings. One thing's for sure though: we can't blame Brussels for this one!

# A BETTER BACK

Hi Mark

I read your pages avidly to find new ways of making dust out of good timber, and I hope you can help to guide me with my latest challenge. We've rearranged our bedroom so that the backs of the Ikea wardrobes are now visible. Obviously the hardboard back panels need to be replaced by something more attractive, and, as they are no longer supported by a wall, they need to be made more rigid too. My dilemma concerns the edges. If I use thicker material, it will show where it exceeds the depth of the rebate. Can you or your readers suggest a solution?

#### **Dave Cross**

This is quite a good question, Dave. If you were to go ahead and simply replace the hardboard backs with a thicker board, as long as it was a perfect fit into the rebate it wouldn't look too bad.

If the existing back panels are flush with the sides, you could just plant a new back on and make a feature of it, but the only way of really hiding the edges of the new, thicker back would be to deepen the existing rebate to match the thickness of the chosen board. You'd still have the raw carcass edges to deal with, though. Tricky... If anyone out there has a better solution for this problem, please let us know!

Mark

# **PEEL AND STICK**

Dear Sir

I wonder if you could help me with a problem. I have a wardrobe door covered in a plastic veneer which has started to delaminate. The door is made from mdf with trenched mouldings and rounded-over edges. These are also lifting. Could you please recommend a suitable adhesive which I could use to refix the veneer to the mdf? I am not sure about using pva adhesive. Yours in anticipation

### K Dawson

This type of door is described as being 'foiled'. This means it's moulded in one piece with a very thin layer of plastic laminate as an outer skin. This can look good when new, but it has a limited lifespan. You need a glue that will stick plastic to mdf, and fortunately there are a few contenders.


I'd avoid superglue; it would likely do the job but it will probably end in tears. On a bigger job, an impact or contact adhesive would do the trick, but you'll be working it into gaps on edges and so that's not suitable either.

I think your best bet will be one of the many all-purpose glues that come in a small tube with a fine nozzle to help you apply the glue where it's needed. After you've squeezed enough in, use masking tape to hold the edges down and leave it overnight to be on the safe side. You can then trim off any squeezed-out glue with a sharp knife. Good luck!

Mark

# Submarine Commander


Some of you may recall an electro-mechanical slot machine of this name in the amusement arcades at the end of the pier on childhood seaside holidays. With its realistic periscope viewer, dramatic tension and spectacular effects when you finally 'sank' one of the ships on the distant horizon, it was a hit with everyone... including me





TORPEDO-FIRING SUBMARINE

EXPLODING

Leafing through a copy of The Woodworker from July 1964 (the mid-sixties are fast becoming one of my favourite Woodworker eras), I came across a couple of pages dedicated to this Torpedo-Firing Submarine. Now, there's nothing like a toy that fires some kind of projectile, and this one appealed instantly to the child in me (actually quite a sizeable child, if the truth be known). It soon became clear that the submarine project (possibly known as Operation Poseidon)







was a response to eager reader requests for an adversary for the Exploding Destroyer published earlier in the year in the March issue.

# **Battle stations**

A few intense minutes of frantic searching in the dusty Woodworker archives located the aptly-named Handicraft Teacher's Page, and I was soon reading with interest a similar article showing just how one could go about building a model ship which would 'explode' when cleanly struck amidships. Interestingly, the project was introduced by its writer as similar to something he had been given as a boy over 40 years earlier, dating the original

warship to just after World War 1.

The 'shipwright', Mr E F Scott, went on to inform us that his present classes of boys were still greatly interested, and I strongly suspect that even now, these simple toys would have a surprising amount of appeal to youngsters today.

## **Springing into action**

Both of the vessels are simply constructed from scraps, offcuts, bits of dowel and most importantly - a spring or two, notably a letterbox spring inside the warship to lift the superstructure of this doomed destroyer. I'm seriously tempted to make my own

variations of this brace of battlers. It would be good to be able to even things up a bit and make the submarine 'sinkable', but at present, and short of some kind of depthcharge addition, I can't think of how to do it. So, if there are any nautical types reading this who have an idea or two of what might be done, I'd love to hear from you. Maybe we could do battle together!

More from The Woodworker archive next month...





Big on Performance -Easy on the Budget.





01908 635000

**Call now for more information** 

HAMMER - A range of over 20 machines for the keen and professional woodworker.

# **FELDER-GROUP UK**

Unit 2, Sovereign Business Park, Joplin Court Crownhill, MK8 0JP MILTON KEYNES

www.ukhammer.co.uk

# X-LIFE

Long-lasting precision with ceramic guides

Ceramic guides guarantee excellent cutting results and maximum blade stability with four guiding blocks positioned directly on the saw blade. The flat surface ensures reduced noise emissions and considerably less friction resistance.

Can be retrofitted to every Felder (FB 510, FB 610) and Hammer (N3800, N4400) bandsaw



# The PT260 Planer Thicknesser. Same Great Machine, New Lower Price.

The PT260 needs little introduction, having found its way into countless workshops over the past decade. Its capacities, build quality and reliability make it the obvious choice for the discerning woodworker.

# What They Say...



# The Woodworker

"I fed some 180 mm wide pine through the thicknesser at a 2 mm depth of cut, getting excellent results without straining the motor...it's useful to know the Record will cope. For it's price the Record is excellent value."

# **Good Woodworking**

"At an overall length of one metre the tables are ideal and they are remarkably accurate as well. My straight edge showed no significant discrepancy over the whole length - something other major manufacturers should learn from... a very capable machine."

# **Practical Woodworking**

# PT260-PK/A PT260 & CX2000

Fackage Deal **£699**.95

Price valid until 28.02.2015. E&OE.





Still only £599.99 Inc. VAT







Experience • Knowledge Support • Expertise STARTRITE

CORONET

BURGESS

Incorporating some of the most famous brands in woodworking, Record Power have been manufacturing fine tools & machinery for over 100 years. Built to last we provide support for thousands of machines well over 50 years old, which are still in daily use. Testimony to the sound engineering principles and service support that comes with a Record Power product.